

**ODISHA POWER GENERATION**  
**CORPORATION LIMITED**

**2 X 660 MW, SUPER-CRITICAL TPS,**  
**UNIT # 3 & 4**  
**AT**  
**JHARSUGUDA, ODISHA**

TECHNICAL SPECIFICATION  
FOR  
AUXILIARY STEAM PRESSURE REDUCING  
AND DESUPERHEATING STATION  
ALONGWITH ACCESSORIES

SPECIFICATION No: PE-TS -391-142-N101 (REV 00)



BHARAT HEAVY ELECTRICALS LIMITED  
POWER SECTOR  
PROJECT ENGINEERING MANAGEMENT  
PPEI, NOIDA, INDIA

**ODISHA POWER GENERATION**  
**CORPORATION LIMITED**

**2 X 660 MW, SUPER-CRITICAL TPS,**  
**UNIT # 3 & 4**  
**AT**  
**JHARSUGUDA, ODISHA**

TECHNICAL SPECIFICATION  
FOR  
AUXILIARY STEAM PRESSURE REDUCING  
AND DESUPERHEATING STATION  
ALONGWITH ACCESSORIES

**VOLUME - II B**

**SPECIFICATION No: PE-TS -391-142-N101 (REV 00)**



BHARAT HEAVY ELECTRICALS LIMITED  
POWER SECTOR  
PROJECT ENGINEERING MANAGEMENT  
PPEI, NOIDA, INDIA



TITLE

**PREAMBLE**SPECIFICATION NO **PE-SS-999-100-Q-001**VOLUME **II B**SECTION **PREAMBLE**REV NO. **0** DATE 05.02.2008

SHEET 1 OF 1

**1.0 Volume – II B :**

This volume is sub- divided into following sections: -

Section – A : This section outlines the scope of enquiry

Section – B : This section provides : “ Project Information”.


Section- C : This section indicates tech. Requirements specific to the contract, not covered in Section – D.

Section – D : This section comprises of tech. Specifications of equipments complete with data sheet A,B&C.

Data Sheet – A specifics data and other requirements pertaining to the equipment.


Data sheet – B specifics data to be filled by the bidder (Data Sheet B is contained in Volume – III.

Data Sheet – C indicates data/ documents to be furnished after the award of contract as per agreed schedule by the vendor (as applicable).

|   |  |                               |                 |
|---|--|-------------------------------|-----------------|
|  | <b>TITLE</b><br><br><b>AUXILIARY STEAM PRESSURE REDUCING<br/>&amp; DESUPERHEATING STATION</b><br><br><b>OPGCL - 2 x 660 MW, IB TPS, Unit # 3 &amp; 4 at<br/>Jharsuguda, Odisha</b> | SPEC. NO.: PE-TS-391-142-N101 |                 |
|   |  | VOLUME <b>II-B</b>            |                 |
|   |  | SECTION <b>CONTENTS</b>       |                 |
|   |  | REV NO. <b>0</b>              | DATE 05.07.2014 |
|   |  | SHEET 1 OF 2                  |                 |

### CONTENTS

| <u>SECTION</u>   | <u>TITLE</u>  | <u>SPECIFICATION NO</u> | <u>NO. OF SHEETS</u> |
|------------------|---|-------------------------|----------------------|
| <b>Section-A</b> | <b>Scope of enquiry</b>   |                         | 3                    |
| <b>Section-B</b> | <b>Project Information<br/>OPGCL - 2x660 BANHARPALLI</b>                      |                         | 3                    |
| <b>Section-C</b> | Specific Technical Requirements   |                         | 20                   |
| 1.00             | Brief System Description  |                         |                      |
| 2.0.0            | Equipment to be provided by tenderer  |                         |                      |
| 3.0.0            | Specific technical requirements for control valves                            |                         |                      |
| 4.0.0            | Information to be furnished along with the offer by bidder                    |                         |                      |
| 5.0.0 Spares     |   |                         |                      |
| 6.0.0            | Information to be furnished along with the offer by bidder                    |                         |                      |
| 7.00 Drawing     |   |                         |                      |
| 8.00 Quality     | Plan  |                         |                      |
| Data Sheet - A 1 | Sizing Data For High Capacity Aux. Steam PRDS (Combined type ASV-22, CDV-151) |                         |                      |
| Data Sheet - A 2 | Sizing Data For Aux. Steam PRDS (ASV-26)                                      |                         |                      |
| Data Sheet - A 3 | Sizing Data For Low Temp. Desh (CDV-157 & DESH-2)                             |                         |                      |
| Data Sheet - A 4 | Sizing Data For TGS Desuperheater & Spray Control Valve (DESH-3 & CDV-93)     |                         |                      |

|   |  |                               |                 |
|---|--|-------------------------------|-----------------|
|  | <b>TITLE</b><br><br><b>AUXILIARY STEAM PRESSURE REDUCING<br/>&amp; DESUPERHEATING STATION</b><br><br><b>OPGCL - 2 x 660 MW, IB TPS, Unit # 3 &amp; 4 at<br/>Jharsuguda, Odisha</b> | SPEC. NO.: PE-TS-391-142-N101 |                 |
|   |  | VOLUME <b>II-B</b>            |                 |
|   |  | SECTION <b>CONTENTS</b>       |                 |
|   |  | REV NO. <b>0</b>              | DATE 05.07.2014 |
|   |  | SHEET 2 OF 2                  |                 |

| <u>SECTION</u>                | <u>TITLE</u>   | <u>SPECIFICATION/<br/>DRG/DOC NO</u> | <u>NO. OF<br/>SHEETS</u> |
|-------------------------------|--|--------------------------------------|--------------------------|
| Section D                     | <b>Equipment Specification</b><br>Specification For Control Valve<br>(With Pneumatic Actuator<br>(SMART))                        | PES – 145 - 06                       | 12 + 4                   |
| <b>Data Sheet<br/>A&amp;B</b> | Data Sheet For Control Valves (With<br>Pneumatic Actuator) for tag nos.<br>ASV-22,<br>ASV-26,<br>CDV-151,<br>CDV-157 &<br>CDV-93 |                                      | 13                       |
|                               | Data Sheet For Control Valves<br>(With Pneumatic Actuator)<br>Common for all Control Valves                                      |                                      |                          |
|                               | <b>Equipment Specification</b><br>Steam Desuperheater  | PES-148-01                           | 3                        |
| <b>Data Sheet –A1</b>         | Data for DesuperHeater DESH-2  |                                      | 1                        |
| <b>Data Sheet –A2</b>         | Data for DesuperHeater DESH-3  |                                      | 1                        |
| <b>Data Sheet C</b>           | List of Documents and Data to be<br>Submitted after Award of Contract  |                                      | 1                        |
| <b>Quality Plan</b>           | Quality Plan for Control Valve   |                                      | 5                        |
|                               | Quality Plan for Steam<br>DeSuperheater  |                                      | 2                        |
| <b>Tender<br/>Drawings</b>    | Auxiliary Pr. Reducing and<br>DeSuperHeating Station   | PE-DG-391-142-N101                   | 1                        |

FILLED-UP QUALITY PLAN AS MINIMUM REQUIREMENTS IS INCLUDED  
FOR CONTROL VALVE & STEAM DESUPERHEATER.



TITLE


**SCOPE OF ENQUIRY****AUXILIARY STEAM PRESSURE REDUCING  
& DESUPERHEATING STATION****FOR  
OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at  
Jharsuguda, Odisha**

SPEC. NO.: PE-TS-392-142-N101

VOLUME **IIB**SECTION **A**REV NO. **00** DATE 05.07.14

SHEET 1 OF 3

**SECTION – A****SCOPE OF ENQUIRY**


|   |   |                               |               |
|---|---|-------------------------------|---------------|
|  | <p>TITLE</p> <p><b>SCOPE OF ENQUIRY</b></p> <p><b>AUXILIARY STEAM PRESSURE REDUCING &amp; DESUPERHEATING STATION</b></p> <p><b>FOR</b></p> <p><b>OPGCL - 2 x 660 MW, IB TPS, Unit # 3 &amp; 4 at Jharsuguda, Odisha</b></p> | SPEC. NO.: PE-TS-392-142-N101 |               |
|   |   | VOLUME <b>IIB</b>             |               |
|   |   | SECTION <b>A</b>              |               |
|   |   | REV NO. <b>00</b>             | DATE 05.07.14 |
|   |   | SHEET <b>2</b>                | OF <b>3</b>   |

- 1.1 This enquiry covers the Design, Manufacture, Assembly, Inspection and Testing at Vendor's and/or his sub-vendors works, painting and delivery to site of Auxiliary Steam Pressure Reducing & Desuperheating Stations, as mentioned in different sections of this specification for OPGCL – 2X660 MW JHARSUGUDA, ODISHA UNIT-3/4.

The tenderer shall also quote separately for the following:-

- a) Supervision of erection & commissioning of the equipment, if applicable.
  - b) Recommended spares for 3 years of post guarantee period operation.
- 1.2 It is not the intent to specify herein all the details of design and manufacture. However, the equipment shall conform in all respects to high standards of design, engineering and workmanship and shall be capable of performing the required duties in a manner acceptable to the Engineer/Owner who will interpret the meaning of drawings and specifications and shall be entitled to reject any work or material, which in his judgment is not in full accordance herewith.
- 1.3 The bidder may quote for his standard, proven design of equipment and shall indicate any deviations from this specification in the enclosed schedule. **In the absence of duly filled deviation schedule, it shall be presumed that the offer confirms exactly to this specification.** The bidder shall also furnish the performance feedback data of the equipment from similar installations. However, the acceptance of the deviations/options is not binding on the Engineer/Owner.
- 1.4 The bids shall be in English language and MKS Units.
- 1.5 Filled up quality Plans as minimum technical requirements, are included in this specification in Vol. IIB Sec D. Bidder is required to submit the enclosed Quality Plan, or bring out specific deviations on it, while submitting the bid.
- 1.6 Similar to Quality Plan, Bidder is required to furnish Field Quality Plan (FQP), if applicable. FQP shall indicate all inspection/test to be carried out at site covering the following:
- i). Receipt of material.
  - ii). Storage or Conservation.
  - iii). Pre-Erection & Erection
  - iv). Pre-Commissioning, commissioning & post commissioning.

FQP shall furnish adequate instructions to be followed by erection & commissioning agency at site.

|   |   |                               |               |
|---|---|-------------------------------|---------------|
|    | <b>TITLE</b><br><br><b>SCOPE OF ENQUIRY</b><br><br><b>AUXILIARY STEAM PRESSURE REDUCING<br/>&amp; DESUPERHEATING STATION</b><br><br><b>FOR</b><br><b>OPGCL - 2 x 660 MW, IB TPS, Unit # 3 &amp; 4 at<br/>Jharsuguda, Odisha</b> | SPEC. NO.: PE-TS-392-142-N101 |               |
|   |   | VOLUME <b>IIB</b>             |               |
|   |   | SECTION <b>A</b>              |               |
|   |   | REV NO. <b>00</b>             | DATE 05.07.14 |
|   |   | SHEET <b>3</b>                | OF <b>3</b>   |
| <p>Bidder is requested to refer standard no PE S-100-918 on field quality plan enclosed in Volume III of this specification.</p> <p>1.7 The omission of specific reference to any component / accessory necessary for the proper performance of the equipments shall not relieve the supplier of the responsibility of providing such facilities to complete the supply within the quoted prices.</p> <p>1.8 BHEL's / OPGCL's representatives shall be given access to the shop in which the equipments are being manufactured or tested and all test records shall be made available to him.</p> <p>1.9 The Equipment covered under this specification shall not be dispatched unless the same have been finally inspected, accepted and Material Dispatch Clearance Certificate (MDCC) is issued by BHEL / OPGCL.</p> |   |                               |               |





TITLE

**PROJECT INFORMATION****AUXILIARY STEAM PRESSURE REDUCING  
& DESUPERHEATING STATION****OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at  
Jharsuguda, Odisha**

SPEC. NO.: PE-TS-391-142-N101

VOLUME **II-B**


SECTION B

REV NO. **00**


DATE 17.07.2014

SHEET 1 OF 3


**SECTION – B****PROJECT INFORMATION**

|   |   |   |   |
|---|---|---|---|
|  | <b>Odisha Power Generation Corporation Ltd.</b> | <b>Technical Specification for Main Plant Package</b> | <b>IB TPS – 2 X 660 MW Units 3 &amp;4, Jharsuguda, Odisha</b> |
|---|---|---|---|

## CONTENT

| CLAUSE NO.   | DESCRIPTION         | PAGE NO.        |
|--|---------------------|-----------------|
| 1.00.00  | INTRODUCTION        | V.IIA/S-III : 1 |
| 2.00.00  | APPROACH TO SITE    | V.IIA/S-III : 1 |
| 3.00.00  | LAND                | V.IIA/S-III : 1 |
|  |                     |                 |
| 7.00.00  | METEOROLOGICAL DATA | V.IIA/S-III : 2 |



|   |  |  |   |
|---|--|--|---|
|  | Odisha Power Generation Corporation Ltd. | Technical Specification for Main Plant Package | IB TPS – 2 X 660 MW Units 3 & 4, Jharsuguda, Odisha |
|---|--|--|---|

## VOLUME : IIA

### SECTION-III

#### PROJECT SYNOPSIS AND GENERAL INFORMATION

##### 1.00.00 INTRODUCTION

The proposed Thermal Power Station comprising of 2 x 660 MW base unit size, Super-Critical Units would be set up by Odisha Power Generation Corporation Limited (OPGCL) in the Jharsuguda district of Odisha, India. OPGCL had already installed two units of 210 MW each adjacent to the proposed units under Phase-I of the project at IB Thermal Power Station and the units have been working for the last fifteen years.

Seller has acquainted himself by visiting to the site, with the conditions prevailing at site. The information given here in under is for general guidance and shall not be contractually binding on the Buyer. All relevant site data /information as may be necessary shall have to be obtained/ collected by the Seller.

##### 2.00.00 APPROACH TO SITE

The project site is located at Banaharpalli in the Jharsuguda district of Odisha on the bank of Hirakud Reservoir and about 20 km south of Belpahar railway station and 40 km south west of Jharsuguda. The main Howrah-Mumbai railway line passes 20 km north of the plant (at Belpahar). NH-200 (Chandikhole to Raipur) and SH-10 (Sambalpur to Sundergarh) pass through Jharsuguda town.

OPGCL has a private railway siding connecting the plant to the Indian Railways network at Lajkura Railway station.

Nearest Airport – Bhubaneswar.

Nearest Seaport – Paradeep/ Haldia.

##### 3.00.00 LAND


The total land proposed to be required (around 40 Ha) taking into account the locations of various facilities and plant auxiliaries for units 3 & 4 under IB Thermal Power Station 2 x 660 MW units 3 & 4 and also future 2 x 660 MW will be as per the Plot Plan enclosed in Volume II-L. Land for the proposed units have already been acquired and Power block area is fairly flat land sloping towards South to South -West with contour variation from RL 204.00 M to RL 199.00 M. The Seller shall accommodate equipment offered under this specification generally within the spaces allocated for such equipment in the Plot Plan. Specific approval from Consultant shall be taken by the Seller prior to any revision or relocation.




|                               |                 |                                   |
|-------------------------------|-----------------|-----------------------------------|
| Doc. No. : K8B09-MP-SPC-G-001 | V.IIA/S-III : 1 | Development Consultants Pvt. Ltd. |
|-------------------------------|-----------------|-----------------------------------|

(2. K8B09-MP-V-II-A-LEA1\_OPGC\_CONTRACT-BHEL.docx)



|   |  |  |  |
|---|--|--|--|
|  | Odisha Power Generation Corporation Ltd. | Technical Specification for Main Plant Package | IB TPS – 2 X 660 MW Units 3 &4, Jharsuguda, Odisha |
|---|--|--|--|



#### 7.00.00 **METEOROLOGICAL DATA**


7.01.00 For the purpose of equipment design, the following Ambient Conditions / Meteorological data of site (Jharsuguda) shall be taken into consideration:-

|                            |   |  |
|----------------------------|---|--|
| Site elevation above MSL   | : | 199.5 M  |
| Highest temp recorded      | : | 48.0 °C.   |
| Lowest temp recorded       | : | 4.0 °C.  |
| Monthly max. dry bulb temp | : | 38.9 °C/28.0 °C/33.4 °C<br>(Summer/winter/monsoon) |



|                               |                 |                                   |
|-------------------------------|-----------------|-----------------------------------|
| Doc. No. : K8B09-MP-SPC-G-001 | V.IIA/S-III : 2 | Development Consultants Pvt. Ltd. |
|-------------------------------|-----------------|-----------------------------------|

(2. K8B09-MP-V-II-A-LEA1\_OPGC\_CONTRACT-BHEL.docx)

|   |  |  |  |
|---|--|--|--|
|  | Odisha Power Generation Corporation Ltd. | Technical Specification for Main Plant Package | IB TPS – 2 X 660 MW Units 3 &4, Jharsuguda, Odisha |
|---|--|--|--|

|   |   |  |
|---|---|--|
| Monthly min. dry bulb temp  | : | 25.4 °C/16.7 °C/26.8 °C<br>(Summer/winter/monsoon) |
| Monthly max. wet bulb temp  | : | 23.9 °C/17.8 °C/25.5 °C<br>(Summer/winter/monsoon) |
| Monthly min. wet bulb temp  | : | 17.6 °C/13.4 °C/25.0 °C<br>(Summer/winter/monsoon) |
| Maximum Relative Humidity   | : | 46% / 67% / 87%<br>(Summer/winter/monsoon)         |
| Minimum Relative Humidity   | : | 21% / 33% / 87%<br>(Summer/winter/monsoon)         |
| Average relative Humidity   | : | 65%  |
| Average Annual Rainfall   | : | 1460 mm.   |
| Normal period of rain fall  | : | June – September.                                  |
| Heaviest rainfall in 24 hours   | : | 257.8 mm   |
| Wind direction  | : | South West – North East.                           |
| Basic Wind Speed at 10 m Height   | : | 44 m/sec as per IS:875 Part-3 (1987).              |
| Seismic Zone  | : | Zone III as per IS:1893 Part-1 (2002).             |
| Geographical location : At Latitude 21° 48' North and Longitude 83° 52' East. |   |  |



|                               |                 |                                   |
|-------------------------------|-----------------|-----------------------------------|
| Doc. No. : K8B09-MP-SPC-G-001 | V.IIA/S-III : 3 | Development Consultants Pvt. Ltd. |
|-------------------------------|-----------------|-----------------------------------|

(2. K8B09-MP-V-II-A-LEA1\_OPGC\_CONTRACT-BHEL.docx)



TITLE  
**SPECIFIC TECHNICAL REQUIREMENTS**  
**AUXILIARY STEAM PRESSURE REDUCING**  
**& DESUPERHEATING STATION**  
**FOR**  
**OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at**  
**Jharsuguda, Odisha**

SPEC. NO. PE-TS-391-142-N101

VOLUME **II-B**

SECTION **C**

REV NO. **00** DATE 17.07.2014

Sheet 1 of 20

## SECTION-C

### SPECIFIC TECHNICAL REQUIREMENTS



TITLE  
**SPECIFIC TECHNICAL REQUIREMENTS**  
**AUXILIARY STEAM PRESSURE REDUCING**  
**& DESUPERHEATING STATION**  
**FOR**  
**OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at**  
**Jharsuguda, Odisha**

SPEC. NO. PE-TS-391-142-N101

VOLUME **II-B**

SECTION **C**

REV NO. **00** DATE 17.07.2014

Sheet 13 of 20

**1.0.0 BRIEF SYSTEM DESCRIPTION**

- 1.1.0 Auxiliary steam system is designed to provide steam for the turbine auxiliaries, boiler auxiliaries and fuel oil heating system during start-up, low loads and normal running of unit.
- 1.2.0 The system comprises of two auxiliary steam pressure reducing and desuperheating stations (PRDS). One "High capacity PRDS" with tapping off steam from main steam line to meet auxiliary steam requirements during unit start-up, low loads & for fuel oil system, and the other "Low Capacity PRDS" with tapping off steam from CRH line to meet auxiliary steam requirements during normal running. Spray water required for desuperheating will be tapped off from CEP discharge.
- 1.3.0 These two stations will reduce the pressure and temperature of the steam tapped off from CRH line and main steam line to 16 kg/cm<sup>2</sup> (abs) & 310°C at the high temperature auxiliary steam header and subsequently to 16 kg/cm<sup>2</sup> (abs) & 250°C at the low temperature auxiliary steam header through a suitable desuperheater between the high temperature and low temperature auxiliary steam headers.

**2.0.0 EQUIPMENT TO BE PROVIDED BY TENDERER**

**2.1.0 AUXILIARY STEAM PRDS COMPRISING OF :**

**2.1.1 Control Valves & Accessories:**

- 2.1.1.1 Combined Type High Capacity Pressure Reducing & Desuperheating Valve (On MS line) (ASV-22) : One No. / Unit (02 nos. for 02 Unit)
- 2.1.1.2 Low Capacity PRV on CRH Line (ASV-26) : One No. / Unit (02 nos. for 02 Unit)
- 2.1.1.3 Spray Control Valve for HC-PRDS (CDV-151) : One No. / Unit (02 nos. for 02 Unit)
- 2.1.1.4 Spray Control Valve for LT-DESH (CDV-157) : One No. / Unit (02 nos. for 02 Unit)
- 2.1.1.5 Spray Control valve to TGS DESH (CDV-93) : One No. / Unit (02 nos. for 02 Unit)
- 2.1.1.6 Each control valve shall be supplied with the accessories specified in the relevant data sheets at Section-D.

**2.1.2 Desuperheaters :**

- 2.1.2.1 Direct mixing type LT desuperheater (DESH-2) : One No. / Unit (02 nos. for 02 Unit)
- 2.1.2.2 Direct mixing type TGS desuperheater (DESH-3) : One No. / Unit (02 nos. for 02 Unit)
- 2.1.2.3 The desuperheater shall be complete with pipe, spray nozzle along with necessary attachment as specified in section-D. **Insertion type desuperheaters are not acceptable.**



Technical specification for  
**Control Valves with Accessories**  
(Pneumatically Operated)

SPEC NO.:

VOLUME II B

SECTION C

REV. NO. 00

DATE :

SHEET 3 OF 23

**SPECIFIC TECHNICAL REQUIREMENTS.**

1. In case of any clash between this SPECIFIC TECHNICAL REQUIREMENTS and customer SPECIFIC TECHNICAL REQUIREMENTS, attached further the customer specific technical requirements shall override
2. The Hook-up diagram for Control valve, is attached. the scope demarcation as indicated should be adhered. The connection details at Instrument Air valve shall be furnished to successful bidder after the award of contract.
3. Valve Body Sizes shall be quoted to take care of the specification requirements like parameters, and limitations of Fluid outlet velocities, Noise Level etc. **However Port (Trim) Sizes shall be selected to suit CV requirement for achieving percentage valve lift as per Technical Specification.**
4. Bidder to note that, **wherever downstream side of the valve is subjected to the Vacuum service, bidder to offer double Gland packing, and in that case, flow direction of working fluid shall be to close the valve.** Separate indication for the same has not been made in the data sheets-A.
5. For valves subjected to cavitation service, anti-cavitation trim shall be provided.
6. In case during erection/commissioning of the control valve, any spares are required which have not been specified in the Start-up/commissioning spares list, the same will have to be supplied by the bidder free of cost
7. Facility to adjust the maximum travel of the stem & starting point of travel shall be incorporated.
8. SS nameplate to control valve shall include Tag no./ KKS no./ Sl. No./ Body material/ size/ Press Rating/ Trim material/ Trim type/ action on air failure/ diaphragm air press at full open and close condition
9. Hand wheel shall have open/ close direction.
10. Limit switch shall be designed for 1,00,000 operations.
11. JB shall be 36 ways as per enclosed hook-up diagram.
12. The material of filter for Air Filter Regulator shall be Sintered bronze.
13. Bidder to indicate pick-up & drop out voltage for all solenoid valves.
14. Protection class for Limit switches, I/P converter and Position transmitter shall be IP-65 only.
15. All JB's and valves shall be with double compression type Ni plated brass cable glands.





Technical specification for  
**Control Valves with Accessories**  
(Pneumatically Operated)

SPEC NO.:

VOLUME II B

SECTION C

REV. NO. 00


DATE :

SHEET 4 OF 23


16. Solenoid valve class of protection shall be IP-65.

17. All local cabling up to JB's shall be in Conduit (Flexible/Rigid). If JB is not mounted near valve

18. All regulating type final control elements shall have actuator of pneumatic type.

|   |   |  |   |
|---|---|--|---|
|  | Odisha Power Generation Corporation Limited | Technical Specification for Main Plant Package | IB TPS – 2 X 660 MW Units 3&4, Jharsuguda, Odisha |
|---|---|--|---|

### Control Valve Sizing and Construction

- i) The design of all valve bodies shall meet the specification requirements and shall conform to the requirements of ANSI (USA) for dimensions, material thickness and material specification for their respective pressure classes.
  - ii) The valve sizing shall be suitable for obtaining rated flow conditions with valve opening at approximately 80% of total valve stem travel and minimum flow conditions with valve stem travel not less than 10% of total valve stem travel. All the valves shall be capable of handling at least 120% of the required rated flow. Further, the valve stem travel range from minimum flow condition to rated flow condition shall not be less than 50% of the total valve stem travel. The sizing shall be in accordance with the latest edition of ISA on control valves. While deciding the size of valves, Seller shall ensure that valves port outlet velocity does not exceed 8 m/sec for liquid services, 150 m/sec. for steam services and 50% of sonic velocity for flashing services. Seller shall furnish the sizing calculations clearly indicating the outlet velocity achieved with the valve size selected by him as well as noise calculations, which shall be subject to Consultant's approval during detailed engineering stage.
  - iii) Control valves of steam and water applications shall be designed to prevent cavitation, wire drawing, flashing on the downstream side of valve and downstream piping. Thus for cavitation/flashing service, only valve with anti cavitation trim shall be provided. Detailed calculations to establish whether cavitation shall occur or not for any given application shall be furnished during detailed engineering stage.
- 
- v) All control valves shall have minimum leakage rate as per leakage Class-IV. However the leakage class may vary in critical applications subject to approval.
  - vi) The control valve induced noise shall be limited to 85 dBA at 1 meter from the valve surface under actual operating conditions. The noise abatement shall be achieved by valve body and trim design and not by use of silencers.





### Valve Construction

- i) All valves shall be of globe body design & straightaway pattern with single or double port unless other wise specified or recommended by the manufacturer to be of angle body type. Rotary valve may alternatively be offered when pressure drops permit.
- ii) Valves with high lift cage guided plugs & quick change trims shall be supplied.
- iii) Cast iron valves are not acceptable.
- iv) Bonnet joints for all control valves shall be of the flanged and bolted type or other construction acceptable to the Consultant. Bonnet joints of the internal threaded or union type shall not be acceptable.
- v) Plug shall be one-piece construction either cast, forged or machined from solid bar stock. Plug shall be screwed and pinned to valve stems or shall be integral with the valve stems.

- vii) Valve characteristic shall match with the process characteristics.
- viii) Extension bonnets shall be provided when the maximum temperature of flowing fluid is greater than 280 deg. C.

### Valve Materials

The control valve body & trim material shall be as stipulated in Annexure-IV of this section.

However, Seller may offer valves with body and trim materials better than specified materials and in such cases Seller shall furnish the comparison of properties including cavitation resistance, hardness, tensile strength, strain energy, corrosion resistance and erosion resistance etc. of the offered material vis-à-vis the specified material for Consultant's consideration and approval.

### End Preparation





~~Valve body ends shall be either butt welded/socket welded, flanged (Rubber lined for condensate service) or screwed as finalized during detailed engineering and as per Consultant's approval. The welded ends wherever required shall be butt welded type as per ANSI B 16.25 for control valves of sizes 65 mm and above. For valves size 50 mm and below welded ends shall be socket welded as per ANSI B 16.11 Flanged ends wherever required shall be of ANSI pressure-temperature class equal to or greater than that of control valve body.~~

### Valve Actuators


~~The HP and LP Bypass, turbine inlet control valves shall be with electro-hydraulic actuators and all other control valves shall be furnished with pneumatic actuators. The Seller shall be responsible for proper selection and sizing of valve actuators in accordance with the pressure drop and maximum shut off pressure and leakage class requirements. The valve actuators shall be capable of operating at 60 deg. C continuously.~~


Valve actuators and stems shall be adequate to handle the unbalanced forces occurring under the specified flow conditions or the maximum differential pressure specified. An adequate allowance for stem force, at least 0.15 kg/sq.cm. per linear millimeter of seating surface, shall be provided in the selection of the actuator to ensure tight seating unless otherwise specified.


The travel time of pneumatic actuators shall not exceed 10 seconds.

### Control Valve Accessory Devices

All pneumatic actuated control valve accessories such as air locks, hand wheels/hand-jacks, limit switches, microprocessor based electronic Positioner, diffusers, external volume chambers, position transmitters (capacitance or resistance type only), reversible pilot for Positioner, tubing and air sets, solenoid valves and junction boxes etc. shall be provided as per the requirements. Microprocessor based electronic positioner shall be provided as per the requirements of Annexure V of this section.



|  |   |  |
|--|---|--|
|  <b>Odisha Power Generation Corporation Limited</b> | <b>Technical Specification for Main Plant Package</b> | <b>IB TPS – 2 X 660 MW Units 3&amp;4, Jharsuguda, Odisha</b> |
|--|---|--|



7.03.07

All Control valves shall be tested in accordance with the quality assurance programme agreed between the Buyer and Seller which shall meet the requirements of IBR and other applicable codes mentioned elsewhere in the specifications. The tests shall include but not be limited to the following:


Non destructive test as per ANSI B-16.34

Hydrostatic shell test in accordance with ANSI B 16.34 prior to seat leakage test.

Valve closure test and seat leakage test in accordance with ANSI- B 16.34 and as per the leakage class.

Functional test: The fully assembled valves including actuators control devices and accessories shall be functionally tested to demonstrate times from open to close position.

CV test: CV test ~~shall be carried out as~~ **report not older than 5 (five) years** type test on each size, type and design of the valves as per ISA 75.02 standard and test report shall be furnished for Buyer's acceptance.




Doc. No.: K8B09-MP-SPC-G-001

V-II/D/S-I : 34

Development Consultants Pvt. Ltd.


(2-K8B09-MP-V-II-D-PCP1\_OPGC\_CONTRACT-BHEL.DOC)





# BANAHARPALLI SUPER THERMAL POWER PROJECT - 2 X 660 MW

## HOOK-UP DIAGRAM WITH SMART POSITIONER



### NOTES :-

1. FACILITY REQUIRED FOR VALVE STAYPUT ON AIR SUPPLY FAILURE.
2. SOLENOID VALVE & LIMIT SWITCHES WILL BE PROVIDED ONLY FOR ON/OFF DUTY VALVES AND CONTROL VALVES WHERE OPEN/CLOSE INTERLOCK IS REQUIRED AND INDICATED IN RESPECTIVE DATA SHEETS.
3. SOLENOID VALVES PORTS CONDITION:  
PORT 1 AND 2 SHALL BE CONNECTED UNDER DE-ENERGISED CONDITION.  
PORT 2 AND 3 SHALL BE CONNECTED UNDER ENERGISED CONDITION.
4. GAUGES REQUIRED FOR AIR SUPPLY & OUTPUT(S).
5. MOUNTING ACCESSORIES AS REQUIRED.
6. POSITION FEEDBACK SIGNAL SHALL BE 4-20mA (ISOLATED SIGNAL)
7. JB TERMINALS SHALL BE CAGE CLAMP TYPE SUITABLE FOR 2.5 SQ. MM COPPER WIRE.
8. FOR ON/OFF DUTY PNEUMATIC CONTROL VALVES  
THE FOLLOWING ACCESSORIES SHALL NOT BE APPLICABLE:-  
a) SMART POSITIONER b) POSITION TRANSMITTER c) I/P CONVERTER
9. 12 METERS 1/4" PVC COATED COPPER TUBING & 1 SET OF FITTINGS TO BE SUPPLIED FOR EACH CONTROL VALVE FOR CONNECTION TO ISO VLV AT INST AIR HEADER ON ONE END AND TO AIR LOCK RELAY/AIR FILTER REGULATOR ON THE OTHER END. ALL THE BRASS FITTINGS SHALL BE DOUBLE COMPRESSION TYPE.
10. VOLUME BOOSTER SHALL BE PROVIDED IF REQUIRED

\* SOLENOID VALVE & LIMIT SWITCH- IF APPLICABLE AS PER DATASHEET



TITLE  
**SPECIFIC TECHNICAL REQUIREMENTS**  
**AUXILIARY STEAM PRESSURE REDUCING**  
**& DESUPERHEATING STATION**  
**FOR**  
**OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at**  
**Jharsuguda, Odisha**

SPEC. NO. PE-TS-391-142-N101

VOLUME **II-B**

SECTION **C**

REV NO. 00 DATE 17.07.2014

Sheet 14 of 20

#### **4.0.0 SPARES, CONSUMABLE AND SPECIFIED TOOLS & TACKLES (For all Units):**

##### **4.1.1 Commissioning Spares & Consumables**

The bidder shall supply spares and consumables for all the above valves & desuperheater required during start-up. A list of all spares and consumables to be supplied shall be submitted along with the bid.

##### **4.1.2 Recommended Spares**

The bidder shall submit a list of recommended spares for all the above valves and desuperheaters for three years of normal operation. These are to be quoted separately & unit prices to be indicated, to enable placement of a separate order later if required.

##### **4.1.3 Special Tools & Tackles**

The bidder shall supply one complete set of special tools & tackles required for the erection, assembly, disassembly & maintenance of the equipment. A list of such tools & tackles to be supplied shall be submitted along with the bid.

##### **4.1.4 Bidder to indicate the service life expectancy period for the spare parts under normal working conditions. The spares shall be treated and packed for long storage under climatic conditions prevailing at site. Small items shall be packed in sealed transparent plastic bags with desiccators' packs as necessary.**

#### **5.0.0 SPARES:** The following spares are required to be offered.

##### **a) Stat-up & Commissioning spares:**

- i) Start-up and Commissioning spares are those spares, which may be required during the start-up and commissioning of the Control Valves. All start-up spares, which are supplied under this contract, shall be strictly interchangeable with the parts for which they are intended for replacements. The format for price schedule to be filled-up by the bidder is enclosed in Volume-III
- ii) The Start-up and commissioning spares indicated by the bidder shall be a part of the main Control valves supply. However bidder to indicate prices separately. The list of these spares required to be supplied shall be submitted along with the bid.

#### **LIST OF COMMISSIONING SPARES**

| S.No. | ITEM DESCRIPTION | QUANTITY REQUIRED (per unit)   |
|-------|------------------|--|
| 1     | Gaskets          | One (1) set with each control valve Tag                                    |
| 2     | Gland Packings   | One (1) set with each control valve Tag                                    |
| 3     | Cu Tubing        | 25 Meters of ¼ " PVC coated Cu. Tubing, with 1 set of Fittings for each CV |



TITLE  
**SPECIFIC TECHNICAL REQUIREMENTS**  
**AUXILIARY STEAM PRESSURE REDUCING**  
**& DESUPERHEATING STATION**  
**FOR**  
**OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at**  
**Jharsuguda, Odisha**

SPEC. NO. PE-TS-391-142-N101

VOLUME **II-B**

SECTION **C**

REV NO. **00** DATE 17.07.2014

Sheet 15 of 20

**6.0.0 INFORMATION TO BE FURNISHED ALONGWITH THE OFFER BY THE BIDDER.**

The bidder shall submit four (04) sets of the following drawings and data along with the bid without which the offer will be deemed incomplete.

- 6.1.0. Un-priced Bill of Quantities (BOQ) for main package & mandatory Spares.
- 6.2.0. Calculations for valve sizing, actuator sizing, valve velocities and noise level.
- 6.3.0. Dimensioned outline drawing giving overall dimensions, material.
- 6.4.0. **Duly filled BHEL technical data sheets 'B'** for each control valve & desuperheater in the format as enclosed in volume III of this specification.
- 6.5.0. Hook-up diagram of control valves with actuator & accessories.
- 6.6.0. Reference list, Catalogue & Technical bulletins for various items being offered.
- 6.7.0. Any deviations from the specification / data sheet & reasons thereof.
- 6.8.0. Schedules as in Vol. III.
- 6.9.0. Quality Plan for the equipment offered in the format enclosed with this specification.
- 6.10.0. Field quality plan, if applicable
- 6.11.0. List of commissioning and recommended spares.
- 6.12.0. List of tools & tackles, if applicable
- 6.13.0. List of consumables / lubricants, if applicable

**7.0.0 DRAWING**

For general arrangement and terminal point details refer enclosed drawings nos. PE-DG-391-142-N101 in Volume II B Sec. D.

**8.0.0 QUALITY PLAN**

The bidder shall furnish quality plan along with the offer and the same shall be finalized before the issue of LOI.

Detailed quality plan shall be submitted by the successful tenderer after the placement of order for each project during contract execution for final approval by BHEL / its customer. BHEL / its customer shall indicate Customer Hold Points (CHP) in the approved quality plan beyond which work shall not proceed without the approval of BHEL / its customer for any particular project during final execution.





TITLE  
**SPECIFIC TECHNICAL REQUIREMENTS**  
**AUXILIARY STEAM PRESSURE REDUCING**  
**& DESUPERHEATING STATION**  
**FOR**  
**OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at**  
**Jharsuguda, Odisha**

SPEC. NO. PE-TS-391-142-N101

VOLUME **II-B**

SECTION **C**

REV NO. **00** DATE 17.07.2014

Sheet 16 of 20

The quality plans enclosed in volume-II-B 'D' of the specification are for bidder's guidance only and are not exhaustive. The bidder shall comply with these and other minimum requirements specified in the specification and shall furnish his own quality plan in BHEL/Customer formats in the event of order based on the guidance given as above for BHEL/Customer's approval.



TITLE  
**SPECIFIC TECHNICAL REQUIREMENTS**  
**AUXILIARY STEAM PRESSURE REDUCING**  
**& DESUPERHEATING STATION**  
**FOR**  
**OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at**  
**Jharsuguda, Odisha**

SPEC. NO. PE-TS-391-142-N101

VOLUME **II-B**

SECTION **C**

REV NO. **00** DATE 17.07.2014

Sheet 17 of 20

**DATA SHEET- A-1**  
**SIZING DATA FOR AUXILIARY STEAM PRDS**

| SL. NO | PARAMETERS                                  | CASE-I              | CASE-II | CASE-V | CASE-VI | CASE-VII | CASE-VIII | MECH. DESIGN |
|--------|---|---------------------|---------|--------|---------|----------|-----------|--------------|
| 1.0    | INLET PARAMETERS TO COMBINED PRDS (ASV-22)  |                     |         |        |         |          |           |              |
| 1.1    | PRESSURE (Kg/Cm²a)                          | 63                  | 109     | 247    | 94      | 108      | 108       | 271          |
| 1.2    | TEMP. (°C)                                  | 375                 | 490     | 565    | 385     | 425      | 440       | 573          |
| 1.3    | FLOW (T/HR)                                 | Bidder to calculate |         |        |         |          |           |              |
| 2.0    | OUTLET PARAMETERS AT COMBINED PRDS (ASV-22) |                     |         |        |         |          |           |              |
| 2.1    | PRESSURE (Kg/Cm²a)                          | 16                  | 16      | 16     | 16      | 16       | 16        | 21           |
| 2.2    | TEMP. (°C)                                  | 310                 | 310     | 310    | 310     | 310      | 310       | 360          |
| 2.3    | FLOW (T/HR)                                 | 109.4               | 69.3    | 159.7  | 132.3   | 137.1    | 160       | -            |
| 3.0    | INLET OF SPRAY CONTROL VALVE (CDV-262)      |                     |         |        |         |          |           |              |
| 3.1    | PRESSURE (Kg/Cm²a)                          | 37                  | 37      | 34.7   | 37      | 37       | 35.7      | 46           |
| 3.2    | TEMP. (°C)                                  | 47                  | 46.6    | 46.3   | 47      | 46.6     | 46.6      | 55           |
| 3.3    | FLOW (T/HR)                                 | Bidder to calculate |         |        |         |          |           |              |

**NOTE:**

- Case-1 is the capability check point for PRV ASV-22. Case-V is the capability check point for Spray Water control valves.
- High capacity steam pressure reducing valve (ASV-22) min. flow at 10% valve lift shall correspond to the passing capability of low capacity steam pressure reducing valve (ASV-26) at 95% valve lift (refer datasheet A-2).
- Outlet pressure of HT-DESH is indicative only. Bidder shall calculate outlet pressure of Combined PRDS considering pressure drop across DESH-2



TITLE  
**SPECIFIC TECHNICAL REQUIREMENTS**  
**AUXILIARY STEAM PRESSURE REDUCING**  
**& DESUPERHEATING STATION**  
**FOR**  
**OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at**  
**Jharsuguda, Odisha**

SPEC. NO. PE-TS-391-142-N101

VOLUME **II-B**

SECTION **C**

REV NO. **00** DATE 17.07.2014

Sheet 18 of 20

**DATA SHEET- ~~A-2~~**  
**SIZING DATA FOR AUXILIARY STEAM PRESSURE REDUCING VALVE (PRV)**  
**ASV- 26**

| <u>S.NO</u> | <u>PARAMETERS</u>                        | <u>CASE-III</u> | <u>CASE-IV (A)</u> | <u>CASE-IV (B)</u> | <u>MECH. DESIGN</u> |
|-------------|--|-----------------|--------------------|--------------------|---------------------|
| <b>1.0</b>  | <b>INLET PARAMETERS OF PRV (ASV-26)</b>  |                 |                    |                    |                     |
| 1.1         | PRESSURE<br>(Kg/Cm <sup>2</sup> a)       | 22.66           | 22.66              | 56.13              | 67.3                |
| 1.2         | TEMP. (°C)                               | 343.5           | 343.5              | 334.2              | 360                 |
| 1.3         | FLOW (T/HR)                              | 14.10           | 11.40              | 11.70              | -                   |
| <b>2.0</b>  | <b>OUTLET PARAMETERS OF PRV (ASV-26)</b> |                 |                    |                    |                     |
| 2.1         | PRESSURE<br>(Kg/Cm <sup>2</sup> a)       | 16              | 16                 | 16                 | 21                  |
| 2.2         | FLOW (T/HR)                              | 14.10           | 11.40              | 11.70              | -                   |

**NOTE:**

1. High capacity steam pressure reducing valve (ASV-22) min. flow at 10% valve lift shall correspond to the passing capability of low capacity steam pressure reducing (ASV-26) valve at 95% valve list (refer datasheet A-1).
2. Outlet pressure of ASV-26 is indicative only. Bidder shall calculate outlet pressure of PRV (ASV-26) considering pressure drop across DESH-2/DESH-3.
3. Valve shall be suitable for passing **30T/Hr** at rated parameters (i.e. Case-IV B above).



TITLE  
**SPECIFIC TECHNICAL REQUIREMENTS**  
**AUXILIARY STEAM PRESSURE REDUCING**  
**& DESUPERHEATING STATION**  
**FOR**  
**OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at**  
**Jharsuguda, Odisha**

SPEC. NO. PE-TS-391-142-N101

VOLUME **II-B**

SECTION **C**

REV NO. **00** DATE 17.07.2014

Sheet 19 of 20

**DATA SHEET- A-3**  
**SIZING DATA FOR AUXILIARY STEAM PRDS ( (DESH-2) & SPRAY CONTROL**  
**VALVE (CDV-157)**

| Sl. No. | PARAMETERS                                  | CASE-I              | CASE-II | CASE-III | CASE-IV     | CASE-V | CASE-VI | CASE-VII | CASE-VIII | MECH. DESIGN |
|---------|---|---------------------|---------|----------|-------------|--------|---------|----------|-----------|--------------|
| 1.0     | PARAMETERS AT DESUPERHEATER INLET (DESH-2)  |                     |         |          |             |        |         |          |           |              |
| 1.1     | PRESSURE (Kg/Cm²a)                          | 16                  | 16      | 16       | 16          | 16     | 16      | 16       | 16        | 21           |
| 1.2     | TEMP. (°C)                                  | 310                 | 310     | 333      | 332.3/291.6 | 310    | 310     | 310      | 310       | 350          |
| 1.3     | FLOW (T/HR)                                 | Bidder to calculate |         |          |             |        |         |          |           |              |
| 2.0     | PARAMETERS AT DESUPERHEATER OUTLET (DESH-2) |                     |         |          |             |        |         |          |           |              |
| 2.1     | PRESSURE (Kg/Cm²a)                          | 16                  | 16      | 16       | 16          | 16     | 16      | 16       | 16        | 21           |
| 2.2     | TEMP. (°C)                                  | 250                 | 250     | 250      | 250         | 250    | 250     | 250      | 250       | 280          |
| 2.2     | FLOW (T/HR)                                 | 90.6                | 53.7    | 12.2     | 11.8        | 134.5  | 97.7    | 112.6    | 165       | -            |
| 3.0     | INLET OF SPRAY CONTROL VALVE CDV-157        |                     |         |          |             |        |         |          |           |              |
| 3.1     | PRESSURE (Kg/Cm²a)                          | 37                  | 37      | 35.7     | 35.7 / 34.7 | 34.7   | 37      | 37       | 35.7      | 46           |
| 3.2     | TEMP. (°C)                                  | 47                  | 39.6    | 39.6     | 46.3        | 45.9   | 39.6    | 46.6     | 46.6      | 55           |
| 3.3     | FLOW (T/HR)                                 | Bidder to calculate |         |          |             |        |         |          |           |              |

**NOTE:**

- Vendor to ensure the D/S pressure of DESH-2 shall be 16 Kg/ Cm<sup>2</sup> (a)



TITLE  
**SPECIFIC TECHNICAL REQUIREMENTS**  
**AUXILIARY STEAM PRESSURE REDUCING**  
**& DESUPERHEATING STATION**  
**FOR**  
**OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at**  
**Jharsuguda, Odisha**

SPEC. NO. PE-TS-391-142-N101

VOLUME **II-B**

SECTION **C**

REV NO. **00** DATE 17.07.2014

Sheet 20 of 20

**DATA SHEET- ~~A~~-4**  
**SIZING DATA FOR TGS DESUPERHEATER (DESH-3) & SPRAY CONTROL**  
**VALVE (CDV-93)**

| S.NO | PARAMETERS                                      | Condition-1         | Condition-2 | Condition-3 | Condition-4 | MECH.<br>DESIGN |
|------|---|---------------------|-------------|-------------|-------------|-----------------|
| 1.0  | PARAMETERS AT TGS DESUPERHEATER INLET (DESH-3)  |                     |             |             |             |                 |
| 1.1  | PRESSURE<br>(Kg/Cm²a)                           | 16                  | 16          | 16          | 16          | 21              |
| 1.2  | TEMP. (°C)                                      | 310                 | 310         | 310         | 290         | 350             |
| 1.3  | FLOW (T/HR)                                     | Bidder to calculate |             |             |             |                 |
| 2.0  | PARAMETERS AT TGS DESUPERHEATER OUTLET (DESH-3) |                     |             |             |             |                 |
| 2.1  | PRESSURE<br>(Kg/Cm²a)                           | 16                  | 16          | 16          | 16          | 21              |
| 2.2  | TEMP. (°C)                                      | 270                 | 300         | 270         | 270         | 350             |
| 2.3  | FLOW (T/HR)                                     | 2.7                 | 2.7         | 2.7         | 2.7         | -               |
|      | INLET OF SPRAY CONTROL VALVE (CDV-93)           |                     |             |             |             |                 |
| 3.1  | PRESSURE<br>(Kg/Cm²a)                           | 34.7                | 37          | 35.7        | 37          | 46              |
| 3.2  | TEMP. (°C)                                      | 46.3                | 47          | 46.6        | 39.6        | 60              |
| 3.3  | FLOW (T/HR)                                     | Bidder to calculate |             |             |             |                 |



TITLE

**EQUIPMENT SPECIFICATIONS**

**AUXILIARY STEAM PRESSURE REDUCING  
& DESUPERHEATING STATION**

**OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at  
Jharsuguda, Odisha**

SPEC. NO.: PE-TS-391-142-N101

VOLUME **II-B**

SECTION **D**

REV NO. **00** DATE 05.07.2014

SHEET 1 OF 1

**SECTION – D**

**EQUIPMENT SPECIFICATIONS**



TITLE

**EQUIPMENT SPECIFICATIONS****AUXILIARY STEAM PRESSURE REDUCING  
& DESUPERHEATING STATION****OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at  
Jharsuguda, Odisha**

SPEC. NO.: PE-TS-391-142-N101

VOLUME **II-B**SECTION **D**REV NO. **00** DATE 05.07.2014

SHEET 1 OF 1

**SECTION – D****EQUIPMENT SPECIFICATIONS****FOR****CONTROL VALVE WITH PNEUMATIC ACTUATOR**



## SPECIFICATION FOR CONTROL VALVE (WITH PNEUMATIC / ELECTRIC ACTUATOR)

SPECIFICATION NO.: PES – 145 - 06

VOLUME II B

SECTION D

REV. NO. 05

DATE : 15-05-2007

SHEET 2 OF 12

### 1.0 SCOPE

This specification covers the Design, Manufacture, Inspection and Testing at the manufacturer's works, proper packing for transportation and delivery to site of Control valve (with Pneumatic/Electric Actuator) for use in Utility/Captive Power Station/Combined Cycle Station.

### 2.0 CODES AND STANDARDS

2.1 All the equipments specified herein shall comply with the requirements of the latest issue of the relevant National and International standards.

2.2 The Design and Materials used for the components shall also comply with the relevant National and International standards.

2.3 As a minimum requirement, the following standards shall be complied with :

|                                   |   |                           |
|-----------------------------------|---|---------------------------|
| Indian Boiler Regulation (IBR)    | : | ANSI-B16.104 / FCI-70.2   |
| Allowable Seat leakage            | : | ANSI-B16.34               |
| Pressure & Temperature ratings    | : | IEC-144 / NEMA / IS-13947 |
| Enclosure class                   | : | ISA S-75                  |
| Control Valves                    | : | IS-9334                   |
| Electric Motor operated Actuators | : |                           |

### 3.0 TECHNICAL REQUIREMENTS

The Control valve, Actuator and the accessories shall be suitable for continuous operation under an ambient temperature of 0-55°C and Relative Humidity of 0-95% unless specified otherwise in volume IIB Section-B or Section-C.

#### 3.1 Control Valve

The control valve shall be suitably designed for the operating conditions and system characteristics as specified in the Data Sheet-A.

3.1.1 The control valve shall be of globe body design with single port. The valve trim, shall be suitable for quick removal without any cutting or welding.

3.1.2 The material of body, internals and packing shall be as specified in the data sheets. Alternatives, considered more suitable for service specified may be given as alternative offer, along with adequate justification. However main offer shall totally meet specification requirements. Asbestos shall not be used for the packing or any other component.

3.1.3 The valve bonnet and packing shall be suitable for the service conditions as in Data Sheet-A. Gland sealed type bonnets are not acceptable. Double packing is mandatory for applications involving vacuum service. Bonnets having teflon packing shall have valve stem finished to 2-4 microns. Packing material requiring lubrication will not be acceptable. Justification for proper selection of bonnet & packing shall be furnished in the bid.

3.1.4 The valve end connection as specified in Data Sheet-A shall conform to ANSI B16.25 for Butt Weld connection and ANSI B16.5 for flanged ends. End to end dimension shall be as per ANSI 16.10.

3.1.5 The valve seat leakage shall be as per ANSI B16.104 / FCI-70.2. The leakage class shall be as per Data Sheet-A.





**SPECIFICATION FOR CONTROL VALVE  
(WITH PNEUMATIC / ELECTRIC ACTUATOR)**

SPECIFICATION NO.: PES – 145 - 06

VOLUME II B

SECTION D

REV. NO. 05

DATE : 15-05-2007

SHEET 3 OF 12

- 3.1.6 The valve body shall have the direction of flow embossed on all valves.
- 3.1.7 The sizing shall conform to the requirements of ANSI/ISA(S75- 01), and the valve capacity shall be selected so as to meet the following:
- |  |   |   |   |                    |
|--|---|---|---|--------------------|
| Valve with Linear characteristic.        | - | Normal Flow (Design Point)  | : | 70-75% valve lift. |
|  | - | Max. Flow   | : | 90% valve lift.    |
|  | - | Min. Flow   | : | >10% valve lift.   |
| Valve with Equipercentage Characteristic | - | Normal Flow (Design Point)  | : | 75-85% valve lift. |
|  | - | Max. Flow   | : | 90% valve lift.    |
|  | - | Min. Flow   | : | >10% valve lift.   |
| ON/OFF Quick open Characteristic         | - | 1.1 times the CV calculated on the basis of maximum flow condition. |   |                    |
- 3.1.8 Calculation for valve sizing, velocity and noise shall be subject to purchaser's approval during contract stage. However responsibility of proper selection and design for the duties specified lies with the vendor. Any modifications required to be done on the valves or actuators & accessories to achieve satisfactory performance of the control system shall be done without any commercial implication.
- 3.1.9 Suitable justification and evidence shall be furnished regarding proper selection of the valve.
- 3.1.10 The valve outlet velocities shall be limited to the following values, unless otherwise specified in the Data sheet-A.
- |     |                |    |  |
|-----|----------------|----|--|
| i)  | Liquid service | <= | 7 Metres/Sec.                          |
| ii) | Steam service  | <= | 1/3 Sonic velocity in the flow medium. |
- 3.1.11 For flashing duty, the trim design shall be such that the vapour bubbles are kept away from valve body.
- 3.1.12 For cavitation service, the trim design shall be of multistage pressure drop type, so as to avoid cavitation altogether, instead of keeping cavitation away from valve parts.
- 3.1.13 In case of predicted noise level above 85 dBA, suitable low noise trim or inbuilt diffusers shall be provided to bring down the noise level below 85dBA.
- 3.1.14 The equivalent weighted sound level measured at 1.5M. above floor level in elevation and one metre horizontally from the control valve expressed in decibels to a reference of 0.0002 microbar shall not exceed 85 dBA (without pipe insulation). The offer shall include noise prediction calculations for each valve.
- 3.1.15 In case of wrong selection/mal operation of valve and for associated actuator during guarantee period, the vendor shall replace the valve suitably with a modified/new valve of design as approved by purchaser and all the expenses for replacement, rectification/modification including transportation both ways will be at vendor's expenses.



**SPECIFICATION FOR CONTROL VALVE  
(WITH PNEUMATIC / ELECTRIC ACTUATOR)**

SPECIFICATION NO.: PES – 145 - 06

VOLUME II B

SECTION D

REV. NO. 05

DATE : 15-05-2007

SHEET 4 OF 12

### 3.2 Pneumatic Actuator

The pneumatic actuators shall be employed for modulating or open/close duty, as specified in Data Sheet-A. The bidder shall be responsible for proper selection and sizing of valve actuators in accordance with the pressure drops and shut off pressure.

3.2.1 The pneumatic spring opposed diaphragm actuator for modulating duty shall be capable of positioning the associated valve at desired opening for all the operating conditions specified.

3.2.2 The pneumatic actuator for open/close duty shall be suitable for fast opening/closing of the associated valve.

3.2.3 The actuator design shall allow valve assembly to be mounted at 45° inclination on either side in the vertical plane.

3.2.4 The actuators shall be suitably sized to ensure that the associated valve travel time from full open to full closed position and vice versa is less than 20 seconds under the most stringent service conditions.

3.2.5 The actuator shall be painted with epoxy based paint.

### 3.3 Accessories for Control valve with Pneumatic Actuator

The bidder shall offer all the accessories as specified in the Data Sheet - A for the Pneumatic Actuators under modulating or OPEN/CLOSE duty. The accessories specified shall be supplied duly mounted on the valve actuator and piped with PVC covered copper tube and flareless brass fittings (Refer typical hook up diagram in sheet 12 of 12).

#### 3.3.1 Handwheel

Handwheel shall have OPEN & CLOSE direction marking and clockwise rotation as viewed from front shall close the valve. The handwheel shall have a circular stainless steel plate with Tag number and service.

#### 3.3.2 Local Position Indicator

Each actuator shall be provided with a mechanical pointer attached to stem, moving over a graduated scale with markings, for OPEN, 25%, 50%, 75%, CLOSE positions.

#### 3.3.3 Position Transmitter

The position transmitter shall be supplied as indicated in Data Sheet-A. The electronic position transmitter shall be non-contact type with 4-20 mA DC 2-wire output suitable for 12-50V DC supply. The resistance type position transmitter shall have 0-100 ohm variation for valve position change of 0-100%. The position transmitters of both types shall have accuracy and enclosure class. Necessary cable glands shall be supplied.



**SPECIFICATION FOR CONTROL VALVE  
(WITH PNEUMATIC / ELECTRIC ACTUATOR)**

SPECIFICATION NO.: PES – 145 - 06

VOLUME II B

SECTION D

REV. NO. 05

DATE : 15-05-2007

SHEET 5 OF 12

### 3.3.4 Air Filter Regulator

Instrument quality air at suitable pressure of 5.5 Kg/Cm<sup>2</sup>(g) to 7 Kg/Cm<sup>2</sup>(g) shall be supplied to each valve through air filter regulator. The filter regulator shall include an inbuilt blow-down valve, 5 micron size filter. The design pressure for regulator shall be 7 Kg/cm<sup>2</sup>g. The Air filter regulator shall be selected to meet the requirements of positioner/actuator, E/P convertor and air-lock. The flow capacity of the Air filter regulator shall be variable with a knob. Output gauge shall be provided wherever pneumatic positioner is not specified for the valve.

### 3.3.5 Air Lock Relay

Air lock relay shall retain the valve position stayput, in case of air supply failure and shall reset automatically on resumption of air supply. Air lock shall have a threaded plug for evacuating diaphragm air if required for local manual operation.

### 3.3.6 Solenoid Valves

Solenoid valves are meant for interlock & protection purposes overriding the controller signal, and/or to result stayput action on controller signal failure. The Solenoid valve shall be 3-way Universal type and the valve internals shall be of stainless steel. The coil shall have class-H insulation and rated for continuous AC/DC duty as specified in Data sheet-A. The enclosure shall be to IP-55. Cable gland shall be provided for cable entry. The solenoid shall in general conform to IS-8935. The solenoid operation shall be universal type. The solenoid shall be suitable for 24V DC supply, unless specified otherwise in Data Sheet-A.

### 3.3.7 Limit Switches

Limit switches are required as specified in the data sheet-A. Each limit switch shall have 2NO+2NC contacts with contact rating of 5A at 240V AC/0.2A at 220V DC unless otherwise specified. The switch enclosure shall conform to IP-55. Each limit switch shall be supplied with cable glands.

### 3.3.8 I/P Converter

I/P Converters shall preferably be of force balance type and shall produce pneumatic output signal corresponding to input current signal, also specified in Data Sheet. Convertor electronics shall be protected against reverse connection of signal polarities and a separate external connection shall be provided to facilitate grounding of instrument casing. Cable glands with neoprene gromets suitable for PVC cables shall be provided. I/P convertor shall have span adjustment facility. I/P convertor enclosure shall conform to IP-55 enclosure class.

### 3.3.9 Positioner

Positioner shall be suitable for accepting controller output signal 0.2-1.0 Kg/cm<sup>2</sup>, 0.2-0.6 Kg/cm<sup>2</sup> or 0.6-1.0 Kg/cm<sup>2</sup> as specified and give an output suitable for the actuator. Pneumatic positioner shall have 3 gauges. All gauges shall have metric scales. The positioner input signal range shall be adjustable. Wherever applicable, it shall be possible to bypass the positioner by means of a switch. Linearity and Hysteresis shall be as indicated in Data sheet-A

### 3.3.10 Electro pneumatic Positioner

In place of separate E/P Converter and pneumatic positioner a combined electro pneumatic positioner can also be supplied. The electro pneumatic positioner shall have 2 gauges.



**SPECIFICATION FOR CONTROL VALVE  
(WITH PNEUMATIC / ELECTRIC ACTUATOR)**

SPECIFICATION NO.: PES – 145 - 06

VOLUME II B

SECTION D

REV. NO. 05

DATE : 15-05-2007

SHEET 6 OF 12

### 3.3.11 Junction Box

Wherever specified, an integral junction box with all electrical accessories conduited up to JB shall be supplied. The junction box shall have two (2) cable glands for outgoing cables. Junction box shall have enclosure class of IP-55.

### 3.4 Guarantee & Performance

3.4.1 The overall performance of the control valve with pneumatic actuator assembly shall be as follows:-

|      |                    |   |                      |
|------|--------------------|---|----------------------|
| i)   | Hysteresis         | : | $\pm 1\%$ of span    |
| ii)  | Linearity          | : | $\pm 2\%$ of span    |
| iii) | Sensitivity        | : | $\pm 0.5\%$ of span. |
| iv)  | Repeatability      | : | $\pm 1\%$ of span    |
| v)   | Accuracy (Overall) | : | $\pm 2\%$ of span    |

3.4.2 The guarantee for the control valve, pneumatic actuator & accessories shall be for 12 months continuous operation from the date of commissioning, unless specified otherwise in VOL-II B Section-B or Section-C.

### 3.5 Electric Actuator

The electric actuator shall be employed for modulating duty.

3.5.1 The actuator assembly shall be complete with drive motors, gears, hand wheel, signaling & switching units, associated control, integral starter, (when specified) and other accessories as required.

3.5.2 The Electric Actuator shall be capable of positioning the associated valve at the desired opening for all the operating conditions.

3.5.3 The motor shall meet the requirements of Current, torque, Axial thrust, Accelerating & stall time as imposed by the driven equipment.

3.5.4 The motor shall be suitable for direct on line starting.

3.5.5 Motors shall be suitable for inching & plugging duty operations.

3.5.6 The motors shall be capable of starting and accelerating to rated speed at 85% of rated voltage.

3.5.7 The motors shall be rated for continuous operations for modulating duty.

3.5.8 The motor shall operate satisfactorily under the following conditions:

- i)  $\pm 10\%$  supply voltage variation at rated frequency.
- ii)  $-5\%$  to  $+3\%$  variation in frequency at rated supply voltage.

iii) Simultaneous variation in voltage and frequency, the sum of absolute percentage not exceeding 10%.  
3.5.9 The Actuator shall be suitable for mounting directly on the valve and shall be suitable for mounting in any position. Supports required for inclined mounting shall form part of supply of valve assembly.

3.5.10 The actuator shall be capable of producing the required torque and thrust at the output shaft for satisfactory operation of the associated valve.



**SPECIFICATION FOR CONTROL VALVE  
(WITH PNEUMATIC / ELECTRIC ACTUATOR)**

SPECIFICATION NO.: PES – 145 - 06

VOLUME II B

SECTION D

REV. NO. 05

DATE : 15-05-2007

SHEET 7 OF 12

- 3.5.11 Each actuator shall have a hand wheel for emergency operation. The hand wheel shall be designed such that it is declutched automatically when the power supply to the motor is restarted.
- 3.5.12 The hand wheel shall be so arranged that when looking from hand wheel, the valve is closed by rotating the hand wheel in clockwise direction.
- 3.5.13 Motor shall be totally enclosed conforming to IP-65 or better as per data sheet. The enclosure shall be suitable to protect the motor from leakage steam, water or oil from valve joints and glands.
- 3.5.14 Where flameproof enclosures are specified, it shall meet the specification IS-2148.
- 3.5.15 Insulation shall be at least class-B or better and shall be tropicalised to withstand the atmospheric condition.
- 3.5.16 The actuator shall be provided with antifriction bearing in grease filled cartridge.
- 3.5.17 Each actuator shall be provided with a mechanical position indicator to indicate accurately the valve position.
- 3.5.18 The integral starter, if specified in data sheet-A, shall be provided in weatherproof enclosure with protection class not less than IP-65 or better as per data sheet.
- The integral starter shall consist of:
- i) Mechanical & Electrically interlocked reversing contractors suitable for class AC4 duty or Thyristor as per data sheet.
  - ii) Thermal overload relay.
  - iii) Step down control transformer with fuses.
  - iv) Interposing relay.
  - v) Monitoring relay..
  - vi) Open, Close & Stop push buttons.
  - vii) Indicating lamps.
  - viii) Local-Remote lockable selector switch with spare potential free contacts, wired for remote interface.
  - ix) A potential free contact shall be provided for remote annunciation of power failure/overload condition. The contact shall be SPDT, rated for at 5A 240V AC or 0.2A at 220V DC.



**SPECIFICATION FOR CONTROL VALVE  
(WITH PNEUMATIC / ELECTRIC ACTUATOR)**

SPECIFICATION NO.: PES – 145 - 06

VOLUME II B

SECTION D

REV. NO. 05

DATE : 15-05-2007

SHEET 8 OF 12

- 3.5.19 The actuator shall be suitably time rated for the duty cycle involved with the necessary number of starts per hour, but in no case, less than 1200 starts per hour.
- 3.5.20 The actuator shall be provided with a suitable control unit for receiving 4-20 mA signal from remote controller.
- 3.5.21 The servomotor gear should have self locking or suitable brake so as to maintain it's last position as and when the motor power is switched off.
- 3.5.22 Thermostat/Thermistor as specified in the data sheet shall be provided for sensing the winding temperature and giving trip command. The trip contact shall be change over type. The contact shall be wired up to the actuator terminal box.
- 3.6 Accessories for Control Valve with Electric Actuator
- 3.6.1 Torque Switches
- i) Each actuator shall be provided with at least one open and one close torque switches each with 2 NO+2 NC contacts. The contacts shall be rated for 5A at 240V AC or 0.2A at 220V DC.
  - ii) The torque switches shall have a minimum accuracy  $\pm 3\%$  of set value.
  - iii) The torque switches shall be provided with calibrated knobs for setting desired torque. Separate knobs shall be provided for close and open torque switches.
  - iv) The torque switches shall be provided with mechanical latching device to prevent operation when unsealing from the positions. The latching device shall unlatch as soon as the valve leaves the end position. If such provision is not possible, the torque switches shall be bypassed by end position limit switches, which open on valve leaving end position. These limit switches are additional to the number of limit switches specified elsewhere.
  - v) The torque switches or worm gear shall be self-locking type so that when torque switch operates it remains operated until the actuator is operated in the reverse.
  - vi) The torque switch enclosure shall conform to IP-55.
- 3.6.2 Limit Switches
- Each limit switch shall have 2NO+2NC contact with contacts rated for 5A 240V AC/0.2A 220V DC unless otherwise specified. The switch enclosure shall conform to IP-55. Each limit switch shall be supplied with cable glands.
- 3.6.3 Space Heater
- A space heater shall be provided in limit switch and starter compartments to prevent condensation. This shall be suitable for the power supply specified in the data sheet. Where integral starters are provided the space heaters shall be wired to control supply within the actuator.



**SPECIFICATION FOR CONTROL VALVE  
(WITH PNEUMATIC / ELECTRIC ACTUATOR)**

SPECIFICATION NO.: PES – 145 - 06

VOLUME II B

SECTION D

REV. NO. 05

DATE : 15-05-2007

SHEET 9 OF 12

### 3.6.4 Remote Position Transmitter

The position transmitter shall be supplied as indicated in Data Sheet-A. The electronic position transmitter shall be non-contact type with 4-20mA DC 2-wire output suitable for 12-50V DC supply. The resistance type position transmitter shall have 0- 100 ohm variation for valve position change of 0-100%. The position transmitters of both types shall have  $\pm 1\%$  accuracy. The enclosure shall conform to IP-55. Necessary cable glands shall be supplied.

### 3.6.5 Wiring

- i) The actuator and the accessories will be neatly wired up to the terminal boxes.
- ii) The internal wiring shall be minimum of 1 mm<sup>2</sup> stranded PVC insulated copper conductor.
- iii) The wiring shall be identified by means of numbered ferrules on both ends of all wires.

### 3.7 Terminal and Terminal boxes

#### 3.7.1 Motor Terminal Box

- i) The terminals, terminal boards, terminal boxes, winding tails and associated equipment shall be suitable for connection to supply system having short circuit capacity specified in data sheet and clearance time determined by the associated fuses.
- ii) The terminals shall be stud type insulated from the frame. The insulation shall not be porcelain. The studs shall be of brass or stainless steel or phosphor bronze of adequate size.
- iii) The terminal box shall be totally enclosed conforming to degree of protection IP-65.

#### 3.7.2 Actuator Terminal Box

- i) All terminals of limit and torque switches, space heater, position transmitters, thermostat/thermister shall be brought to a common terminal box. The enclosure shall be to degree of protection IP-65.
- ii) Terminal board with plug in connector shall be provided. Alternatively stud type or insertion type may be considered. Pinch screw type however will not be accepted. All terminals shall be shrouded to prevent accidental contact. Where stud type terminals are offered, it shall be as per clause 3.7.1 (ii).
- iii) There shall be at least five terminals spare to terminate spare cores of cable.

#### 3.7.3 Cable Glands

The motor terminal box and actuator terminal box shall be provided with required number of double compression nickel plated brass cable glands to suit cable type and associated size.

#### 3.7.4 Earthing Terminal

Two earthing terminal shall be provided on either side of motor and actuator terminal box.

#### 3.7.5 Painting

The Actuator shall be painted with epoxy-based paint.



**SPECIFICATION FOR CONTROL VALVE  
(WITH PNEUMATIC / ELECTRIC ACTUATOR)**

SPECIFICATION NO.: PES – 145 - 06

VOLUME II B

SECTION D

REV. NO. 05

DATE : 15-05-2007

SHEET 10 OF 12

#### 4.0 TESTING AND INSPECTION

4.1 The bidder shall adopt suitable quality assurance plan to ensure that the equipments offered will meet the specification requirements in full.

4.2 The bidder shall furnish the Quality Plan in the format enclosed in volume-III. In case the Quality Plan(s) is/are included in volume-IIB, the bidder shall furnish his Quality Plan strictly in line with the same. The Quality Plan shall be discussed and finalised with the technically accepted bidders before opening the price bid. The stages where purchaser would like to be associated for witnessing or verification of tests would be indicated by the purchaser in the Quality Plan before approval.

4.3 The following test shall be conducted as a minimum requirement.

##### 4.3.1 Control Valve

- i) Radiographic tests on castings.
- ii) Dye penetrant tests on machined surface.
- iii) Ultrasonic tests for the forgings & bars of all valves with 60 Kg/cm<sup>2</sup> & higher ratings.
- iv) Hydrostatic tests as per ANSI B 16.34 prior to seat leakage tests.
- v) Valve closure and seat leakage tests as per ANSI B 16.104 / FCI-70.2.

##### 4.3.2 Pneumatic Actuators

Functional test of actuator and each accessory.

##### 4.3.3 Electric Actuator

- i) Routine tests on motors as per IS: 325.
- ii) Functional test on actuator and each accessory.
- iii) Insulation resistance and high voltage test.
- iv) Stall current & Stall torque test.
- v) Output shaft speed and torque of actuator and corresponding current tests.

##### 4.3.4 Control valve with Actuator & Accessories fully assembled

- i) Functional tests of control valve operation along with actuator & accessories.
- ii) Dimension checks.

##### 4.3.5 Type tests or Test Reports

- i) Valve lift vs. Flow test (Cv Test)
- ii) Degree of protection tests for the enclosures
- ii) Temperature rise test (applicable for Electrical Actuator only).
- iii) Type test for motor as per IS: 325.

4.4 Inspection will be conducted by BHEL and/or their authorised representatives as per the agreed inspection schedule. The inspection schedule will be submitted by the bidder, for BHEL's approval at contract stage. The cost of all tests and inspections will be deemed to have been included in the bid. For all the type tests covered under 4.3.5 above, "Type Test Certificates" as per agreed Quality Plan shall be furnished. In the absence of the same, such Type Tests shall be arranged at the Vendor's works in the presence of BHEL and/or their authorised representatives or in independent Test House/Laboratory approved by BHEL.

4.5 The Standard QP is included in this specification to enable bidder to understand the extent of inspection and testing requirements to execute this job. The successful bidder has to follow the agreed QP, taking care of customer requirements mentioned in Sec-C and submit QP for final approval by BHEL / Customer.





**SPECIFICATION FOR CONTROL VALVE  
(WITH PNEUMATIC / ELECTRIC ACTUATOR)**

SPECIFICATION NO.: PES – 145 - 06

VOLUME II B

SECTION D

REV. NO. 05

DATE : 15-05-2007

SHEET 11 OF 12

**5.0 SPARES AND CONSUMABLES**

**5.1 Commissioning Spares and consumables**

As part of the main equipment supply, the bidder shall supply all commissioning spares and consumables required during Start-up,

**5.2 Mandatory Spares**

The bidder shall offer along with main offer, the Mandatory Spares as specified in Volume IIB Section-C of the specification. The Mandatory Spares offered shall be of the same make and type as the main equipment.

**5.3 Recommended Spares**

The bidder shall furnish a list of Recommended Spares along with the normal service expectancy period and frequency of replacement; quantities recommended for 3 years operation along with unit rate against each item to enable BHEL / BHEL's Customer to place a separate order later, if required.

**5.4 Special Tools & Tackles**

The bidder shall furnish a list of Special Tools & Tackles included in the bid.

**6.0 DRAWINGS AND DOCUMENTS**

**6.1 The bidder shall furnish the following documents in required number of copies along with the bid:**

6.1.1 Data sheet-B, completely filled-up along with all enclosures.

6.1.2 Wiring diagrams for Electrical Actuators.

6.1.3 Hook up diagrams of Control Valve with Actuator & accessories.

6.1.4 Valve & actuator assembly dimensional drawings with weights.

6.1.5 Quality Plan

6.1.6 All relevant Catalogs with detailed technical information.

6.1.7 Bar-chart to indicate the time schedule for procurement, manufacture, testing and despatch.

**6.2 The successful bidder shall furnish the following documents in required number of copies to BHEL during the contract stage:**

**6.2.1 For approval**

- i) Dimensional drawings.
- ii) Installation drawings with overall dimensions of the completed equipment and clearances for operation and maintenance.
- iii) Data sheet-C, completely filled-up along with all the enclosures including the sizing calculations & noise calculations.
- iv) Quality Plan.
- v) Test Certificates.



**SPECIFICATION FOR CONTROL VALVE  
(WITH PNEUMATIC / ELECTRIC ACTUATOR)**

SPECIFICATION NO.: PES – 145 - 06

VOLUME II B

SECTION D

REV. NO. 05

DATE : 15-05-2007

SHEET 12 OF 12

**6.2.2 Final / As-built Drawings**

Final / As-built drawings / CDs in required number of copies shall be submitted.

**6.3 Operation & Maintenance Manuals**

O&M Manuals in required number of copies shall be submitted. O&M manuals shall also contain storage and commissioning instructions.

**7.0 MARKING AND PACKING**

**7.1 Marking**

A stainless steel metal nameplate should be permanently fixed on each equipment giving its tag number and technical specifications.

**7.2 Packing**


All equipment / materials shall be suitably packed and protected for the entire period of dispatch, storage and erection against impact, abrasion, corrosion, incidental damage due to vermin, sunlight, high temperature, rain, moisture, humidity, dust, sea water spray (where applicable) as well as rough handling and delays in transit and storage in open.

55

**8.0 APPLICABLE DATA SHEET FORMS**

This document shall be read with one or more of the following data sheet forms :

- |  |                                 |
|--|---------------------------------|
| - Data sheet A&B for Control Valve with Pneumatic Actuator : | Data sheet no. PES-145-06-DS1-1 |
| - Data sheet C for Control Valve with Pneumatic Actuator :   | Data sheet no. PES-145-06-DS2-1 |
| - Data sheet A&B for Control Valve with Electric Actuator :  | Data sheet no. PES-145-06-DS3-1 |
| - Data sheet C for Control Valve with Electric Actuator :    | Data sheet no. PES-145-06-DS4-1 |

|  |   |  |
|--|---|--|
|  <b>Odisha Power Generation Corporation Limited</b> | <b>Technical Specification for Main Plant Package</b> | <b>IB TPS – 2 X 660 MW Units 3&amp;4, Jharsuguda, Odisha</b> |
|--|---|--|



ANNEXURE-IV

## MATERIALS OF CONSTRUCTION FOR CONTROL VALVES

Materials for Control Valves shall be equivalent/superior to the following:


| Sl. No. | Service  | Body Material                         | Trim Material  |
|---------|--|---------------------------------------|--|
| 1       | Non-corrosive, non-flashing and non-cavitation service below 275 deg. C. like Aux. steam flow to deaerator, condensate flow to deaerator, CRH flow to deaerator etc. | Compatible with piping material       | SS-316 with stellite faced guide posts and bushings.         |
| 2       | Severe flashing/cavitation services like HP Heaters and LP Heaters, emergency drain, Deaerator overflow drain to hotwell etc.  | Alloy steel as per ASTM A 217 Gr. WC9 | 400 series SS or equivalent to suit the specific requirement |
| 3       | Low flashing/cavitation service like HP Heater/ LP Heater normal drains level control, GSC minimum flow, Gland seal steam pressure control valve etc.                | Alloy steel as per ASTM A 217 Gr. WC6 | 400 series SS or equivalent to suit the specific requirement |
| 4       | Condensate service below 300 deg. C. like condensate normal and emergency make-up control, DMCW DP control   | SS-316                                | SS-316   |

**Note :** Valve body rating shall meet the process pressure and temperature requirements as per ANSI B16.34.



|                               |                         |                                   |
|-------------------------------|-------------------------|-----------------------------------|
| Doc. No. : K8B09-MP-SPC-G-001 | V-IID/S-II/Annx-IV : 47 | Development Consultants Pvt. Ltd. |
|-------------------------------|-------------------------|-----------------------------------|



(2. K8B09-MP-V-II-D-PCP1\_OPGC\_CONTRACT-BHEL.DOC)

|  |   |  |
|--|---|--|
|  <b>Odisha Power Generation Corporation Limited</b> | <b>Technical Specification for Main Plant Package</b> | <b>IB TPS – 2 X 660 MW Units 3&amp;4, Jharsuguda, Odisha</b> |
|--|---|--|

**ANNEXURE-V**

### DATA SPECIFICATIONS SHEET FOR MICROPROCESSOR BASED ELECTRONIC POSITIONER



|  |   |  |
|--|---|--|
| Electrical   | Input Signal  | 4-20 mA.   |
|  | Power Supply  | Loop Powered from the output card of Control System.   |
|  | Hart Protocol   | Compatibility For Remote Calibration & Diagnostics (Super-Imposed Hart Signal On Input Signal(4-20 mA).  |
|  | Valve Position Sensing  | Position Sensing (Non Contact-Sensing Type), 4-20 Ma O/P Signal For Control System To Be Provided.   |
| Environment  | Operating Temp  | (-)30 To 80 Deg. C   |
|  | Humidity  | 0-95 %   |
|  | Protection Class  | IP-65 Minimum.   |
| Software For Configuration And Diagnostic  | Software  | Windows Based Software. Configuration Shall Meet the Requirement, Diagnostics, Calibration Testing Of The Actuator.  |
|  | Diagnostic/Test Features  | Advanced Diagnostic Features Like Features Stroke Counter Or Travel Counter, Leakage In Actuators, On Line Partial Closure Test, Valve Signature Analysis, Step Response Test, Valve Friction /Jamming Detection Etc To Be Provided. |
|  | Factory Valve Signature Tests Reports (Pr Vs Valve Travel And Travel Vs I/P Signal) are to be provided. |  |
| Hardware   | PC  | For Configuration/Software, Ref PC Specified Under DDCMIS Section.   |
| Tests Certificates   |   | Test certificates as per Manufacture Standard/Relevant Standard are To Be Submitted.   |
| Configuration / Remote Calibration, Auto & Manual Calibration Shall Be Possible. |   |  |
| Operating  | Operating Range   | Full Range & Split Range Signal Range.   |
| Modes  | Valve Action  | Direct & Reverse. Valve Action.  |
|  | Flow Characterisation   | Possible To Fit Valve Characteristic Curve Linear & Equal Percentage.  |
| Doc. No. : K8B09-MP-SPC-G-001  |   | V-IID/S-I/Annx-V : 48  |
|  |   | Development Consultants Pvt. Ltd.  |





ANNEXURE-V

|                       |  |  |
|-----------------------|--|--|
| Fail Safe/Fail Freeze | Fail Safe/Fail Freeze Feature is to be Provided. |  |
| Pneumatic             | Air Capacity                                     | Sufficient To Handle The Valves Selected/Boosters To Be Supplied If Required.  |
|                       | Air Supply Pressure                              | To Suit The Air Supply Pressure/ Quality Available.  |
|                       | Process Connection                               | 1/4 Inch NPT.  |
| Performance           | Characteristic Deviation                         | $\leq 0.5\%$ Of Span.  |
|                       | Ambient Temp Effect                              | $\leq 0.01\%$ /Deg C Or Better.  |
| EMC & CE Compliance   | Required To International Standard Like EN/IEC.  | En50081-2& En50082 Or Equivalent.  |
| Accessories           | In Built Operator                                | Display With Push Buttons For Configuration Panel And Display On The Positioner Itself (Password Protected/Hardware Lock).     |
|                       | Hand Held Hart Calibrator                        | Universal Hart To Be Calibrator Provided, One Per Unit.  |
|                       | Press Gauge Block                                | For Supply & Output Pr., Filter Regulator Other Accessories Shall Be Provided As On Required Basis For Making System Complete. |
|                       | Electrical Cable Entry                           | 1/2-Npt, Side Or Bottom Entry To Avoid Water Ingress.  |
|                       | Valves Mounting Assembly                         | For Sliding Stem/Rotary/Single Acting/Double Acting On Required Basis.   |





**DATA SHEET FOR CONTROL VALVES  
(WITH PNEUMATIC ACTUATOR)**  
**For**  
**OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at**  
**Jharsuguda, Odisha**

SPEC. NO.: PE-TS-391-142-N101

VOLUME II - B

SECTION D

REV. NO. 0

DATE : 05.07.2014

SHEET 1 OF 13

**DATA SHEETS- A&B  
FOR CONTROL VALVES**



**DATA SHEET FOR CONTROL VALVES  
(WITH PNEUMATIC ACTUATOR)  
For  
OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at  
Jharsuguda, Odisha**

SPECIFICATION NO.: PE-TS-391-142-N101

VOLUME II - B

SECTION D

REV. NO. 0

DATE : 05.07.2014

SHEET 2 OF 13

### INDEX

**Control Valve datasheets for**

| Sl. No. | TAG No. | SERVICE   | SHEET |
|---------|---------|---|-------|
| 1.      | ASV-22  | MAIN STEAM TO AUXILIARY STEAM PRESSURE REDUCING & DEUPERHEATING VALVE (COMBINED TYPE HC PRDS) | 3-4   |
| 2.      | ASV-26  | COLD REHEAT STEAM TO AUXILIARY STEAM PRESSURE REDUCING VALVE (LC PRV)                         | 5-6   |
| 3.      | CDV-151 | SPRAY CONTROL VALVE TO COMBINED TYPE HC PRDS  | 7-8   |
| 4.      | CDV-157 | SPRAY CONTROL VALVE TO LOW TEMP. DESUPERHEATER (DESH-2)                                       | 9-10  |
| 5.      | CVD-93  | SPRAY CONTROL VALVE TO TGS DESUPERHEATER  | 11-12 |
| 6.      | ----    | DATASHEET FOR ACCESSORIES   | 13    |

|                                       |   |                   |    |
|---------------------------------------|---|-------------------|----|
| SPECIFICATION NO.: PE-TS-391-142-N101 |   |                   |    |
| VOLUME                                |   | II - B            |    |
| SECTION                               |   | D                 |    |
| REV. NO.                              | 0 | DATE : 05.07.2014 |    |
| SHEET                                 | 3 | OF                | 13 |

## DATA SHEET – A & B

| DATA SHEET – A FOR CONTROL VALVE (WITH PNEUMATIC ACTUATOR)<br>(TO BE FILLED BY PURCHASER) |  |  |  |  |  | DATA SHEET – B<br>(TO BE FILLED UP BY BIDDER)   |  |  |  |  |  |
|---|--|--|--|--|--|---|--|--|--|--|--|
| GENERAL*  |  | PROJECT<br>SERVICE<br>LOCATION<br>DUTY<br>PIPE SIZE (inlet / outlet)<br>PIPE MATERIAL (inlet / outlet)   |  |  |  | RRVUNL - 2 x 660 MW Suratgarh<br><b>COMBINED TYPE MAIN STEAM TO AUX.<br/>STEAM PRDS (HC PRDS)</b><br>[•] INDOOR      [] OUTDOOR<br>[] ON/OFF        [•] MODULATING<br>Ø 219.1x 34       Ø 508 x 9.53<br>SA 335 P91        SA 335 P22  |  |  |  |  |  |
| BODY*   |  | MODEL NO.<br>TYPE OF BODY: GUIDING : NO. OF PORTS<br>BODY SIZE: PORT SIZE: DESIGN CV<br>END CONNECTION & RATING (ANSI)<br>BODY MATERIAL<br><br>PACKING: MATERIAL SINGLE / DOUBLE<br>BONNET TYPE<br>TRIM FORM<br><br>TRIM MATERIAL: SEAT   PLUG<br>: CAGE   GUIDE BUSH<br><br>FLOW<br>OUTLET VELOCITY<br>REQUIRED LEAKAGE CLASS<br>NOISE LEVEL (dBA) (spec. 3.1.14)<br>VACUUM SERVICE<br>ANTI CAVITATION TRIM |  |  |  | BIDDER TO SPECIFY<br>[] GLOBE [•] ANGLE   [] TOP [•] CAGE   ONE<br><br>[•] BWE [] SWE [] FLANGED<br>[] A216 WCB [] A217 WC6 [•] SA182 F91 [] SS<br>[] A217 C5    [] A351 CF8M<br>[] PTFE [•] GRAFOIL [] DOUBLE [•] SINGLE<br>[] STD [] EXTENDED [•] FINNED<br>[] LINEAR [•] EQ. PERCENTAGE<br>[] QUICK OPEN (ON/OFF)<br>SS316 (ST)          SS316 (ST)<br>SS316 (ST)          SS316 (ST)<br>[] BELOW SEAT [] ABOVE SEAT<br>[] < 7 M/SEC (WATER)   [•] MAC NO. < 1/3 (STM)<br>[] II [] III [] IV [•] V [] VI<br>LESS THAN 85 dBA (AT ONE METER DESTANCE)<br>[] YES [•] NO<br>[] YES [•] NO |  |  |  |  |  |
| PNEUMATIC ACTUATOR  |  | MODEL NO. & SIZE<br>CLOSE AT : OPEN AT (KG/CM2g)<br>*TRAVEL TIME FOR OPEN TO CLOSE AND }<br>CLOSE TO OPEN<br>*VALVE POSN. ON SIGNAL AIR FAILURE<br>*VALVE POSN. ON SUPPLY AIR FAILURE  |  |  |  | PNEUMATIC PISTON TYPE<br>0.2                                 1.0<br><br>LESS THAN 10 SECS.<br>[] TO OPEN [] STAYPUT [•] TO CLOSE<br>[•] STAYPUT   |  |  |  |  |  |
| ACCESSORIES   |  | POSITIONER (SMART)<br>AIR FILTER REGULATOR<br>AIR LOCK RELAY<br>POSITION LIMIT SWITCH<br>POSITION TRANSMITTER<br>SOLENOID VALVE<br>E/P CONVERTOR<br>JUNCTION BOX<br>HAND WHEEL (SIDE MOUNTED)<br>LOCAL POSITION INDICATOR  |  |  |  | [•] REQUIRED [] NOT REQUIRED<br>[•] REQUIRED [] NOT REQUIRED<br>[•] REQUIRED [] NOT REQUIRED<br>[•] REQUIRED [] NOT REQUIRED<br>PART OF SMART POSITIONER<br>[•] REQUIRED [] NOT REQUIRED<br>PART OF SMART POSITIONER<br>[•] REQUIRED [] NOT REQUIRED<br>[•] REQUIRED<br>[•] REQUIRED  |  |  |  |  |  |



|                                       |   |                   |    |
|---------------------------------------|---|-------------------|----|
| SPECIFICATION NO.: PE-TS-391-142-N101 |   |                   |    |
| VOLUME                                |   | II - B            |    |
| SECTION                               |   | D                 |    |
| REV. NO.                              | 0 | DATE : 05.07.2014 |    |
| SHEET                                 | 4 | OF                | 13 |

Data Sheet No. PES-145-06-DS1-0

## DATA SHEET – A & B

DATA SHEET – B  
(TO BE FILLED UP BY  
BIDDER)

$\pm 2\%$   
 $\pm 1\%$   
 $\pm 0.5\%$   
 $+ 2\%$

VALVE  
O/L  
VELOCITY

**Refer Sizing Data Sheet A-1 for Aux. Steam PRDS**  
(Case-1 is the capability point for control valve ASV-22 )

☐ CAVITATION    ☐ FLASHING  
☒ HIGH DP

|   |  |
|---|--|
| * MAX SHUT OFF PRESS ( KG/CM2(A)                | <b>271</b>   |
| * BODY DESIGN : PRESS (KG/CM2(A)   TEMP (DEG C) | 271   <b>573</b>   |
| * IBR FORM III-C                                | <input checked="" type="checkbox"/> REQUIRED <input type="checkbox"/> NOT REQUIRED |

TOTAL WEIGHT (VALVE + ACTUATOR + ACCESSORIES) Kg

NOTES:

1. DESI GN C<sub>v</sub> SHALL BE BASED ON SERVICE CONDITIONS INDICATED AS PER SPECIFICATION CLAUSE NUMBER 3.1.7. OF SPECIFICATION NO. : PES – 145 – 06 VOL IIB SECTION D OF TECHNICAL SPECIFICATION



**DATA SHEET FOR CONTROL VALVES  
(WITH PNEUMATIC ACTUATOR)  
For  
OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at  
Jharsuguda, Odisha**

SPECIFICATION NO.: PE-TS-391-142-N101

VOLUME II - B

SECTION D

REV. NO.

0

DATE : 05.07.2014

SHEET

5

OF

13

Tag No.: **ASV-26**Qty.: **ONE PER UNIT**  
**DATA SHEET – A & B**

Data Sheet No. PES-145-06-DS1-0

| DATA SHEET – A FOR CONTROL VALVE (WITH PNEUMATIC ACTUATOR)<br>(TO BE FILLED BY PURCHASER) |  | DATA SHEET – B<br>(TO BE FILLED UP BY BIDDER)  |  |
|---|--|--|--|
| GENERAL *   | PROJECT SERVICE                                  | RRVUNL - 2 x 660 MW Suratgarh<br>COLD REHEAT STEAM TO AUXILIARY<br>STEAM PR. REDUCING VALVE (LC PRV) |  |
|   | LOCATION   | [•] INDOOR      [ ] OUTDOOR  |  |
| BODY *  | DUTY   | [ ] ON/OFF      [•] MODULATING   |  |
|   | PIPE SIZE (inlet / outlet)                       | Ø 114.3x6.02             Ø 219.1 x 8.18  |  |
|   | PIPE MATERIAL (inlet / outlet)                   | SA 106 Gr. B             SA 106 Gr. B  |  |
|   | MODEL NO.  | BIDDER TO SPECIFY  |  |
|   | TYPE OF BODY: GUIDING : NO. OF PORTS             | [•] GLOBE [ ] ANGLE [ ] TOP [•] CAGE [ ] ONE   |  |
|   | BODY SIZE: PORT SIZE: DESIGN CV                  |  |  |
|   | END CONNECTION & RATING (ANSI)                   | [•] BWE [ ] SWE [ ] FLANGED  |  |
|   | BODY MATERIAL                                    | [ ] A216 WCC [•] A217 WC9 [ ] SS [ ] A217 C5 [ ] A351 CF8M   |  |
|   | PACKING: MATERIAL SINGLE / DOUBLE                | [ ] PTFE [•] GRAFOIL [ ] DOUBLE [•] SINGLE   |  |
|   | BONNET TYPE                                      | [ ] STD [•] EXTENDED [ ] FINNED  |  |
| TRIM FORM   | [ ] LINEAR [•] EQ. PERCENTAGE                    |  |  |
| TRIM MATERIAL: SEAT   PLUG  | [ ] QUICK OPEN (ON/OFF)                          |  |  |
| : CAGE   GUIDE BUSH   | SS316 (ST)             SS316 (ST)                |  |  |
| FLOW  | SS316 (ST)             SS316 (ST)                |  |  |
| OUTLET VELOCITY   | [ ] BELOW SEAT [ ] ABOVE SEAT                    |  |  |
| REQUIRED LEAKAGE CLASS  | [ ] < 7 M/SEC (WATER)   [•] MAC NO. < 1/3 (STM)  |  |  |
| NOISE LEVEL (dBA) (spec. 3.1.14)  | [ ] II [ ] III [ ] IV [•] V [ ] VI               |  |  |
| VACUUM SERVICE  | LESS THAN 85 Dba (AT ONE METER DISTANCE)         |  |  |
| ANTI CAVITATION TRIM  | [ ] YES [•] NO                                   |  |  |
| PNEUMATIC ACTUATOR  | MODEL NO. & SIZE                                 | BIDDER TO SPECIFY  |  |
|   | CLOSE AT : OPEN AT (KG/CM2g)                     | 1.0             0.2  |  |
|   | *TRAVEL TIME FOR OPEN TO CLOSE AND CLOSE TO OPEN | LESS THAN 10 SECS.   |  |
| *VALVE POSN. ON SIGNAL AIR FAILURE  | [•] TO OPEN [ ] STAYPUT [ ] TO CLOSE             |  |  |
| *VALVE POSN. ON SUPPLY AIR FAILURE  | [•] STAYPUT                                      |  |  |
| ACCESSORIES   | POSITIONER (SMART)                               | [•] REQUIRED [ ] NOT REQUIRED  |  |
|   | AIR FILTER REGULATOR                             | [•] REQUIRED [ ] NOT REQUIRED  |  |
|   | AIR LOCK RELAY                                   | [•] REQUIRED [ ] NOT REQUIRED  |  |
|   | POSITION LIMIT SWITCH                            | [•] REQUIRED [ ] NOT REQUIRED  |  |
|   | POSITION TRANSMITTER                             | PART OF SMART POSITIONER   |  |
|   | SOLENOID VALVE                                   | [•] REQUIRED [ ] NOT REQUIRED  |  |
|   | E/P CONVERTOR                                    | PART OF SMART POSITIONER   |  |
|   | JUNCTION BOX                                     | [•] REQUIRED [ ] NOT REQUIRED  |  |
|   | HAND WHEEL (SIDE MOUNTED)                        | [•] REQUIRED   |  |
|   | LOCAL POSITION INDICATOR                         | [•] REQUIRED   |  |

|                                       |   |                   |    |
|---------------------------------------|---|-------------------|----|
| SPECIFICATION NO.: PE-TS-391-142-N101 |   |                   |    |
| VOLUME                                |   | II - B            |    |
| SECTION                               |   | D                 |    |
| REV. NO.                              | 0 | DATE : 05.07.2014 |    |
| SHEET                                 | 6 | OF                | 13 |

Data Sheet No. PES-145-06-DS1-0

## DATA SHEET – A & B

DATA SHEET – B  
(TO BE FILLED UP BY  
BIDDER)

|             |
|-------------|
| $\pm 2\%$   |
| $\pm 1\%$   |
| $\pm 0.5\%$ |
| $+ 2\%$     |

VALVE  
O/L  
VELOCITY

VALVE TYPE

☐ CAVITATION    ☐ FLASHING  
☒ HIGH DP

\* MAX SHUT OFF PRESS ( KG/CM2(A)

74.1

BODY DESIGN : PRESS (KG/CM2(A) | TEMP (DEG C) 74.1 | **360**  
 \* IBR FORM III-C [• REQUIRED] [ ] NOT REQUIRED

TOTAL WEIGHT (VALVE + ACTUATOR + ACCESSORIES) Kg

NOTES:

1. DESI GN C<sub>V</sub> SHALL BE BASED ON SERVICE CONDITIONS INDICATED AS PER SPECIFICATION CLAUSE NUMBER 3.1.7. OF SPECIFICATION NO. : PES – 145 – 06 VOL IIB SECTION D OF TECHNICAL SPECIFICATION



|                                       |   |                   |    |
|---------------------------------------|---|-------------------|----|
| SPECIFICATION NO.: PE-TS-391-142-N101 |   |                   |    |
| VOLUME                                |   | II - B            |    |
| SECTION                               |   | D                 |    |
| REV. NO.                              | 0 | DATE : 05.07.2014 |    |
| SHEET                                 | 8 | OF                | 13 |

Data Sheet No. PES-145-06-DS1-0

## DATA SHEET – A & B

**DATA SHEET – B**  
**(TO BE FILLED UP BY**  
**BIDDER)**

|                         |                    |             |       |
|-------------------------|--------------------|-------------|-------|
| PERFORMANCE<br>OF VALVE | LINEARITY          | $\pm 2\%$   | ..... |
|                         | HYSTERESIS         | $\pm 1\%$   | ..... |
|                         | SENSITIVITY        | $\pm 0.5\%$ | ..... |
|                         | ACCURACY (OVERALL) | $\pm 2\%$   | ..... |

|   |              |   |                |                        |                            |                 |   |                 |                          |
|---|--------------|---|----------------|------------------------|----------------------------|-----------------|---|-----------------|--------------------------|
|   | SL.<br>No. + | LOAD  | FLOW<br>(T/HR) | INLET PR.<br>KG/CM2(A) | OUTLET<br>PR.<br>KG/CM2(A) | TEMP<br>DEG (C) | CALCU-<br>LATED<br>CV   | % VALVE<br>LIFT | VALVE<br>O/L<br>VELOCITY |
|   |              |   |                |                        |                            |                 |   |                 |                          |
| SERVICE<br>CONDITION*   |              | <b>Refer Sizing Data Sheet A-1 for High Capacity PRDS</b> |                |                        |                            |                 |   |                 |                          |
|   |              |   |                |                        |                            |                 |   |                 |                          |
|   |              |   |                |                        |                            |                 |   |                 |                          |
|   |              |   |                |                        |                            |                 |   |                 |                          |
| VALVE TYPE  |              |   |                |                        |                            |                 | <input type="checkbox"/> CAVITATION <input type="checkbox"/> FLASHING<br><br><input type="checkbox"/> HIGH DP |                 |                          |
| * MAX SHUT OFF PRESS ( KG/CM2(A)                      46<br>* BODY DESIGN : PRESS (KG/CM2(A)   TEMP (DEG C)    46   <b>60</b><br>* IBR FORM III-C <input type="checkbox"/> REQUIRED    [•] NOT REQUIRED |              |   |                |                        |                            |                 | .....<br>..... .....<br>.....   |                 |                          |

TOTAL WEIGHT (VALVE + ACTUATOR + ACCESSORIES) Kg

---

NOTES:

1. DESI GN C<sub>v</sub> SHALL BE BASED ON SERVICE CONDITIONS INDICATED AS PER SPECIFICATION CLAUSE NUMBER 3.1.7. OF SPECIFICATION NO. : PES – 145 – 06 VOL IIB SECTION D OF TECHNICAL SPECIFICATION



**DATA SHEET FOR CONTROL VALVES  
(WITH PNEUMATIC ACTUATOR)  
For  
OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at  
Jharsuguda, Odisha**

SPECIFICATION NO.: PE-TS-391-142-N101

VOLUME II - B

SECTION D

REV. NO.

0

DATE : 05.07.2014

SHEET

9

OF

13

Tag No.: **CDV-157**Qty.: **ONE EACH PER UNIT**

Data Sheet No. PES-145-06-DS1-0

**DATA SHEET – A & B**

**DATA SHEET – A FOR CONTROL VALVE (WITH PNEUMATIC ACTUATOR)  
(TO BE FILLED BY PURCHASER)**

**DATA SHEET – B  
(TO BE FILLED UP BY  
BIDDER)**

**GENERAL\***

PROJECT

SERVICE

LOCATION

DUTY

PIPE SIZE (inlet / outlet)

PIPE MATERIAL (inlet / outlet)

**RRVUNL - 2 x 660 MW Suratgarh****SPRAY TO LT DESH CONTROL VALVE**

[•] INDOOR      [ ] OUTDOOR

[ ] ON/OFF      [•] MODULATING

Ø 48.3 x5.08      |      Ø 48.3 x5.08

SA 106 Gr. B      |      SA 106 Gr. B

**BODY\***

MODEL NO.

TYPE OF BODY: GUIDING : NO. OF PORTS

BODY SIZE: PORT SIZE: DESIGN CV

END CONNECTION &amp; RATING (ANSI)

BODY MATERIAL

PACKING: MATERIAL SINGLE / DOUBLE

BONNET TYPE

TRIM FORM

TRIM MATERIAL: SEAT | PLUG

: CAGE | GUIDE BUSH

FLOW

OUTLET VELOCITY

REQUIRED LEAKAGE CLASS

NOISE LEVEL (dBA) (spec. 3.1.14)

VACUUM SERVICE

ANTI CAVITATION TRIM

BIDDER TO SPECIFY

[•] GLOBE [ ] ANGLE [ ] TOP [•] CAGE [ ] ONE

[ ] BWE [•] SWE [ ] FLANGED

[ ] A216 WCB [•] A217 WC6 [ ] SS [ ] A217 C5

[ ] A351 CF8M

[ ] PTFE [•] GRAFOIL [ ] DOUBLE [•] SINGLE

[ ] STD [ ] EXTENDED [ ] FINNED

[ ] LINEAR [•] EQ. PERCENTAGE

[ ] QUICK OPEN (ON/OFF)

SS-316 | SS-316

SS-316 | SS-316

[ ] BELOW SEAT [ ] ABOVE SEAT

[•] &lt; 7 M/SEC (WATER) [ ] MAC NO &lt; 1/3

(STM)

[ ] II [ ] III [ ] IV [•] V [ ] VI

LESS THAN 85 dBA (AT ONE METER DESTANCE)

[ ] YES [•] NO

[ ] YES [•] NO

**PNEUMATIC  
ACTUATOR**

MODEL NO. &amp; SIZE

CLOSE AT : OPEN AT (KG/CM2g)

\*TRAVEL TIME FOR OPEN TO CLOSE } AND CLOSE TO OPEN

\*VALVE POSN. ON SIGNAL AIR FAILURE

\*VALVE POSN. ON SUPPLY AIR FAILURE

BIDDER TO SPECIFY

0.2      |      1.0

LESS THAN 10 SECS.

[ ] TO OPEN [ ] STAYPUT [•] TO CLOSE

[•] STAYPUT

**ACCESSORIES**

POSITIONER (SMART)

AIR FILTER REGULATOR

AIR LOCK RELAY

POSITION LIMIT SWITCH

POSITION TRANSMITTER

SOLENOID VALVE

E/P CONVERTOR

JUNCTION BOX

HAND WHEEL (SIDE MOUNTED)

LOCAL POSITION INDICATOR

[•] REQUIRED [ ] NOT REQUIRED

[•] REQUIRED [ ] NOT REQUIRED

[•] REQUIRED [ ] NOT REQUIRED

[•] REQUIRED [ ] NOT REQUIRED

PART OF SMART POSITIONER

[•] REQUIRED [ ] NOT REQUIRED

PART OF SMART POSITIONER

[•] REQUIRED [ ] NOT REQUIRED

[•] REQUIRED

[•] REQUIRED

|                                       |    |                   |    |
|---------------------------------------|----|-------------------|----|
| SPECIFICATION NO.: PE-TS-391-142-N101 |    |                   |    |
| VOLUME                                |    | II - B            |    |
| SECTION                               |    | D                 |    |
| REV. NO.                              | 0  | DATE : 05.07.2014 |    |
| SHEET                                 | 10 | OF                | 13 |

Data Sheet No. PES-145-06-DS1-0

## DATA SHEET – A & B

DATA SHEET – B  
(TO BE FILLED UP BY  
BIDDER)

|             |
|-------------|
| $\pm 2\%$   |
| $\pm 1\%$   |
| $\pm 0.5\%$ |
| $+ 2\%$     |

VALVE  
O/L  
VELOCITY

**Refer Sizing Data Sheet A-3 for Low Capacity PRDS**

☐ CAVITATION    ☐ FLASHING

☐ HIGH DP

|  |  |
|--|--|
| * MAX SHUT OFF PRESS ( KG/CM2 (A)                | 46   |
| * BODY DESIGN : PRESS (KG/CM2 (A)   TEMP (DEG C) | 46   60  |
| * IBR FORM III-C                                 | <input type="checkbox"/> REQUIRED <input checked="" type="checkbox"/> NOT REQUIRED |

TOTAL WEIGHT (VALVE + ACTUATOR + ACCESSORIES) Kg

NOTES:

1. DESI GN C<sub>v</sub> SHALL BE BASED ON SERVICE CONDITIONS INDICATED AS PER SPECIFICATION CLAUSE NUMBER 3.1.7. OF SPECIFICATION NO. : PES – 145 – 06 VOL IIB SECTION D OF TECHNICAL SPECIFICATION



**DATA SHEET FOR CONTROL VALVES  
(WITH PNEUMATIC ACTUATOR)  
For  
OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at  
Jharsuguda, Odisha**

SPECIFICATION NO.: PE-TS-391-142-N101

VOLUME II - B

SECTION D

REV. NO.

0

DATE : 05.07.2014

SHEET

11

OF

13

Tag No.: **CDV-93**Qty.: **ONE PER UNIT**

Data Sheet No. PES-145-06-DS1-0

**DATA SHEET – A & B**

**DATA SHEET – A FOR CONTROL VALVE (WITH PNEUMATIC ACTUATOR)  
(TO BE FILLED BY PURCHASER)**

**DATA SHEET – B  
(TO BE FILLED UP BY  
BIDDER)**

**GENERAL\***

PROJECT

SERVICE

LOCATION

DUTY

PIPE SIZE (inlet / outlet)

PIPE MATERIAL (inlet / outlet)

**RRVUNL - 2 x 660 MW Suratgarh****SPRAY TO TGS DESUPERHEATER (DESH-3)**☐ INDOOR ☐ OUTDOOR☐ ON/OFF ☐ MODULATING**Ø 33.4 x4.55 | Ø 33.4 x4.55****SA 106 Gr. B | SA 106 Gr. B****BODY\***

MODEL NO.

TYPE OF BODY: GUIDING : NO. OF PORTS

BODY SIZE: PORT SIZE: DESIGN CV

END CONNECTION &amp; RATING (ANSI)

BODY MATERIAL

PACKING: MATERIAL SINGLE / DOUBLE

BONNET TYPE

TRIM FORM

TRIM MATERIAL: SEAT | PLUG

: CAGE | GUIDE BUSH

FLOW

OUTLET VELOCITY

REQUIRED LEAKAGE CLASS

NOISE LEVEL (dBA) (spec. 3.1.14)

VACUUM SERVICE

ANTI CAVITATION TRIM

BIDDER TO SPECIFY

☐ GLOBE ☐ ANGLE ☐ TOP ☐ CAGE ☐ ONE☐ BWE ☐ SWE ☐ FLANGED☐ A216 WCB ☐ A217 WC6 ☐ SS ☐ A217 C5☐ A351 CF8M☐ PTFE ☐ GRAFOIL ☐ DOUBLE ☐ SINGLE☐ STD ☐ EXTENDED ☐ FINNED☐ LINEAR ☐ EQ. PERCENTAGE☐ QUICK OPEN (ON/OFF)

SS-316 | SS-316

SS-316 | SS-316

☐ BELOW SEAT ☐ ABOVE SEAT☐ < 7 M/SEC (WATER) | ☐ MAC NO < 1/3

(STM)

☐ II ☐ III ☐ IV ☐ V ☐ VI

LESS THAN 85 dBA (AT ONE METER DESTANCE)

☐ YES ☐ NO☐ YES ☐ NO**PNEUMATIC  
ACTUATOR**

MODEL NO. &amp; SIZE

CLOSE AT : OPEN AT (KG/CM2g)

\*TRAVEL TIME FOR OPEN TO CLOSE

AND CLOSE TO OPEN

\*VALVE POSN. ON SIGNAL AIR FAILURE

\*VALVE POSN. ON SUPPLY AIR FAILURE

BIDDER TO SPECIFY

0.2

1.0

LESS THAN 10 SECS.

☐ TO OPEN ☐ STAYPUT ☐ TO CLOSE☐ STAYPUT**ACCESSORIES**

POSITIONER (SMART)

AIR FILTER REGULATOR

AIR LOCK RELAY

POSITION LIMIT SWITCH

POSITION TRANSMITTER

SOLENOID VALVE

E/P CONVERTOR

JUNCTION BOX

HAND WHEEL (SIDE MOUNTED)

LOCAL POSITION INDICATOR

☐ REQUIRED ☐ NOT REQUIRED☐ REQUIRED ☐ NOT REQUIRED☐ REQUIRED ☐ NOT REQUIRED☐ REQUIRED ☐ NOT REQUIRED

PART OF SMART POSITIONER

☐ REQUIRED ☐ NOT REQUIRED

PART OF SMART POSITIONER

☐ REQUIRED ☐ NOT REQUIRED☐ REQUIRED☐ REQUIRED



|                                       |    |                   |    |
|---------------------------------------|----|-------------------|----|
| SPECIFICATION NO.: PE-TS-391-142-N101 |    |                   |    |
| VOLUME                                |    | II - B            |    |
| SECTION                               |    | D                 |    |
| REV. NO.                              | 0  | DATE : 05.07.2014 |    |
| SHEET                                 | 12 | OF                | 13 |

Data Sheet No. PES-145-06-DS1-0

## DATA SHEET – A & B

DATA SHEET – B  
(TO BE FILLED UP BY  
BIDDER)

|             |
|-------------|
| $\pm 2\%$   |
| $\pm 1\%$   |
| $\pm 0.5\%$ |
| $+ 2\%$     |

**Refer Sizing Data Sheet A-4 for TGS DESUPERHEATER**

☐ CAVITATION    ☐ FLASHING  
☐ HIGH DP

.....

..... | .....

.....

.....

1. DESI GN C<sub>v</sub> SHALL BE BASED ON SERVICE CONDITIONS INDICATED AS PER SPECIFICATION CLAUSE NUMBER 3.1.7. OF SPECIFICATION NO. : PES – 145 – 06 VOL IIB SECTION D OF TECHNICAL SPECIFICATION

|  |   |               |  |   |  |   |
|--|---|---------------|--|---|--|---|
|  | <b>DATA SHEET FOR CONTROL VALVES<br/>(WITH PNEUMATIC ACTUATOR)</b>  |               |  | SPECIFICATION NO.: PE-TS-387-145-I106   |  |   |
|  |   |               |  | VOLUME IIB  |  |   |
|  |   |               |  | SECTION D   |  |   |
|  |   |               |  | REV. NO. 00   | DATE :07.11.2012   |   |
|  |   |               |  | SHEET   |  | OF  |
| <b>Tag No: Applicable for all tag nos.      Quantity: As required      Data Sheet No. PES-145-06-DS1-0</b> |   |               |  |   |  |   |
| <b>Applicable for tag nos. wherever statement "REQUIRED" indicated in the individual CV data sheets</b>    |   |               |  |   |  |   |
| <b>DATA SHEET – A &amp; B for ACCESSORIES</b>  |   |               |  |   |  |   |
| <b>DATA SHEET – A FOR CONTROL VALVE (WITH PNEUMATIC ACTUATOR)</b>  |   |               |  |   |  |   |
| SMART POSITIONER<br>(UNIVERSAL HART<br>PROTOCOL BASED)   | MFR. & MODEL NUMBER   |               | Bidder to Specify  |   |  |   |
|  | BYPASS  | GAUGES        | ENCL. CLASS  | <input type="checkbox"/> YES<br><input checked="" type="checkbox"/> NO                                | <input type="checkbox"/> THREE <input checked="" type="checkbox"/> TWO | <input checked="" type="checkbox"/> IP – 65 |
|  | INPUT SIGNAL  |               | 4- 20 mA DC  |   |  |   |
|  | OUTPUT SIGNAL (Kg / Cm <sup>2</sup> ) T   |               | O SUIT ACTUATOR  |   |  |   |
| AIR FILTER<br>REGULATOR<br>TWO (2) Nos./CV<br><=5MICRON<br>(SINTERED BRONZE)                               | MFR. & MODEL NUMBER   |               | Bidder to Specify  |   |  |   |
|  | AIR SUPPLY PRESS (MAX.) (Kg / Cm <sup>2</sup> g)  |               | <input checked="" type="checkbox"/> 7.0 <input type="checkbox"/>   |   |  |   |
|  | OUTPUT PRESS (Kg / Cm <sup>2</sup> g)   |               | TO SUIT ACTUATOR   |   |  |   |
|  | OUTPUT GAUGE  |               | <input checked="" type="checkbox"/> REQUIRED (2 Inch) <input type="checkbox"/> NOT REQUIRED  |   |  |   |
| AIR LOCK   | MFR. & MODEL NUMBER   |               | Bidder to Specify  |   |  |   |
|  | SET PRESS (Kg / Cm <sup>2</sup> )   |               |  |   |  |   |
|  | SUPPLY PRESS (MAX.) (Kg / Cm <sup>2</sup> )   |               | <input checked="" type="checkbox"/> 7.0 <input type="checkbox"/>   |   |  |   |
|  | RESET TYPE  |               | AUTO   |   |  |   |
|  | VENT PLUG   |               | REQUIRED   |   |  |   |
| LIMIT SWITCH   | MFR. & MODEL NUMBER   |               | Bidder to Specify  |   |  |   |
|  | OPEN posn   | INT posn      | CLOSE posn   | <input checked="" type="checkbox"/> 1 NO. <input type="checkbox"/> --- <input type="checkbox"/> 1 NO. |  |   |
|  | CONTACT TYPE  |               | SPDT   |   |  |   |
|  | RATING (AC / DC)  |               | 5A 240V AC AND 0.5A 220V DC  |   |  |   |
|  | ENCLOSURE CLASS   |               | <input type="checkbox"/> NEMA-4 <input checked="" type="checkbox"/> IP-65  |   |  |   |
| POSITION<br>TRANSMITTER  | MFR. & MODEL NUMBER   |               | Bidder to Specify (Part of SMART Positioner)   |   |  |   |
|  | TYPE  |               | <input checked="" type="checkbox"/> Electronic (2-Wire) Contactless <input type="checkbox"/> OTHER   |   |  |   |
|  | SUPPLY  |               | <input checked="" type="checkbox"/> 24V DC <input type="checkbox"/> 220V DC <input type="checkbox"/> 110V AC <input type="checkbox"/> 240V AC                  |   |  |   |
|  | OUTPUT RATING   |               | <input checked="" type="checkbox"/> 4-20mA <input type="checkbox"/> 0-100 ohms   |   |  |   |
|  | ACCURACY +  |               | _ 2% FS  |   |  |   |
|  | ENCLOSURE CLASS   |               | <input type="checkbox"/> NEMA-4 <input checked="" type="checkbox"/> IP-65  |   |  |   |
| SOLENOID<br>VALVE  | MFR. & MODEL NUMBER   |               | ROTEX / ASCO   |   |  |   |
|  | RATING  |               | <input checked="" type="checkbox"/> 24V DC <input type="checkbox"/> 220V DC <input type="checkbox"/> 240V AC <input type="checkbox"/>                          |   |  |   |
|  | OPERATION Q   | UANTITY       |  | <input type="checkbox"/> Stayput <input checked="" type="checkbox"/> Interlock                        | <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2       |   |
|  | COIL INSULATION CLASS   |               | CLASS - H  |   |  |   |
|  | ENCLOSURE CLASS   |               | <input type="checkbox"/> NEMA-4 <input checked="" type="checkbox"/> IP-65  |   |  |   |
|  | BODY & TRIM   |               | SS BAR STOCK & AISI SS-316 respectively  |   |  |   |
| JUNCTION BOX   | NO. OF WAYS   |               | <input type="checkbox"/> 24-WAYS <input type="checkbox"/> AS REQUIRED <input checked="" type="checkbox"/> 36-Ways  |   |  |   |
|  | SIZE AS   |               | REQUIRED   |   |  |   |
|  | CABLE GLANDS (Size / Quantity)  |               | AS REQUIRED (Double Compression Type).   |   |  |   |
|  | ENCLOSURE CLASS   |               | <input type="checkbox"/> NEMA-4 <input checked="" type="checkbox"/> IP-65  |   |  |   |
| I/P CONVERTER<br>(Part of SMART Positioner)  | INPUT SIGNAL  | POWER SUPPLY  |  | 4-20mA DC   | 24V DC   |   |
|  | SPLIT RANGE   |               | <input type="checkbox"/> YES <input type="checkbox"/> NO   |   |  |   |
|  | ENCLOSURE CLASS   |               | <input type="checkbox"/> NEMA-4 <input checked="" type="checkbox"/> IP-65  |   |  |   |
|  | Accuracy  | Repeatability |  | ± 0.5 % FS  | ± 0.5 % FS   |   |
| Cu. Tubing & Fittings /<br>per CV  | This is in addition to cu. Tubing and fittings which are integral part of CV as per ASTM B68 to B75 (USA) |               | 25 Meters of ¼" PVC coated anneled Cu. Tubing, with 1 set of Fittings for each CV for connection to IA Header on one end and accessories on another end of CV. |   |  |   |



TITLE

**EQUIPMENT SPECIFICATIONS**

**AUXILIARY STEAM PRESSURE REDUCING  
& DESUPERHEATING STATION**

**OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at  
Jharsuguda, Odisha**

SPEC. NO.: PE-TS-391-142-N101

VOLUME **II-B**

SECTION **D**

REV NO. **00** DATE 05.07.2014

SHEET 1 OF 1

**SECTION – D**  
**EQUIPMENT SPECIFICATIONS**  
**FOR**  
**STEAM DESUPERHEATER**



TITLE

**EQUIPMENT SPECIFICATION****STEAM DESUPERHEATER**SPECIFICATION NO **PES-148-01**VOLUME **II-B**SECTION **D**REV NO. **0** DATE 05.02.2008SHEET **1 OF 3****1.0.0 GENERAL**

This standard specification covers the design, materials, construction features, manufacturing process, assembly, inspection and testing requirements, painting and packing requirements of Steam Desuperheater along with spray nozzle.

**2.0.0 CODES AND STANDARDS**

2.1.0 The design, manufacture, inspection and testing of the equipment shall comply with the requirements of the latest national and international codes and standards wherever applicable. Wherever the specific code requirements are specified herein, the same shall be adhered to.

In particular, the equipment shall be designed to comply with latest editions of the following standards

- (i) Indian Boiler Regulations (IBR).
- (ii) ASME Section - VIII / Div. - 1.
- (iii) Material specifications as per ASTM, AISI.


**3.0.0 DESIGN AND CONSTRUCTIONAL FEATURES**

3.1.0 The desuperheater shall be of direct mixing mechanical spray type. The assembly shall consist of desuperheater pipe with steam inlet and outlet & spray water connection along with spray nozzle. The spray nozzle shall direct the spray in the direction of steam flow for proper mixing and arranged in such position that direct impingement of spray water on desuperheater walls is avoided.

3.2.0 The spray nozzle shall be accurately sized for best results in total range as stipulated in the data sheet.

3.3.0 The desuperheater shall be complete with matching counter flanges including bolts, nuts, gaskets, necessary reducers / expanders to suit purchaser's pipe line and supporting legs / pads & holding down bolts as required.

3.4.0 The material of construction shall be as indicated in Data Sheet – A.

|   |   |                                    |                 |
|---|---|------------------------------------|-----------------|
|  | TITLE<br><br><b>EQUIPMENT SPECIFICATION</b><br><br><b>STEAM DESUPERHEATER</b> | SPECIFICATION NO <b>PES-148-01</b> |                 |
|   |   | VOLUME <b>II-B</b>                 |                 |
|   |   | SECTION <b>D</b>                   |                 |
|   |   | REV NO. <b>0</b>                   | DATE 05.02.2008 |
|   |   | SHEET <b>2 OF 3</b>                |                 |

**4.0.0 SHOP INSPECTION AND TEST**

4.1.0 The bidder shall submit along with the offer the Quality Plans in the enclosed format together with all reference documents/standards etc. as applicable.

4.2.0 Indicative Quality Plans, specifying minimum checks and tests as considered necessary are enclosed along with this specification for compliance. These however are not intended to exhibit the total comprehensive testing programmes, which are the responsibility of the bidder.

4.3.0 Detailed Quality Plans to be submitted by the bidders should also include all the checks/tests carried out by the suppliers as part of their normal practice. The Quality Plans submitted by the bidders shall be subject to approval of BHEL/their Customer who reserves the right to ask for further checks during finalization of Quality Plans. BHEL/their Customer shall indicate customer hold points in the approved Quality Plans beyond which the work shall not proceed without their approval.

4.4.0 The supplier shall furnish their production program along with scheduled dates of testing at least three months in advance to enable BHEL/their customer to plan for witnessing the tests identified as hold points.

4.5.0 Material identification and co-relation with test certificates for all major components shall be essentially required. In absence of these, the material of each component shall be tested as per relevant specification for Chemical Composition and Mechanical properties i.e. Yield Stress, Ultimate Tensile Stress, Impact test, % Elongation, % Reduction in Area, Hardness etc. In addition, to ensure freedom from surface and sub-surface defects, suitable Non Destructive Testing shall also be carried out.

4.6.0 Following tests shall be done at Manufacturers' works during various stages as minimum requirement:


4.6.1 Visual examination of all components.

4.6.2 Check for weld joints for proper fit up, Dye Penetration Test after root run and final welding. 100% Radiographic test as per ASTM E 165 for all butt welds.

4.6.3 Verification of stress relieving chart if post-weld heat treatment is called for.

4.6.4 Check / test for pressure retaining bolts and nuts as per relevant Codes/Standards.

4.6.5 Dimension check for all components including surface finish.

|  |   |                                    |                 |
|--|---|------------------------------------|-----------------|
|   | TITLE<br><br><b>EQUIPMENT SPECIFICATION</b><br><br><b>STEAM DESUPERHEATER</b> | SPECIFICATION NO <b>PES-148-01</b> |                 |
|  |   | VOLUME <b>II-B</b>                 |                 |
|  |   | SECTION <b>D</b>                   |                 |
|  |   | REV NO. <b>0</b>                   | DATE 05.02.2008 |
|  |   | SHEET <b>3 OF 3</b>                |                 |
| <p>4.6.6 Hydraulic Test to two times the rated design pressure for desuperheater body and other pressure retaining parts.</p> <p>4.6.7 Check for final completeness, cleaning, surface finish, appearance, identification, surface preparation, painting, marking and packing including spares.</p> <p>4.6.8 The equipment comes under the purview of IBR (Indian Boiler Regulations). All tests certificates duly signed by Chief Inspector (IBR) / authorized representative shall be furnished in IBR from III-C.</p> <p>4.6.9 The particulars of proposed shop tests and process of test shall be submitted to BHEL/their Customer along with Quality Plan for approval.</p> <p><b>5.0.0 <u>PERFORMANCE REQUIREMENTS</u></b></p> <p>Bidder shall guarantee that equipment offered shall meet the rating and performance requirements as stipulated in this specification. In case it is not as per guarantee furnished by the bidder, the deficiency shall be made good by the bidder by rectification / replacement of defective parts within reasonable time at their own cost inclusive of cost of transportation both ways if required. The Purchaser is entitled to reject the equipment in case of repeated failures to meet the guaranteed performance.</p> <p><b>6.0.0 <u>PAINTING</u></b></p> <p>6.1.0 All foundry sand and loose material shall be removed and surface should be made thoroughly clean for further protection as required.</p> <p>6.2.0 A shop coat of paint, removable after installation at site, shall be applied to all steel surfaces and other exposed surfaces requiring corrosion protection during transit and storage at site.</p> <p><b>7.0..0 <u>PRESERVATION, MARKING AND PACKING</u></b></p> <p>7.1.0 A Stainless Steel metal nameplate should be permanently fixed on each equipment giving its Tag. No. and technical specifications i.e. Service, Size, Pressure Rating etc.</p> <p>7.2.0 All equipments / materials shall be packed suitably and protected from impact, abrasion, corrosion, incidental damage due to vermin, Sun-light, high temperature, rain, moisture, humidity, dust, sea water (where applicable) as well as rough handling during entire period of dispatch, storage and erection including delays in transit and storage in open.</p> <p>7.3.0 Spares shall be packed separately and marked clearly for identification. These shall be specially packed for long storage without damage.</p> |   |                                    |                 |



TITILE

## EQUIPMENT SPECIFICATION

### STEAM DESUPERHEATER

For

OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at  
Jharsuguda, Odisha

SPEC. NO.: PE-TS-391-142-N101

VOLUME **II-B**

SECTION **D**

REV NO. **0** DATE 05.07.2014

SHEET 1 OF 2

### DESUPERHEATER DATA SHEET A-1

#### DATA SHEET FOR LOW TEMP. DESUPERHEATER DESH-2

| S.NO | DESCRIPTION                                   | UNITS                  | DATA FOR HIGH CAP. PRDS<br>DESUPERHEATER  |
|------|---|------------------------|---|
| 1.0  | TAG NO.                                       |                        | DESH-2  |
| 2.0  | TYPE  |                        | VARIABLE ORIFICE / VENTURI TYPE   |
| 3.0  | STEAM PARAMETERS                              |                        | (INLET OF DESUPERHEATER)  |
| 3.1  | FLOW  | T/HR                   | REFER SIZING DATA SHEET A-3   |
| 3.2  | PRESSURE                                      | Kg/cm <sup>2</sup> (a) | BIDDER TO DECIDE BASED ON SIZING DATA   |
| 3.3  | TEMPERATURE                                   | °C                     | BIDDER TO DECIDE BASED ON SIZING DATA   |
| 4.0  | STEAM PARAMETERS<br>(OUTLET OF DESUPERHEATER) |                        | REFER SIZING DATA SHEET A-3   |
| 5.0  | SPRAY WATER<br>PARAMETERS                     |                        | (INLET OF DESUPERHEATER)  |
| 5.1  | FLOW  | T/HR                   | REFER SIZING DATA SHEET A-3   |
| 5.2  | PRESSURE                                      | Kg/cm <sup>2</sup> (a) | BIDDER TO DECIDE BASED ON SIZING DATA   |
| 5.3  | TEMPERATURE                                   | °C                     | REFER SIZING DATA SHEET A-3   |
| 6.0  | END DETAILS                                   |                        | (STEAM INLET / OUTLET)  |
| 6.1  | TYPE / MATCHING PIPE                          | mm x mm                | BW / 457.2 x 9.53   |
| 7.0  | END DETAILS                                   |                        | (SPRAY WATER INLET)   |
| 7.1  | TYPE / MATCHING PIPE                          |                        | SW/ 48.3 x 5.08   |
| 8.0  | MATERIALS OF CONSTRUCTION                     |                        |   |
| 8.1  | BODY  |                        | A216 WCB  |
| 8.2  | PIPE  |                        | SA 106GRB   |
| 8.3  | SPRAY NOZZLE WITH<br>ASSEMBLY                 |                        | SS 316 (Spray Nozzle design pressure shall be equal to Design Spray Water Pressure) |
| 9.0  | DESIGN PARAMETERS                             |                        |   |
| 9.1  | DESIGN PRESSURE                               | Kg/cm <sup>2</sup> (a) | 21  |
| 9.2  | DESIGN TEMPERATURE                            | °C                     | 350   |



TITILE

## EQUIPMENT SPECIFICATION

### STEAM DESUPERHEATER

For

OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at  
Jharsuguda, Odisha

SPEC. NO.: PE-TS-391-142-N101

VOLUME **II-B**

SECTION **D**

REV NO. **0**

DATE 05.07.2014


SHEET 2 OF 2

### DESUPERHEATER DATA SHEET A-2

#### DATA SHEET FOR 'TGS DESUPERHEATER' DESH-3

| S.NO | DESCRIPTION                                   | UNITS                  | DATA FOR HIGH CAP. PRDS<br>DESUPERHEATER  |
|------|---|------------------------|---|
| 1.0  | TAG NO.                                       |                        | DESH-3  |
| 2.0  | TYPE  |                        | VARIABLE ORIFICE / VENTURI TYPE   |
| 3.0  | STEAM PARAMETERS                              |                        | (INLET OF DESUPERHEATER)  |
| 3.1  | FLOW  | T/HR                   | REFER SIZING DATA SHEET A-4   |
| 3.2  | PRESSURE                                      | Kg/cm <sup>2</sup> (a) | BIDDER TO DECIDE BASED ON SIZING DATA   |
| 3.3  | TEMPERATURE                                   | °C                     | BIDDER TO DECIDE BASED ON SIZING DATA   |
| 4.0  | STEAM PARAMETERS<br>(OUTLET OF DESUPERHEATER) |                        | REFER SIZING DATA SHEET A-4   |
| 5.0  | SPRAY WATER<br>PARAMETERS                     |                        | (INLET OF DESUPERHEATER)  |
| 5.1  | FLOW  | T/HR                   | REFER SIZING DATA SHEET A-4   |
| 5.2  | PRESSURE                                      | Kg/cm <sup>2</sup> (a) | BIDDER TO DECIDE BASED ON SIZING DATA   |
| 5.3  | TEMPERATURE                                   | °C                     | REFER SIZING DATA SHEET A-4   |
| 6.0  | END DETAILS                                   |                        | (STEAM INLET / OUTLET)  |
| 6.1  | TYPE / MATCHING PIPE                          | mm x mm                | BW / 88.9 x 5.49  |
| 7.0  | END DETAILS                                   |                        | (SPRAY WATER INLET)   |
| 7.1  | TYPE / MATCHING PIPE                          |                        | SW/ 33.4 x 4.55   |
| 8.0  | MATERIALS OF CONSTRUCTION                     |                        |   |
| 8.1  | BODY  |                        | A216 WCB  |
| 8.2  | PIPE  |                        | SA 106GRB   |
| 8.3  | SPRAY NOZZLE WITH<br>ASSEMBLY                 |                        | SS 316 (Spray Nozzle design pressure shall be equal to Design Spray Water Pressure) |
| 9.0  | DESIGN PARAMETERS                             |                        |   |
| 9.1  | DESIGN PRESSURE                               | Kg/cm <sup>2</sup> (a) | 21  |
| 9.2  | DESIGN TEMPERATURE                            | °C                     | 350   |



|   |   |                               |                 |
|---|---|-------------------------------|-----------------|
|  | <b>TITLE</b><br><br><b>EQUIPMENT SPECIFICATIONS</b><br><br><b>AUXILIARY STEAM PRESSURE REDUCING<br/>&amp; DESUPERHEATING STATION</b><br><br><b>OPGCL - 2 x 660 MW, IB TPS, Unit # 3 &amp; 4 at<br/>Jharsuguda, Odisha</b> | SPEC. NO.: PE-TS-391-142-N101 |                 |
|   |   | VOLUME <b>II-B</b>            |                 |
|   |   | SECTION <b>D</b>              |                 |
|   |   | REV NO. <b>00</b>             | DATE 05.07.2014 |
|   |   | SHEET 1 OF 1                  |                 |

### **DATA SHEET-C**

#### **LIST OF DOCUMENTS AND DATA TO BE SUBMITTED AFTER AWARD OF CONTRACT**

The list of documents and data to be submitted by the successful bidder after the award of the contract are specified in Data Sheet - C.

The supplier shall after award of contract submit FIFTEEN (15) sets of the following documents for purchaser's approval / vetting.

- (i) Certified final drawings & data sheets as per cl. 4.0.0 of section-C.
- (ii) Quality Plans, Inspection/Test Reports as agreed with the Purchaser.
- (iii) Material and Hydraulic Test Certificates along with IBR form III C.
- (iv) Performance Test Procedures and Reports.
- (v) Field Quality Plan as agreed.
- (vi) Storage Instructions.
- (vii) List of Commissioning and Recommended Spares.
- (viii) List of Tools and Tackles required.
- (ix) List of lubricants.

\*\*\*\*\***(x)**\*\*\*\*\*Qperation and Maintenance Instruction Manual.

**NOTE:** Above list is only tentctive. Successful bidder shall'r repare detailed schedule of Drawings/ Documngnts, which shall be mwually agreed anf includgd in the contract document/ordering Specification.



TITLE

## EQUIPMENT SPECIFICATIONS

### AUXILIARY STEAM PRESSURE REDUCING & DESUPERHEATING STATION

OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at  
Jharsuguda, Odisha

SPEC. NO.: PE-TS-391-142-N101

VOLUME **II-B**

SECTION **D**

REV NO. **00** DATE 05.07.2014

SHEET 1 OF 1

### FINAL DOCUMENTATION

| S.NO. | DESCRIPTION   | INITIAL<br>SUBMISSION<br>FOR<br>APPROVAL<br>TO BHEL | COPIES FOR<br>NLC/TCE<br>APPROVAL<br>AFTER<br>BHEL<br>CLEARANCE |
|-------|---|---|---|
| 1.    | Vendor drawing / document for approval<br>Note :<br><ul style="list-style-type: none"> <li>Initial submissions with Rev. No. P0, P1, P2 etc.</li> <li>After BHEL clearance, submission to OPGC with Rev. No. R0, R1, R2 etc.</li> </ul> | 05+Soft Copy  | 3+Soft Copy   |
| 2.    | <del>Issue of action A/B/C Civil / Erection Drawings / documents for construction at site (for civil packages only)</del>   | 8   |   |
| 3.    | Release of finally approved drawings / documents (action A/E) i.e. distribution prints  | 6 + Soft Copy+2 CD's                                |   |
| 4.    | O&M Manuals   | 2+Soft  | 9+Soft+4 CD's   |
| 5.    | "As-Built" drawings, certificates, reports etc  | 9+Soft+4 CD's                                       |   |



TITLE

**EQUIPMENT SPECIFICATIONS**

**AUXILIARY STEAM PRESSURE REDUCING  
& DESUPERHEATING STATION**

**OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at  
Jharsuguda, Odisha**

SPEC. NO.: PE-TS-391-142-N101

VOLUME **II-B**

SECTION **D**


REV NO. **00** DATE 05.07.2014

SHEET 1 OF 1

**QUALITY PLAN**

QUALITY PLAN  
FOR CONTROL VALVES

|   |               |              |             |              |
|---|---------------|--------------|-------------|--------------|
| REV. 03   | DATE 09/04/14 | ALT.D RM-9d- | CHD SSB-9d- | APPD MAM-9d- |
| REVISED INLINE WITH CUST. COMMENTS RCVD VIDE LETTER NO. DPCC/BTG/0193/05-04-2014        |               |              |             |              |
| JOB NO. 391   |               |              |             |              |
| STATUS STANDARD   |               |              |             |              |
| DISTRIBUTION  |               |              |             |              |
| REV. 02   | DATE 27/02/14 | ALT.D RM-9d- | CHD SSB-9d- | APPD MAM-9d- |
| REVISED INLINE WITH CUST. COMMENTS RCVD VIDE LETTER NO. DPCC/BTG/0040/28-01-2014        |               |              |             |              |
| JOB NO. 391   |               |              |             |              |
| STATUS STANDARD   |               |              |             |              |
| DISTRIBUTION  |               |              |             |              |
| TITLE   |               |              |             |              |
| BHARAT HEAVY ELECTRICALS LTD<br>POWER SECTOR<br>PROJECT ENGINEERING MANAGEMENT<br>NOIDA |               |              |             |              |
| DEPT. CODE 1  |               |              |             |              |
| NAME RM   |               |              |             |              |
| SIGN -9d-   |               |              |             |              |
| DATE 08.11.13   |               |              |             |              |
| CHD SSB   |               |              |             |              |
| SIGN -9d-   |               |              |             |              |
| DATE 08.11.13   |               |              |             |              |
| APPD MAM  |               |              |             |              |
| SIGN -9d-   |               |              |             |              |
| DATE 08.11.13   |               |              |             |              |
| DEPT. SCALE   |               |              |             |              |
| SIGN  |               |              |             |              |
| DATE  |               |              |             |              |
| DRAWING NO. PE-QP-391-145-1006  |               |              |             |              |
| SHEET 00 OF 06  |               |              |             |              |
| REV. 03   |               |              |             |              |

|  |   |   |                   |                                  |                     |  |  |  |                      |     |     |   |  |
|--|---|---|-------------------|----------------------------------|---------------------|--|--|--|----------------------|-----|-----|---|--|
| <div></div> <div>PEM :: C&amp;I</div> |   | STANDARD QUALITY PLAN<br>FOR<br>CONTROL VALVE (PNEUMATIC) |                   |                                  |                     |  |  | QUALITY PLAN NO.: <b>PE-QP-391-145-I 006</b> |                      |     |     |   |  |
|  |   |   |                   |                                  |                     |  |  | VOLUME                                       |                      | IIB |     |   |  |
|  |   |   |                   |                                  |                     |  |  | SECTION                                      |                      | D   |     |   |  |
|  |   |   |                   |                                  |                     |  |  | REV. NO.                                     |                      | 03  |     | DATE: 09.04.14  |  |
|  |   |   |                   |                                  |                     |  |  | SHEET  |                      | 1   |     | OF 7  |  |
| Sl. No.  | Component / operation   | Characteristics Checked                                   | *<br>Cate<br>gory | Type/Method<br>of<br>Check       | Extent of<br>Check  | Reference<br>documents                   | Acceptance<br>Norms                      | Format<br>of<br>Records                      | Agency <sup>\$</sup> |     |     | Remarks   |  |
|  |   |   |                   |                                  |                     |  |  |  | P                    | W   | V   |   |  |
| 1.0  | MATERIAL  |   |                   |                                  |                     |  |  |  |                      |     |     |   |  |
| 1.1  | Body & Bonnet casting / forgings, plug, valve stem, seat ring/cage. | 1. Physical, Chemical properties                          | MA                | Physical, Chemical tests         | One/ Heat(HT Batch) | Approved drg. / data sheet / BHEL specn. | Approved drg. / data sheet / BHEL specn. | Test Certificate                             | 3                    | --- | 2,1 |   |  |
|  |   | 2. Heat Treatment   | MA                | Review of H.T. Chart             | Each H.T.           | Approved drg. / data sheet / BHEL specn. | Approved drg. / data sheet / BHEL specn. | Test Certificate                             | 3/2                  | 2   | 1   | IBR Certification (if applicable) to be verified by BHEL  |  |
|  |   | 3. Internal quality of castings                           | MA                | RT for Body & UT for Bonnet(NDT) | 100%                | ASME B 16.34                             | ASME B 16.34                             | Test Report / FILM                           | 3/2                  | 2   | 1   | Only for rating ANSI 900 and above.<br><br>Applicable for Body and Bonnet only. For Lower rating only if called for in specification. |  |
|  |   | 4. Surface Quality  | MA                | 1. Visual                        | 100%                | MSS-SP-55                                | MSS-SP-55                                | Test Certificate                             | 3/2                  | --- | 2,1 |   |  |
|  |   |   |                   | 2. MT/PT                         | 100%                | ASME B 16.34                             | ASME B 16.34                             | Test Certificate                             | 3                    | 2   | 1   | After Machining on machined surface only  |  |

LEGEND: \* CR - Critical characteristics  
MA - Major characteristics  
MI - Minor characteristics


RT- Radiographic Test  
UT – Ultrasonic Test

PT – Dye penetrant Test  
MT- Magnetic Test

\$ P - Agency Performing the Test.  
W - Agency Witnessing the Test.  
V - Agency Verifying the Test.

1 - BHEL  
2 - Vendor  
3 - Sub-vendor

4 - Customer

| <br>PEM :: C&I |                       | STANDARD QUALITY PLAN<br>FOR<br>CONTROL VALVE (PNEUMATIC) |             |                              |                     |                                   |                                   | QUALITY PLAN NO.: <b>PE-QP-391-145-I 006</b> |                     |                |     |                                   |
|---|-----------------------|---|-------------|------------------------------|---------------------|-----------------------------------|-----------------------------------|--|---------------------|----------------|-----|-----------------------------------|
|   |                       |   |             |                              |                     |                                   |                                   | VOLUME IIB                                   |                     |                |     |                                   |
|   |                       |   |             |                              |                     |                                   |                                   | SECTION D                                    |                     |                |     |                                   |
|   |                       |   |             |                              |                     |                                   |                                   | REV. NO. 03                                  |                     | DATE: 09.04.14 |     |                                   |
|   |                       |   |             |                              |                     |                                   |                                   | SHEET 2                                      |                     | OF 7           |     |                                   |
| Sl. No.   | Component / operation | Characteristics Checked                                   | * Cate gory | Type/Method of Check         | Extent of Check     | Reference documents               | Acceptance Norms                  | Format of Records                            | Agency <sup>s</sup> |                |     | Remarks                           |
|   |                       |   |             |                              |                     |                                   |                                   |  | P                   | W              | V   |                                   |
|   |                       | 5. Pressure test for shell                                | MA          | Hyd. Test                    | 100%                | ISA-S-75.19/<br>ASME B 16.34      | ISA-S-75.19/<br>ASME B 16.34      | Test Certificate                             | 2                   | 2              | 1   | For Body & Bonnet after machining |
| 1.2   | Diaphragm             | 1. Surface Quality  | MA          | Visual                       | 100%                | Mfr. standard                     | Mfr. standard                     | Test Certificate                             | 3/2                 | ---            | 2,1 |                                   |
|   |                       | 2. Hardness   | MA          | Measurement                  | 100%                | Mfr. standard                     | Mfr. standard                     | Test Certificate                             | 3/2                 | ---            | 2,1 |                                   |
|   |                       | 3. Endurance / Life cycle                                 | MA          | Cyclic test<br>10,000 cycles | One / Type          | 10,000 cycles/<br>Mfr. standard.  | No damage                         | Test Certificate                             | 3/2                 |                | 2,1 |                                   |
| 1.3   | Spring                | 1. Composition  | MA          | Chemical-Analysis            | One sample/<br>Heat | Material spec. /<br>Mfr. standard | Material spec. /<br>Mfr. standard | Test Certificate                             | 3                   | ---            | 2,1 |                                   |
|   |                       | 2. Mech. Properties                                       | MA          | Mech. Test                   | One sample/<br>Heat | Material spec. /<br>Mfr. standard | Material spec. /<br>Mfr. standard | Test Certificate                             | 3                   | ---            | 2,1 |                                   |
|   |                       | 3. Performance  | MA          | 1. Stiffness ratio           | 100%                | Material spec. /<br>Mfr. standard | Material spec. /<br>Mfr. standard | Test Certificate                             | 3                   | ---            | 2,1 |                                   |
|   |                       |   |             | 2. Scragging                 | 100%                | Material spec. /<br>Mfr. standard | Material spec. /<br>Mfr. standard | Test Certificate                             | 3                   | ---            | 2,1 |                                   |
|   |                       |   |             | 3. Cyclic test (Endurance)   | One / type          | 10,000 cycles                     | Material spec. /<br>Mfr. standard | Test Certificate                             | 3                   | ---            | 2,1 |                                   |
|   |                       |   |             | 4. Dimension (Measurement)   | One sample/<br>Lot  | Mfr. standard                     | Appd Drg                          | Record                                       | 3                   | ---            | 2,1 |                                   |

LEGEND: \* CR - Critical characteristics  
 MA - Major characteristics  
 MI - Minor characteristics


RT- Radiographic Test  
 UT – Ultrasonic Test

PT – Dye penetrant Test  
 MT- Magnetic Test

\$ P - Agency Performing the Test.  
 W - Agency Witnessing the Test.  
 V - Agency Verifying the Test.

1 - BHEL  
 2 - Vendor  
 3 - Sub-vendor

4 - Customer



# STANDARD QUALITY PLAN FOR CONTROL VALVE (PNEUMATIC)

QUALITY PLAN NO.: PE-QP-391-145-I 006

|        |     |
|--------|-----|
| VOLUME | IIB |
|--------|-----|

SECTION

REV. NO.

03

DATE: 09.04.14

SHEET

---

3

C

---

7[illegible]

LEGEND: \* CR - Critical characteristics  
MA - Major characteristics  
MI - Minor characteristics


RT- Radiographic Test  
UT – Ultrasonic Test

PT – Dye penetrant Test  
MT- Magnetic Test

\$ P - Agency Performing the Test.  
W - Agency Witnessing the Test.  
V - Agency Verifying the Test.

1 - BHEL  
2 - Vendor  
3 - Sub-vendor

#### 4 - Customer

| <br>PEM :: C&I |  | STANDARD QUALITY PLAN<br>FOR<br>CONTROL VALVE (PNEUMATIC) |            |   |                 |   |  | QUALITY PLAN NO.: <b>PE-QP-391-145-I 006</b> |                      |                |   |   |
|---|--|---|------------|---|-----------------|---|--|--|----------------------|----------------|---|---|
|   |  |   |            |   |                 |   |  | VOLUME IIB                                   |                      |                |   |   |
|   |  |   |            |   |                 |   |  | SECTION D                                    |                      |                |   |   |
|   |  |   |            |   |                 |   |  | REV. NO. 03                                  |                      | DATE: 09.04.14 |   |   |
|   |  |   |            |   |                 |   |  | SHEET 4                                      |                      | OF 7           |   |   |
| Sl. No.   | Component / operation                                | Characteristics Checked                                   | * Category | Type/Method of Check  | Extent of Check | Reference documents                                   | Acceptance Norms                         | Format of Records                            | Agency <sup>\$</sup> |                |   | Remarks   |
|   |  |   |            |   |                 |   |  |  | P                    | W              | V |   |
| 3.1   | Actuator Chamber                                     | Leakage & Strength  | MA         | Pneumatic test  | 100%            | Mfr. Standard   | No Leakage                               | Test Certificate                             | 2                    | 1,4            | 1 | Refer Note-4  |
| 3.2   | Body   | Leakage and Pressure test (Body Mount Leakage)            | MA         | Hydro test  | 100%            | ISA - S-75.19   | No Leakage                               | Test Certificate                             | 2                    | 1,4            | 1 | Refer Note-4  |
| 3.3   | Seat leakage test for completed valve                | Seat Leakage  | MA         | Pneumatic Test  | 100%            | FCI-70.2  | FCI-70.2                                 | Test Certificate                             | 2                    | 1,4            | 1 | Refer Note-4  |
| 4.0   | OPERATION TEST ON COMPLETED VALVE (Final inspection) | 1. Valve Travel   | MA         | Measurement   | 100%            | Approved drg. / data sheet                            | Approved drg. / data sheet               | Test Report                                  | 2                    | 1              | 1 | Refer Note-4  |
|   |  | 2. Opening/Closing time                                   | MA         | Measurement   | 100%            | Approved drg. / data sheet                            | Approved drg. / data sheet               | Test Report                                  | 2                    | 1              | 1 | Refer Note-4  |
|   |  | 3. Linearity/cam characteristic                           | MA         | Measurement   | 100%            | Approved drg. / data sheet                            | Approved drg. / data sheet               | Test Report                                  | 2                    | 1              | 1 | Refer Note-4  |
|   |  | 4. Repeatability  | MA         | Measurement   | 100%            | Approved drg. / data sheet                            | Approved drg. / data sheet               | Test Report                                  | 2                    | 1              | 1 | Refer Note-4  |
|   |  | 5. Hysteresis   | MA         | Measurement   | 100%            | Approved drg. / data sheet                            | Approved drg. / data sheet               | Test Report                                  | 2                    | 1              | 1 | Refer Note-4  |
|   |  | 6. Sensitivity  | MA         | Measurement   | 100%            | Approved drg. / data sheet                            | Approved drg. / data sheet               | Test Report                                  | 2                    | 1              | 1 | Refer Note-4  |
|   |  | 7. Accuracy (Overall)                                     | MA         | Measurement   | 100%            | Approved drg. / data sheet                            | Approved drg. / data sheet               | Test Report                                  | 2                    | 1              | 1 | Refer Note-4  |
|   |  | 8. Control Valve Flow characteristics / CV Test           | MA         | ◆ Measurement (Press. vs. discharge and discharge vs. opening 0-100% in steps of 10%) | One per type    | As per specs/ Approved drg. / data sheet / ISA S75.02 | As per specs/ Approved drg. / data sheet | Test Certificate                             | 2                    | 1,4            | 1 | ◆ Size = Body & port size Or Body size & CV for non std port. Refer Note 1. |

LEGEND: \* CR - Critical characteristics  
MA - Major characteristics  
MI - Minor characteristics


RT - Radiographic Test  
UT - Ultrasonic Test  
PT - Dye penetrant Test  
MT - Magnetic Test

<sup>\$</sup> P - Agency Performing the Test.  
W - Agency Witnessing the Test.  
V - Agency Verifying the Test.

1 - BHEL  
2 - Vendor  
3 - Sub-vendor

4 - Customer



| <br>PEM :: C&I |   | STANDARD QUALITY PLAN<br>FOR<br>CONTROL VALVE (PNEUMATIC)            |            |  |                 |                            |  | QUALITY PLAN NO.: <b>PE-QP-391-145-I 006</b> |                      |                |   |                                    |
|---|---|--|------------|--|-----------------|----------------------------|--|--|----------------------|----------------|---|------------------------------------|
|   |   |  |            |  |                 |                            |  | VOLUME                                       | IIB                  |                |   |                                    |
|   |   |  |            |  |                 |                            |  | SECTION                                      | D                    |                |   |                                    |
|   |   |  |            |  |                 |                            |  | REV. NO.                                     | 03                   | DATE: 09.04.14 |   |                                    |
|   |   |  |            |  |                 |                            |  | SHEET  | 5                    | OF             | 7 |                                    |
| Sl. No.   | Component / operation   | Characteristics Checked  | * Category | Type/Method of Check                         | Extent of Check | Reference documents        | Acceptance Norms                         | Format of Records                            | Agency <sup>\$</sup> |                |   | Remarks                            |
|   |   |  |            |  |                 |                            |  |  | P                    | W              | V |                                    |
|   |   | 9. Operation of limit switch & solenoids and other accessories       | MA         | Function                                     | 100%            | Approved drg. / data sheet | As per specs/ Approved drg. / data sheet | Test Report                                  | 2                    | 1              | 1 | On assembled valve<br>Refer Note-4 |
|   |   | 10. Overall dimensions   | MI         | Visual and dimensional                       | 100%            | Approved drg. / data sheet | As per specs/ Approved drg. / data sheet | Records                                      | 2                    | 1              | 1 | Refer Note-4                       |
|   |   | 11. Pre defined valve position in case of air failure                | MA         | Visual                                       | 100%            | As per spec & Appd drg     | As per spec & Appd drg                   | Test Certificate                             | 2                    | 1              | 1 |                                    |
|   |   | 12. Cleanliness, painting, stamping (for direction of flow), Tag No. | MA         | Visual and dimensional                       | 100%            | Approved drg. / data sheet | As per specs/ Approved drg. / data sheet | Test Certificate                             | 2                    | 1              | 1 |                                    |
| <b>5.0</b>  | <b>AUXILIARY ITEMS (Performance test of auxiliary items shall be performed on the completely assembled valve)</b> |  |            |  |                 |                            |  |  |                      |                |   |                                    |
| 5.1   | Positioner  | Overall leakage after assembly including Nozzles leakage             | MA         | Leak Test (in the steady state input signal) | 100 %           | Mfr. Standard              | No leakage                               | Test Certificate                             | 3/2                  | ---            | 1 | Overall leakage including tubing   |
| 5.2   | Air filter regulator  | 1. Normal air consumption  | MA         | Measurement                                  | Each type       | Mfr. Standard              | No leakage                               | Test Certificate                             | 3/2                  | ---            | 1 |                                    |
|   |   | 2. Overall leakage   | MA         | Visual (soap solution)                       | 100 %           | Mfr. Standard              | No leakage                               | Test Certificate                             | 3/2                  | ---            | 1 |                                    |
| 5.3   | Air lock relay  | Performance Test   | MA         | Leakage test                                 | 100%            | Mfr. Standard              | No leakage                               | Test Certificate                             | 3/2                  | ---            | 1 |                                    |
| 5.4   | Electronic position transmitter(not applicable if provided integral to smart positioner)                          | 1. Accuracy  | MA         | Operation                                    | 100%            | Approved data sheet /      | Approved data sheet /                    | Test Certificate                             | 2                    | 1              | 1 |                                    |

LEGEND: \* CR - Critical characteristics  
MA - Major characteristics  
MI - Minor characteristics


RT- Radiographic Test  
UT – Ultrasonic Test

PT – Dye penetrant Test  
MT- Magnetic Test

<sup>\$</sup> P - Agency Performing the Test.  
W - Agency Witnessing the Test.  
V - Agency Verifying the Test.

1 - BHEL  
2 - Vendor  
3 - Sub-vendor

4 - Customer



# STANDARD QUALITY PLAN FOR CONTROL VALVE (PNEUMATIC)

QUALITY PLAN NO.: PE-QP-391-145-I 006

|        |     |
|--------|-----|
| VOLUME | IIB |
|--------|-----|

SECTION

REV. NO.

03

DATE: 09.04.14

SHEET

---

6

C

---

7

| Sl. No. | Component / operation   | Characteristics Checked                     | * Category | Type/Method of Check   | Extent of Check | Reference documents                      | Acceptance Norms                         | Format of Records | Agency <sup>s</sup> |     |     | Remarks      |
|---------|---|---|------------|------------------------|-----------------|--|--|-------------------|---------------------|-----|-----|--------------|
|         |   |   |            |                        |                 |  |  |                   | P                   | W   | V   |              |
| 5.5     | Current to Pneumatic converter(not applicable for smart positioner) | 1. Physical Verification Make/Model         | MA         | Visual                 | 100%            | Approved drg. / data sheet               | Approved drg. / data sheet               | Test Certificate  | 2                   | --- | 2,1 |              |
|         |   | 2. Degree of Protection                     | MA         | IP/NEMA test           | Each type       | Relevant Standard                        | Relevant Standard                        | Test Certificate  | 3                   | --- | 2,1 |              |
|         |   | 3. Linearity                                | CR         | Measurement            | 100%            | Approved drg. / data sheet / BHEL specn. | Approved drg. / data sheet / BHEL specn. | Inspection Report | 2                   | --- | 1   |              |
|         |   | 4. Hysterisis                               | CR         | Measurement            | 100%            | Approved drg. / data sheet / BHEL specn. | Approved drg. / data sheet / BHEL specn. | Inspection Report | 2                   | --- | 1   |              |
| 5.6     | Smart Positioner (As Applicable)                                    | 1. Physical Verification Make/Model         | MA         | Visual                 | 100%            | Approved drg. / data sheet               | Approved drg. / data sheet               | Test Certificate  | 2                   | --- | 2,1 |              |
|         |   | 2. Degree of Protection                     | MA         | IP/NEMA test           | Each type       | Relevant Standard                        | Relevant Standard                        | Test Certificate  | 3                   | --- | 2,1 |              |
|         |   | 3. Linearity                                | CR         | Measurement            | 100%            | Approved drg. / data sheet / BHEL specn. | Approved drg. / data sheet / BHEL specn. | Inspection Report | 2                   | --- | 1   |              |
|         |   | 4. Hysterisis                               | CR         | Measurement            | 100%            | Approved drg. / data sheet / BHEL specn. | Approved drg. / data sheet / BHEL specn. | Inspection Report | 2                   | --- | 1   |              |
|         |   | 5. Calibration with Hand Held Communicator  | MA         | Measurement            | Each type       | Approved data sheet / Mfr. Standard      | Approved data sheet / Mfr. Standard      | Test Certificate  | 2                   | 1   | 1   |              |
| 6.0     | PAINTING  | Soundness of Painting                       | MA         | Visual and Measurement | 100%            | BHEL specn. / Mfr. Standard              | BHEL specn. / Mfr. Standard              | Inspection Report | 2                   | --- | --- | Refer Note-2 |
| 7.0     | PACKING   | Soundness of Packing against transit damage | MA         | Visual                 | 100%            | Mfr. Standard                            | Mfr. Standard                            | Inspection Report | 2                   | --- | --- | Refer Note-3 |

LEGEND: \* CR - Critical characteristics  
MA - Major characteristics  
MI - Minor characteristics


RT- Radiographic Test  
UT – Ultrasonic Test

PT – Dye penetrant Test  
MT- Magnetic Test

\$ P - Agency Performing the Test.  
W - Agency Witnessing the Test.  
V - Agency Verifying the Test.

1 - BHEL  
2 - Vendor  
3 - Sub-vendor


#### 4 - Customer

| <br>PEM :: C&I | STANDARD QUALITY PLAN<br>FOR<br>CONTROL VALVE (PNEUMATIC) |                         |            |                      |                 |                     |                  | QUALITY PLAN NO.: <b>PE-QP-391-145-I 006</b> |                      |                |   |         |
|---|---|-------------------------|------------|----------------------|-----------------|---------------------|------------------|--|----------------------|----------------|---|---------|
|   |   |                         |            |                      |                 |                     |                  | VOLUME IIB                                   |                      |                |   |         |
|   |   |                         |            |                      |                 |                     |                  | SECTION D                                    |                      |                |   |         |
|   |   |                         |            |                      |                 |                     |                  | REV. NO. 03                                  |                      | DATE: 09.04.14 |   |         |
|   |   |                         |            |                      |                 |                     |                  | SHEET 7                                      |                      | OF 7           |   |         |
| Sl. No.   | Component / operation                                     | Characteristics Checked | * Category | Type/Method of Check | Extent of Check | Reference documents | Acceptance Norms | Format of Records                            | Agency <sup>\$</sup> |                |   | Remarks |
|   |   |                         |            |                      |                 |                     |                  |  | P                    | W              | V |         |

NOTES:

1. In case valid CV test certificate for a similar control valve(Same type, Same size, Same CV) is not submitted to BHEL by the vendor, CV test shall be conducted at FCRI/Any govt. approved laboratory/ BHEL approved Laboratory.
2. In the absence of BHEL spec. for painting, vendor to obtain BHEL's approval on their painting specification / procedure.
3. Sea worthy packing shall be provided, if applicable.
4. The quantum of check shall be 100% for manufacturer and 10% for BHEL/BHEL nominated inspection agency.
5. IBR certificates in Form III-C shall be submitted if called for in the specification/datasheet.
6. Copies of all TC's(Test Certificates) for materials duly correlated with Heat Nos., TC's for electrical items and mechanical tests(Leak/Operation) shall be submitted to BHEL for verification and acceptance.

|         |   |   |  |  |  |              |
|---------|---|---|--|--|--|--------------|
| LEGEND: | * CR - Critical characteristics<br>MA - Major characteristics<br>MI - Minor characteristics | RT- Radiographic Test<br>UT – Ultrasonic Test | PT – Dye penetrant Test<br>MT- Magnetic Test | <sup>\$</sup> P - Agency Performing the Test.<br>W - Agency Witnessing the Test.<br>V - Agency Verifying the Test. | 1 - BHEL<br>2 - Vendor<br>3 - Sub-vendor | 4 - Customer |
|---------|---|---|--|--|--|--------------|

|  |                         |                          |      |  |                       |                       |                    |  |        |   |   |         |  |
|--|-------------------------|--------------------------|------|--|-----------------------|-----------------------|--------------------|--|--------|---|---|---------|--|
| <div></div> <div>STANDARD QUALITY<br/>PLAN FOR AUXILIARY<br/>STEAM PRDS</div> |                         |                          |      | CUSTOMER : OPGCL                         |                       |                       |                    | PROJECT: 2X660MW IB TPS,<br>JHARSUGUDA,ODISHA    |        |   | SPECIFICATION<br>NUMBR PE-TS-391-142-N995 |         |  |
|  |                         |                          |      | BIDDER/ : AS PER APPROVED<br>VENDOR LIST |                       |                       |                    | SPECIFICATION TITLE :<br>AUXILIARY STEAM P.R.D.S |        |   |   |         |  |
|  |                         |                          |      | SHEET 1 of 2                             |                       |                       |                    | SYSTEM ITEM :<br>STEAM DESUPERHEATER             |        |   | QUALITY PLAN<br>NUMBR                     |         |  |
| SL.<br>NO.   | COMPONENT/<br>OPERATION | CHARACT-ERISTIC<br>CHECK | CAT. | TYPE<br>METHOD OF<br>CHECK               | EXTENT<br>OF<br>CHECK | REFERENCE<br>DOCUMENT | ACCEPTANCE<br>NORM | FORMAT OF<br>RECORD                              | AGENCY |   |   | REMARKS |  |
|  |                         |                          |      |  |                       |                       |                    |  | P      | W | V   |         |  |
| 1  | 2                       | 3                        | 4    | 5  | 6                     | 7                     | 8                  | 9  | 10     |   |   | 11      |  |

|     |                          |                             |  |                           |        |                              |                              |             |     |   |   |                      |
|-----|--------------------------|-----------------------------|--|---------------------------|--------|------------------------------|------------------------------|-------------|-----|---|---|----------------------|
| 1.0 | <b>Raw Materials</b>     |                             |  |                           |        |                              |                              |             |     |   |   |                      |
| 1.1 | Pipes                    | Mechanical & Chemical Prop. |  | Mechanical & Chemical     | 100%   | Appd Specn./ Data Sheet/Drg. | Appd Specn./ Data Sheet/Drg. | TC          | 3/2 | - | 1 | Correlation required |
|     |                          | Leakproofness               |  | Hydraulic test            | 100%   | -do-                         | -do-                         | TC          | 3/2 | - | 1 |                      |
|     |                          | Dimensions                  |  | Measurement               | 100%   | -do-                         | -do-                         | IR          | 3/2 | - | 1 |                      |
| 1.2 | Forging                  | Physical & Chemical Prop.   |  | Physical & Chemical Prop. | 1/heat | Appd Specn./ Data Sheet/Drg. | Appd Specn./ Data Sheet/Drg. | TC          | 3/2 | - | 1 | Correlation required |
|     |                          | Dimensions                  |  | Measurement               | 100%   | -do-                         | -do-                         | IR          | 3/2 | - | 1 |                      |
|     |                          | Heat Treatment              |  | Scrutiny                  | 100%   | -do-                         | -do-                         | HT/SR Chart | 3/2 | - | 1 | Correlation required |
| 2.0 | <b>In Process</b>        |                             |  |                           |        |                              |                              |             |     |   |   |                      |
| 2.1 | Forgings                 | Internal defects            |  | U.T                       | 100%   | ASTMA 435                    | ASTMA 435                    | IR          | 3/2 | - | 1 |                      |
| 2.2 | Machining Body Internals | Dimensions                  |  | Measurement               | 100%   | Appd.Drg.                    | Appd.Drg.                    | IR          | 3/2 | - | 1 | Correlation required |
| 2.3 | Body                     | Surface Defects             |  | D.P. Check                | 100%   | ASTME165                     | ASME-B 16.34 ,Appendix-III   | TC          | 3/2 | - | 1 |                      |

| PARTICULARS | CUSTOMER/CONSULTANT | BHEL | BIDDER / VENDOR | BIDDER'S/ VENDOR'S COMPANY SEALS |
|-------------|---------------------|------|-----------------|----------------------------------|
| NAME        |                     |      |                 |                                  |
| SIGNATURE   |                     |      |                 |                                  |
| DATE        |                     |      |                 |                                  |



PROJECT: 2X660MW IB TPS,  
JHARSUGUDA,ODISHA

SPECIFICATION  
NUMBR **PE-TS-391-142-N995**

BIDDER/ : AS PER APPROVED  
VENDOR LIST

SPECIFICATION TITLE : **AUXILIARY STEAM P.R.D.S**

SHEET 2 of 2

SYSTEM ITEM :  
**STEAM DESUPERHEATER**

| QUALITY PLAN<br>NUMBR | DATE | BY | CHKD BY | APPROVED BY | REVISION |
|-----------------------|------|----|---------|-------------|----------|
|                       |      |    |         |             |          |

SECTION VOLUME

| SL. NO. | COMPONENT/ OPERATION | CHARACT-ERISTIC CHECK | CAT. | TYPE METHOD OF CHECK | EXTENT OF CHECK | REFERENCE DOCUMENT | ACCEPTANCE NORM | FORMAT OF RECORD | AGENCY |   |   | REMARKS |
|---------|----------------------|-----------------------|------|----------------------|-----------------|--------------------|-----------------|------------------|--------|---|---|---------|
|         |                      |                       |      |                      |                 |                    |                 |                  | P      | W | V |         |
| 1       | 2                    | 3                     | 4    | 5                    | 6               | 7                  | 8               | 9                | 10     |   |   | 11      |

|   |                  |  |  |                     |      |                             |                             |        |     |   |   |                     |
|---|------------------|--|--|---------------------|------|-----------------------------|-----------------------------|--------|-----|---|---|---------------------|
| 2.4   | WPS,PQR,WPQ      | WPS,PQR,WPQ                                |  | Physical            | 100% | ASME Sec-IX/IBR             | ASME Sec-IX/IBR             | Format | 3/2 | - | 1 | Records to be shown |
| 3.0   | Final Inspection |  |  |                     |      |                             |                             |        |     |   |   |                     |
| 3.1   | Assembly         | Completeness and Marking                   |  | Visual              | 100% | Appd Specn./Data Sheet/Drg. | Appd Specn./Data Sheet/Drg. | IR     | 3/2 | 1 | - |                     |
|   |                  | Dimensional                                |  | Measurement         | 100% | Appd Specn./Data Sheet/Drg. | Appd Specn./Data Sheet/Drg. | IR     | 3/2 | 1 | - |                     |
| 3.2   | Pressure Test    | Leak Proofness                             |  | Hydraulic Test      | 100% | -do-                        | -do-                        | IR     | 3/2 | 1 | - |                     |
| 4.0   | Painting         | Surface Prepn., Uniformity, Shade & Thick. |  | Visual, Measurement | 100% | -do-                        | -do-                        | IR     | 3/2 | - | 1 |                     |
| 5.0   | Packing          | Soundness of Packing, Marking              |  | Visual              | 100% | Appd Specn./Mfr. Standard   | Appd Specn./Mfr. Standard   | IR     | 3/2 | - | 1 |                     |
| Note:: IBR –Certificate in Form III C shall be submitted. |                  |  |  |                     |      |                             |                             |        |     |   |   |                     |

|        |                               |             |                  |
|--------|-------------------------------|-------------|------------------|
| LEGEND | P – PERFORM                   | W – WITNESS | V – VERIFICATION |
|        | 1 – BHEL, CUSTOMER/CONSULTANT | 2 – VENDOR  | 3 – SUB VENDOR   |

|                    |                            |             |                        |   |
|--------------------|----------------------------|-------------|------------------------|---|
| <b>PARTICULARS</b> | <b>CUSTOMER/CONSULTANT</b> | <b>BHEL</b> | <b>BIDDER / VENDOR</b> |   |
| <b>NAME</b>        |                            |             |                        |   |
| <b>SIGNATURE</b>   |                            |             |                        |   |
| <b>DATE</b>        |                            |             |                        |   |
|                    |                            |             |                        | <b>BIDDER'S/ VENDOR'S COMPANY SEALS</b> |



TITLE

**EQUIPMENT SPECIFICATIONS**

**AUXILIARY STEAM PRESSURE REDUCING  
& DESUPERHEATING STATION**

**OPGCL - 2 x 660 MW, IB TPS, Unit # 3 & 4 at  
Jharsuguda, Odisha**

SPEC. NO.: PE-TS-391-142-N101

VOLUME **II-B**

SECTION **D**

REV NO. **00** DATE 05.07.2014


SHEET 1 OF 1

**TENDER DRAWINGS**

NOTE

1. EQUIPMENTS IN BIDDER'S SCOPE HAVE BEEN MARKED AS BS

1. EQUIPMENTS IN BIDDER'S SCOPE HAVE BEEN MARKED AS



**OPGCL-2x660 MW, Super-Critical TPS,  
Unit#3&4 at Jharsuguda, Odisha**

[illegible]

TECHNICAL SPEC. for AUXILIARY PRDS

|  |  |  |  |  |  |  |  |       |             |                    |
|--|--|--|--|--|--|--|--|-------|-------------|--------------------|
|  |  |  |  |  |  |  |  |       | DRAWING NO. | PE-TS-391-142-N102 |
|  |  |  |  |  |  |  |  | DEPT. | SCALE       | NTS                |
|  |  |  |  |  |  |  |  | SIGN  |             |                    |

**ODISHA POWER GENERATION**  
**CORPORATION LIMITED**

**2 X 660 MW, SUPER-CRITICAL TPS,**  
**UNIT # 3 & 4**  
**AT**  
**JHARSUGUDA, ODISHA**

TECHNICAL SPECIFICATION  
FOR  
AUXILIARY STEAM PRESSURE REDUCING  
AND DESUPERHEATING STATION  
ALONGWITH ACCESSORIES

**VOLUME - III**

**SPECIFICATION No: PE-TS -391-142-N101 (REV 00)**



BHARAT HEAVY ELECTRICALS LIMITED  
POWER SECTOR  
PROJECT ENGINEERING MANAGEMENT  
PPEI, NOIDA, INDIA






TITLE

**PREAMBLE**SPECIFICATION NO **PE-SS-999-100-Q-001**VOLUME **III**SECTION **PREAMBLE**REV NO. **0** DATESHEET **1 OF 1****VOLUME – III TECHNICAL SCHEDULES**

1.0 This volume contains technical schedules and Data Sheets – B , which are to be duly filled by the bidder and the same shall be furnished with the technical bid as per instructions given in Document No. PES-100-901 in Volume-III.

2.0 The requirements mentioned in Section – C / Data Sheets – A of Section – D shall prevail and govern in case of conflict between the same and the corresponding requirements mentioned in the descriptive portion in Section – D.

|   |   |                               |                   |
|---|---|-------------------------------|-------------------|
|  | TITLE<br><br><b>AUXILIARY STEAM PRESSURE REDUCING<br/>&amp; DESUPERHEATING STATION</b>  | SPEC. NO.: PE-TS-391-142-N101 |                   |
|   |   | VOLUME <b>III</b>             |                   |
|   |   | SECTION <b>CONTENTS</b>       |                   |
|   |   | REV NO. <b>0</b>              | DATE   17.07.2014 |
|   |   | SHEET   1   OF 3              |                   |
| 1.0   | Volume III comprises of following: -  |                               |                   |
| 1.1   | Data Sheet   :   Data Sheet(s) ‘B’ Section ‘D’.   |                               |                   |
| 1.2   | Schedules     :   |                               |                   |
|   | PART – A     :     Technical Schedules  |                               |                   |
|   | PART – B     :     Price Schedules  |                               |                   |
|   | (See clause 2 (b) below for unpriced schedules)   |                               |                   |
|   | The Schedule and Data Sheets enclosed/indexed shall be completely filled up by the bidder and furnished with the bid duly signed and stamped by the bidder. Purchaser reserves the right to ask the bidder to fill additional schedules, which are not listed in the contents.  |                               |                   |
| 2.0   | Form No. PEM-6020 is a ‘Checklist’, which is enclosed to facilitate the bidder to make sure that the necessary data/information is furnished by him in his bid. The remarks column of this schedule shall be filled up by the bidder as per the instructions given below:-  |                               |                   |
|   | a) The bidder shall write ‘Not Applicable’ against those schedules / documents which are not listed in the contents.  |                               |                   |
|   | b) The bidder shall write ‘Enclosed’ for the listed schedules / documents which are filled and furnished by the bidder with the bid. Otherwise ‘Not Enclosed’ shall be written.   |                               |                   |
|   | c) Duly filled Part-A schedules as well as Data Sheet-B shall be furnished with the technical offer while Part-B (Price Schedules) shall be submitted with price offer in separate covers.  |                               |                   |
|   | d) Wherever unpriced schedules are to be furnished with Part-A schedules in tech. bids. the same is indicated in the filling space of price schedule formats.   |                               |                   |
|   | e) Other documents / information as required in the checklist shall also be furnished by the bidder.  |                               |                   |
| 3.0   | The Data Sheet(s)-B shall be filled-up completely and typed written and shall be duly signed with Rev. No. and date. One copy of the same shall be furnished with the bid. The items, which deviate from the specification, shall be marked with an asterisk (*) in the data sheets and details shall also be given in the ‘Schedule of deviations’ from technical specification (Form No. PEM-6036). |                               |                   |
| 4.0   | Bidder shall fill specification No. in all schedules .  |                               |                   |
| 5.0   | Schedules PEM – 6020 & PEM 6040 duly filled in shall be enclosed by bidder both in Technical and price offers.  |                               |                   |



TITLE

**AUXILIARY STEAM PRESSURE REDUCING  
& DESUPERHEATING STATION**

SPEC. NO.: PE-TS-391-142-N101

VOLUME **III**

SECTION **CONTENTS**

REV NO. **0** DATE 17.07.2014

SHEET 2 OF 3

## **CONTENTS**

### **PART-A**

| <u><b>SL.NO.</b></u> | <u><b>FORM NO.</b></u> | <u><b>FORM DESCRIPTION</b></u>                                  | <u><b>NO. OF SHEETS</b></u> |
|----------------------|------------------------|---|-----------------------------|
| 1.                   |                        | Data Sheet-C for Control Valves                                 | 3                           |
| 2.                   |                        | Data Sheet-C for Steam Desuperheater                            | 2                           |
| 3.                   | PE-6020                | Check List - List of Schedules                                  | 1                           |
| 4.                   | PE-6024                | Schedule of Drawings / Catalogues submitted with bid            | 1                           |
| 5.                   | PE-6026*               | Schedule of Equipment, Manufacture, Dispatch & Shipment to Site | 1                           |
| 6.                   | PE-6027*               | Schedule of Weights & Dimensions                                | 1                           |
| 7.                   | PE-6030*               | Inspection Schedule   | 1                           |
| 8.                   | PE-6036                | Schedule of Deviations  | 1                           |
| 9.                   | PE-6040                | Schedule of Declaration   | 1                           |
| 10.                  | PE-6041*               | Quality Plan  | 1                           |
| 11.                  | PE-6042-00             | Instructions for filling up the Quality Plan                    | 1                           |
| 12.                  | PE-6042*               | Vendor's Drawings / Document Schedule                           | 1                           |
| 13.                  | PE-6046*               | Inspection Request  | 1                           |

\* To be filled up by successful bidder after LOI.



TITLE

**AUXILIARY STEAM PRESSURE REDUCING  
& DESUPERHEATING STATION**

SPEC. NO.: PE-TS-391-142-N101

VOLUME **III**

SECTION **CONTENTS**

REV NO. **0** DATE 17.07.2014

SHEET 3 OF 3

## **CONTENTS**

### **PART-B**

| <u><b>SL.NO.</b></u> | <u><b>FORM NO.</b></u> | <u><b>FORM DESCRIPTION</b></u>  | <u><b>NO. OF SHEETS</b></u> |
|----------------------|------------------------|---|-----------------------------|
| <b>1.</b>            | PE-6051                | Schedule of Prices  | 1                           |
| <b>2.</b>            | PE-6052                | Schedule of Unit Prices   | 1                           |
| <b>3.</b>            | PE-6053                | Schedules of Prices for Commissioning & Mandatory Spares                  | 1                           |
| <b>4.</b>            | PE-6054                | Schedule of Prices for Recommended Spares                                 | 1                           |
| <b>5.</b>            | PE-6055                | Schedule of Prices for Erection & Maintenance Tools & Tackles             | 1                           |
| <b>6.</b>            | PE-6056*               | Schedule of Bidder's Man-power for Supervision of E & C and their Charges | 1                           |

\* to be filled up by successful bidder after LOI.



TITLE

**AUXILIARY STEAM PRESSURE REDUCING  
& DESUPERHEATING STATION**

SPEC. NO.: PE-TS-391-142-N101

VOLUME **III**

SECTION **PART-A**

REV NO. **00** DATE 17.07.2014

SHEET 1 OF 1

**VOLUME-III  
PART-A**

**SCHEDULES AND DATA SHEETS**



TITLE


**EQUIPMENT SPECIFICATIONS****AUXILIARY STEAM PRESSURE REDUCING  
& DESUPERHEATING STATION**

SPEC. NO.: PE-TS-391-142-N101


VOLUME **III**SECTION **D**REV NO. **0** DATE 17.07.2014

SHEET 1 OF 1


**DATA SHEETS - C**  
**AUXILIARY STEAM PRESSURE REDUCING  
& DESUPERHEATING STATION****(TO BE FILLED BY SUCCESSFUL VENDOR AFTER THE AWARD OF CONTRACT)**


|   |   |   |                  |
|---|---|---|------------------|
|  | <b>Technical specification for<br/>APRDS CONTROL VALVES</b><br>(Pneumatically Operated)<br><b>OPGCL-2X660MW, Super-Critical TPS,</b><br><b>Unit -3 &amp; 4 at Jharsuguda,Odisha</b> | SPECIFICATION NO. <b>PE-TS-391-142-N101</b> |                  |
|   |   | VOLUME <b>III</b>                           |                  |
|   |   | SECTION <b>D</b>                            |                  |
|   |   | REV. NO. 00                                 | DATE: 17.07.2014 |
|   |   | SHEET 1 of 3                                |                  |


|   |   |                                 |
|---|---|---------------------------------|
|   |   | NAME                            |
|   |   | SIGNATURE                       |
|   |   | DATE                            |
| Tag No..... Quantity.....   |   | Data Sheet No. PES-145-06-DS2-0 |
| <b>DATA SHEET C</b>   |   |                                 |
| <b>DATA SHEET – C FOR CONTROL VALVE (WITH PNEUMATIC ACTUATOR)</b><br>(TO BE FILLED BY THE BIDDER AFTER THE AWARD OF CONTRACT) |   |                                 |
| <b>GENERAL*</b>   | PROJECT                                       |                                 |
|   | SERVICE                                       |                                 |
|   | LOCATION                                      |                                 |
|   | DUTY  |                                 |
|   | PIPE SIZE (inlet / outlet)                    |                                 |
|   | PIPE MATERIAL (inlet / outlet)                |                                 |
| <b>BODY</b>   | MODEL NUMBER                                  |                                 |
|   | TYPE OF BODY : GUIDING : NO. OF PORTS         |                                 |
|   | BODY SIZE : PORT SIZE : DESIGN DV             |                                 |
|   | END CONNECTION & RATING (ANSI)                |                                 |
|   | BODY MATERIAL                                 |                                 |
|   | PACKING MATERIAL SINGLE / DOUBLE              |                                 |
|   | BONNET TYPE                                   |                                 |
|   | TRIM FORM                                     |                                 |
|   | TRIM MATERIAL : SEAT   PLUG                   |                                 |
|   | TRIM MATERIAL : CAGE   GUIDE                  |                                 |
|   | FLOW  |                                 |
|   | OUTLET VELOCITY                               |                                 |
|   | REQUIRED LEAKAGE CLASS                        |                                 |
|   | NOISE LEVEL (dBA) (Spec. 3.1.14)              |                                 |
|   | VACUUM SERVICE                                |                                 |
|   | ANTI CAVITATION TRIM                          |                                 |
| <b>PNEUMATIC ACTUATOR</b>   | MODEL NO. & SIZE                              |                                 |
|   | CLOSE AT : OPEN AT (Kg / Cm <sup>2</sup> g)   |                                 |
|   | *TRAVEL TIME FOR OPEN TO CLOSE, CLOSE TO OPEN |                                 |
|   | *VALVE POSN. ON SIGNAL AIR FAILURE            |                                 |
|   | *VALVE POSN. ON SUPPLY AIR FAILURE            |                                 |
| <b>ACCESSORIES</b>  | POSITIONER                                    |                                 |
|   | AIR FILTER REGULATOR                          |                                 |
|   | AIR LOCK RELAY                                |                                 |
|   | POSITION LIMIT SWITCH                         |                                 |
|   | POSITION TRANSMITTER                          |                                 |
|   | SOLENOID VALVE                                |                                 |
|   | E / P CONVERTER                               |                                 |
|   | JUNCTION BOX                                  |                                 |
|   | HAND WHEEL (SIDE MOUNTED)                     |                                 |
|   | LOCAL POSITION INDICATOR                      |                                 |
| ELECTRO PNEUMATIC POSITIONER  |   |                                 |

|  |  |             |                    |  |   |                    |                      |                     |                           |
|--|--|-------------|--------------------|--|---|--------------------|----------------------|---------------------|---------------------------|
|                                       | <b>Technical specification for<br/>APRDS CONTROL VALVES</b><br>(Pneumatically Operated)<br><b>OPGCL-2X660MW, Super-Critical TPS,</b><br><b>Unit -3 &amp; 4 at Jharsuguda, Odisha</b> |             |                    |  | SPECIFICATION NO. <b>PE-TS-391-142-N101</b> |                    |                      |                     |                           |
|  |  |             |                    |  | VOLUME <b>III</b>                           |                    |                      |                     |                           |
|  |  |             |                    |  | SECTION <b>D</b>                            |                    |                      |                     |                           |
|  |  |             |                    |  | REV. NO. 00                                 |                    | DATE: 19.29.2016     |                     |                           |
|  |  |             |                    |  | SHEET 2 of 3                                |                    |                      |                     |                           |
| Tag No..... Quantity..... Data Sheet No. PES-145-06-DS2-0  |  |             |                    |  |   |                    |                      |                     |                           |
| DATA SHEET C   |  |             |                    |  |   |                    |                      |                     |                           |
| DATA SHEET – C FOR CONTROL VALVE (WITH PNEUMATIC ACTUATOR)<br>(TO BE FILLED BY THE BIDDER AFTER THE AWARD OF CONTRACT) |  |             |                    |  |   |                    |                      |                     |                           |
| <b>PERFORMANCE OF VALVE</b>  | LINEARITY  |             |                    |  |   |                    |                      |                     |                           |
|  | HYTERSIS   |             |                    |  |   |                    |                      |                     |                           |
|  | SENSITIVITY  |             |                    |  |   |                    |                      |                     |                           |
|  | ACCURACY   |             |                    |  |   |                    |                      |                     |                           |
| <b>SERVICE CONDITION*</b>  | <b>SL.+ NO.</b>  | <b>LOAD</b> | <b>FLOW (T/HR)</b> | <b>INLET PR. (KG/CM<sup>2</sup> (A))</b> | <b>OUTLET PR. (KG/CM<sup>2</sup> (A))</b>   | <b>TEMP DEG. C</b> | <b>CALCULATED CV</b> | <b>% VALVE LIFT</b> | <b>VALVE O/L VELOCITY</b> |
|  |  |             |                    |  |   |                    |                      |                     |                           |
|  |  |             |                    |  |   |                    |                      |                     |                           |
|  |  |             |                    |  |   |                    |                      |                     |                           |
|  |  |             |                    |  |   |                    |                      |                     |                           |
|  |  |             |                    |  |   |                    |                      |                     |                           |
|  | VALVE TYPE   |             |                    |  |   |                    |                      |                     |                           |
|  | * MAX SHUT OFF PRESS ((KG/CM <sup>2</sup> g)   |             |                    |  |   |                    |                      |                     |                           |
|  | * BODY DESIGN : PRESS ((KG/CM <sup>2</sup> g)   TEMP (DEG. C)  |             |                    |  |   |                    |                      |                     |                           |
|  | * IBR FORM III-C   |             |                    |  |   |                    |                      |                     |                           |
| TOTAL WEIGHT (VALVE + ACTUATOR + ACCESSORIES) KG.  |  |             |                    |  |   |                    |                      |                     |                           |




|  |  |              |                     |       |
|--|--|--------------|---------------------|-------|
|   | <b>Technical specification for<br/>Control Valves with Accessories</b><br>(Pneumatically Operated)   |              | SPECIFICATION NO.   |       |
|  |  |              | VOLUME <b>III</b>   |       |
|  |  |              | SECTION <b>D</b>    |       |
|  |  |              | REV. NO.            | DATE: |
|  |  |              | SHEET OF            |       |
| Tag No..... Quantity..... Data Sheet No. PES-145-06-DS2-1  |  |              |                     |       |
| <b>DATA SHEET C</b>  |  |              |                     |       |
| <b>DATA SHEET – C FOR CONTROL VALVE (WITH PNEUMATIC ACTUATOR)</b><br><b>(TO BE FILLED BY THE BIDDER AFTER THE AWARD OF CONTRACT)</b> |  |              |                     |       |
| <b>POSITIONER</b>  | MFR. & MODEL NUMBER  |              |                     |       |
|  | BYPASS   | GAUGES       | ENCL. CLASS         |       |
|  | INPUT SIGNAL (Kg / Cm <sup>2</sup> )   |              |                     |       |
|  | OUTPUT SIGNAL (Kg / Cm <sup>2</sup> )  |              |                     |       |
| <b>AIR FILTER<br/>REGULATOR</b>  | MFR. & MODEL NUMBER  |              |                     |       |
|  | AIR SUPPLY PRESS (Kg / Cm <sup>2</sup> g)  |              |                     |       |
|  | OUTPUT PRESS (Kg / Cm <sup>2</sup> g)  |              |                     |       |
|  | OUTPUT GAUGE   |              |                     |       |
|  | FILTER SIZE  |              |                     |       |
| <b>AIR LOCK</b>  | MFR. & MODEL NUMBER  |              |                     |       |
|  | SET PRESS (Kg / Cm <sup>2</sup> )  |              |                     |       |
|  | SUPPLY PRESS (Kg / Cm <sup>2</sup> )   |              |                     |       |
|  | RESET TYPE   |              |                     |       |
|  | VENT PLUG  |              |                     |       |
| <b>LIMIT SWITCH</b>  | MFR. & MODEL NUMBER  |              |                     |       |
|  | OPEN posn  | INT posn     | CLOSE posn          |       |
|  | CONTACT TYPE   |              |                     |       |
|  | RATING (AC / DC)   |              |                     |       |
|  | ENCLOSURE CLASS  |              |                     |       |
| <b>POSITION<br/>TRANSMITTER</b>  | MFR. & MODEL NUMBER  |              | PART OF POSITIONER. |       |
|  | TYPE   |              |                     |       |
|  | SUPPLY   |              |                     |       |
|  | OUTPUT RATING  |              |                     |       |
|  | ACCURACY   |              |                     |       |
|  | ENCLOSURE CLASS  |              |                     |       |
| <b>SOLENOID<br/>VALVE</b>  | MFR. & MODEL NUMBER  |              |                     |       |
|  | RATING   |              |                     |       |
|  | OPERATION  | QUANTITY     |                     |       |
|  | COIL INSULATION CLASS  |              |                     |       |
|  | ENCLOSURE CLASS  |              |                     |       |
| <b>HANDWHEEL</b>   | ORIENTATION  |              |                     |       |
| <b>JUNCTION BOX</b>  | NO. OF WAYS  |              |                     |       |
|  | SIZE   |              |                     |       |
|  | CABLE GLANDS (Size / Quantity)   |              |                     |       |
|  | ENCLOSURE CLASS  |              |                     |       |
| <b>I/P CONVERTER</b>   | INPUT SIGNAL   | POWER SUPPLY | PART OF POSITIONER. |       |
|  | SPLIT RANGE  |              |                     |       |
|  | ENCLOSURE CLASS  |              |                     |       |
|  | LINEARITY  |              |                     |       |
|  | HYSTERESIS   |              |                     |       |
| <b>Cu. Tubing &amp; Fittings / per CV</b>  | 25 Meters of ¼ " PVC coated Cu. Tubing, with 1 set of Fittings for connection to IA Header on one end and accessories on another end of CV |              |                     |       |
|  |  |              | COMPANY SEAL        |       |
|  |  |              | NAME                |       |
|  |  |              | SIGNATURE           |       |
|  |  |              | DATE                |       |


|   |   |                      |             |   |                               |               |
|---|---|----------------------|-------------|---|-------------------------------|---------------|
|    | <b>TITLE</b><br><br><b>DATA SHEET - C</b><br><br><b>STEAM DESUPERHEATER</b> |                      |             |   | SPEC. NO.: PE-TS-391-142-N101 |               |
|   |   |                      |             |   | VOLUME III PART -A            |               |
|   | SHEET 1 OF 2  |                      |             |   |                               |               |
| <b>INSTRUCTIONS TO BIDDER</b> 1. This data sheet shall be read in conjunction with specification No. PES - 148 - 01 Section - D, Volume - II B.<br>2. Items which deviate from specification shall be marked with an asterisk (*)<br>3. This data sheet shall be submitted alongwith bid. |   |                      |             |   |                               |               |
| SL.NO.  | ITEM  | UNIT                 | PARTICULARS |   |                               |               |
| 1.0   | TYPE OF DESUPERHEATER   | -                    |             |   |                               |               |
| 2.0   | MODEL NO.   | -                    |             |   |                               |               |
| 3.0   | NUMBER OFFERED NOS.   |                      |             |   |                               |               |
| 4.0   | FLOW CAPACITY (OUTLET OF DESUPERHEATER)                                     | T/HR                 |             |   |                               |               |
| 5.0   | STEAM PARAMETERS AT INLET   |                      |             |   |                               |               |
| 5.1   | PRESSURE  | KG/CM <sup>2</sup> A |             |   |                               |               |
| 5.2   | TEMPERATURE   | °C                   |             |   |                               |               |
| 5.3   | FLOW T/HR   |                      |             |   |                               |               |
| 6.0   | STEAM PARAMETERS AT OUTLET  |                      |             |   |                               |               |
| 6.1   | PRESSURE  | KG/CM <sup>2</sup> A |             |   |                               |               |
| 6.2   | TEMPERATURE   | °C                   |             |   |                               |               |
| 7.0   | SPRAY WATER PARAMETERS  |                      |             |   |                               |               |
| 7.1   | PRESSURE  | KG/CM <sup>2</sup> A |             |   |                               |               |
| 7.2   | QUANTITY  | T/HR                 |             |   |                               |               |
| 8.0   | DESIGN PARAMETERS OF DESUPERHEATER BODY                                     |                      |             |   |                               |               |
| 8.1   | PRESSURE  | KG/CM <sup>2</sup> G |             |   |                               |               |
| 8.2   | TEMPERATURE   | °C                   |             |   |                               |               |
| 9.0   | DESIGN PRESSURE OF SPRAY NOZZLE   | KG/CM <sup>2</sup> G |             |   |                               |               |
| 10.0  | TYPE OF SPRAY NOZZLE  |                      |             |   |                               |               |
| 10.1  | FIXED / VARIABLE AREA ORIFICE   |                      |             |   |                               |               |
| 10.2  | SINGLE HOLE / MULTI HOLE  |                      |             |   |                               |               |
| Name of Bidder / Vendor   |   |                      |             |   | Project                       |               |
| Revision Number   |   | 0                    | 1           | 2 | 3                             | BIDDER'S SEAL |
| Signature of Bidder / Vendor / Authorised Representative  |   |                      |             |   |                               |               |
| Date  |   |                      |             |   |                               |               |


|  |   |                      |             |   |                                      |               |
|--|---|----------------------|-------------|---|--------------------------------------|---------------|
|   | <p align="center"><b>TITLE</b></p> <p align="center"><b>DATA SHEET - C</b></p> <p align="center"><b>STEAM DESUPERHEATER</b></p> |                      |             |   | SPECIFICATION NO. PE-TS-391-142-N101 |               |
|  |   |                      |             |   | VOLUME III PART -A                   |               |
|  |   |                      |             |   | SHEET 2 OF 2                         |               |
| <p>INSTRUCTIONS TO BIDDER</p> <p>1. This data sheet shall be read in conjunction with specification No. PES - 148 - 01 Section - D, Volume - II B.</p> <p>2. Items which deviate from specification shall be marked with an asterisk (*)</p> <p>3. This data sheet shall be submitted alongwith bid.</p> |   |                      |             |   |                                      |               |
| SL.NO.   | ITEM  | UNIT                 | PARTICULARS |   |                                      |               |
| 11.0   | NUMBER OF SPRAY NOZZLE / TURNDOWN RATIO   |                      |             |   |                                      |               |
| 12.0   | SPRAY WATER NOZZLE CHARACTERISTICS  |                      |             |   |                                      |               |
| 13.0   | SIZE OF ORIFICE   | MM                   |             |   |                                      |               |
| 14.0   | MIN. VELOCITY ACCEPTABLE IN THE DESUPERHEATER PIPE  | M/SEC                |             |   |                                      |               |
| 15.0   | END CONNECTIONS TYPE & SIZE   |                      |             |   |                                      |               |
| 15.1   | DESUPERHEATER INLET / OUTLET  |                      |             |   |                                      |               |
| 15.2   | SPRAY WATER INLET   |                      |             |   |                                      |               |
| 16.0   | MATERIAL OF CONSTRUCTION  |                      |             |   |                                      |               |
| 16.1   | BODY  |                      |             |   |                                      |               |
| 16.2   | SPRAY NOZZLE  |                      |             |   |                                      |               |
| 17.0   | OVERALL DIMENSIONS  | MM                   |             |   |                                      |               |
| 18.0   | WEIGHT OF DESUPERHEATER   | KG                   |             |   |                                      |               |
| 19.0   | MOUNTING RECOMMENDATIONS (IF ANY)   |                      |             |   |                                      |               |
| 20.0   | DESIGN CODE   |                      |             |   |                                      |               |
| 21.0   | HYDRAULIC TEST PRESSURE   | KG/CM <sup>2</sup> G |             |   |                                      |               |
| Name of Bidder / Vendor  |   |                      |             |   | Project                              |               |
| Revision Number  |   | 0                    | 1           | 2 | 3                                    | BIDDER'S SEAL |
| Signature of Bidder / Vendor / Authorised Representative   |   |                      |             |   |                                      |               |
| Date   |   |                      |             |   |                                      |               |

**CHECKLIST — LIST OF SCHEDULES**

| Sl. No.   | Form No.  | Description  | Tick Applicable Forms |
|---|-----------|--|-----------------------|
| 1.  | PEM-6024  | Schedule of Drawings / Catalogues submitted with Bid                       | ✓                     |
| 2.  | PEM-6025@ | Schedule of Occurance of Key Events of Delivery,Erection& Commissioning    |                       |
| 3.  | PEM-6026  | Schedule of Equipment Manufacture, Despatch and Shipment to Site.          | ✓                     |
| 4.  | PEM-6027  | Schedule of Weights & Dimensions   | ✓                     |
| 5.  | PEM-6028@ | Schedule of Performance Guarantee  |                       |
| 6.  | PEM-6030  | Inspection Schedule  | ✓                     |
| 7.  | PEM-6031  | Schedule of Cement and Steel and Quarterly Cement Requirement              |                       |
| 8.  | PEM-6032  | Schedule of Quarterly Requirement of Reinforcing Bars and Structural Steel |                       |
| 9.  | PEM-6033@ | Bill of Quantities (Civil Works)   |                       |
| 10.   | PEM-6035  | Schedule of Bidder's Proposed Construction / Site Fabrication Facilities.  |                       |
| 11.   | PEM-6036  | Schedule of Deviations   | ✓                     |
| 12.   | PEM-6040  | Schedule of Declaration  | ✓                     |
| 13.   | PEM-6041  | Quality Plan   | ✓                     |
| 14.   | PEM-6042  | Vendor's Drawings / Documents Schedule                                     | ✓                     |
| 15.   | PEM-6043@ | Schedule of Occurance of Key Events for Civil / Structural Works           |                       |
| 16.   | PEM-6046  | Inspection Request   | ✓                     |
| 17.   | PEM-6051  | Schedule of Prices   | ✓                     |
| 18.   | PEM-6052@ | Schedule of Unit Prices  | ✓                     |
| 19.   | PEM-6053  | Schedule of Prices for Commissioning & Mandatory Spares                    | ✓                     |
| 20.   | PEM-6054  | Schedule of Prices for Recommended Spares                                  | ✓                     |
| 21.   | PEM-6055  | Schedule Prices for Erection and Maintenance Tools & Tackles               | ✓                     |
| 22.   | PEM-6056  | Schedule of Bidder's Man-power for Supervision of E & C and their Charges. | ✓                     |
| 23.   | PEM-6057  | Schedule of Daily & Overtime Rates   |                       |
| 24.   | PEM-6058  | Schedule of Hire-charges for Construction / Site Fabrication Facilities    |                       |
| For Forms marked with @ certain information to be filled by DEs - before issuing to bidder. |           |  |                       |

|   |  |           |  |                     |
|---|--|-----------|--|---------------------|
|    | TITLE<br><br><b>SCHEDULE OF DRAWINGS /<br/>CATALOGUES SUBMITTED WITH BID</b> |           | SPECIFICATION NUMBER <b>PE-TS-391-142-N101</b> |                     |
|   |  |           | VOLUME III                  PART - A           |                     |
|   |  |           | SHEET ..... OF .....                           |                     |
| Section C/D enclosed with the specification indicate the drawings / catalogues to be furnished with the bid. The bidder in addition to furnishing the same, can also include any other drawings / catalogues which he may desire to submit with the bid. This schedule duly lists out such drawings as enclosed by the bidder with the bid. |  |           |  |                     |
| DRAWING./<br>CATALOGUE<br>NUMBER  | DESCRIPTION  |           |  | NUMBER<br>OF SHEETS |
|   |  |           |  |                     |
| PARTICULARS OF BIDDER / AUTHORISED REPRESENTATIVE   |  |           |  | COMPANY SEAL        |
|   |  |           |  |                     |
| NAME  | DESIGNATION  | SIGNATURE | DATE   |                     |

|  |  |   |  |   |              |
|--|--|---|--|---|--------------|
|   | <b>TITLE</b><br><b>SCHEDULE OF EQUIPMENT,<br/>MANUFACTURE, DESPATCH AND<br/>SHIPMENT TO SITE</b> |   |  | <b>SPECIFICATION NUMBER</b> <b>PE-TS-391-142-N101</b>                         |              |
|  |  |   |  | <b>VOLUME III</b> <b>PART - A</b>   |              |
|  |  |   |  | <b>SHEET</b> ..... <b>OF</b> .....  |              |
| Equipment / Major Bought-out Items   | Time for Manufacture/ Procurement from Date of Issue of Letter of Intent (Weeks)                 | Time for Test, Dismantling Packing & Ready for Despatch (Weeks) | Time required for Shipment to Site (Weeks) | Total Time from Date of Issue of Letter of Intent to Shipment to Site (Weeks) |              |
|  |  |   |  |   |              |
| We, the undersigned hereby undertake to meet the above time schedule in weeks for manufacture, despatch and shipment of each equipment and procurement of major boughtout items as listed above. |  |   |  |   |              |
| PARTICULARS OF BIDDER / AUTHORISED REPRESENTATIVE  |  |   |  |   | COMPANY SEAL |
|  |  |   |  |   |              |
| NAME   | DESIGNATION  | SIGNATURE   | DATE                                       |   |              |

|   |  |                        |  |                    |
|---|--|------------------------|--|--------------------|
|                                      | TITLE<br><br><h2 style="text-align: center;">SCHEDULE OF WEIGHTS &amp; DIMENSIONS</h2> |                        | SPECIFICATION NUMBER <b>PE-TS-391-142-N101</b> |                    |
|   |  |                        | VOLUME III    PART - A                         |                    |
|   |  |                        | SHEET ..... OF .....                           |                    |
| The bidder shall state below the weights and dimensions of various packages for shipment covering the complete scope. |  |                        |  |                    |
| Description of Package(s)   |  | Dimensions (in meters) |  | Weight (in tonnes) |
|   |  |                        |  |                    |
|   |  |                        |  |                    |
|   |  |                        |  |                    |
|   |  |                        |  |                    |
| PARTICULARS OF BIDDER / AUTHORISED REPRESENTATIVE   |  |                        |  |                    |
|   |  |                        |  |                    |
|   |  |                        |  |                    |
| NAME  | DESIGNATION  | SIGNATURE              | DATE   | COMPANY SEAL       |



## INSPECTION SCHEDULE

SPECIFICATION PE-TS-391-142-N101  
NUMBERP.O.  
NUMBER

VOLUME - III PART-A


SHEET OF

| S.<br>No. | ITEM / COMPONENT | PLACE & ADDRESS OF TEST / INSPECTION | Scheduled<br>Date of<br>Inspection | Duration of<br>Test /<br>Inspection<br>(in days) |
|-----------|------------------|--------------------------------------|------------------------------------|--|
|           |                  |                                      |                                    |  |

This schedule shall be in line with specification and quality plan requirements. The information in this form shall be furnished after receipt of LOI / PO.

| PARTICULARS OF VENDOR' s / AUTHORISED REPRESENTATIVE |           |      | COMPANY SEAL |
|--|-----------|------|--------------|
|  |           |      |              |
| NAME   | SIGNATURE | DATE |              |



|   |  |           |      |  |  |  |
|---|--|-----------|------|--|--|--|
|    | TITLE<br><b>* SCHEDULE OF DEVIATIONS</b><br>( ) From Conditions of Contract (Volume - I)<br>( ) From General Technical Conditions (Volume - II A)<br>( ) From Technical Specifications (Volume - II B) |           |      |  | SPECIFICATION NUMBER <b>PE-TS-391-142-N101</b> |  |
|   |  |           |      |  | VOLUME III PART - A                            |  |
|   |  |           |      |  | SHEET ..... OF .....                           |  |
|   |  |           |      |  |  |  |
| We the undersigned hereby certify that the above mentioned are the only deviations. |  |           |      |  |  |  |
| PARTICULARS OF BIDDER / AUTHORISED REPRESENTATIVE                                   |  |           |      |  |  |  |
|   |  |           |      |  |  |  |
| NAME  | DESIGNATION  | SIGNATURE | DATE |  |  |  |
|   |  |           |      |  | COMPANY SEAL                                   |  |



TITLE

SPECIFICATION NUMBER PE-TS-391-142-N101

VOLUME III PART - A

SHEET ..... OF .....

## \* SCHEDULE OF DECLARATION

## DECLARATION

I, ..... certify that all the technical data and information pertaining to this specification are correct and are true representation of the equipment/system covered by our formal proposal number Dated ..... and there is no deviation to the specification.

I hereby certify that I am duly authorised representative of the Bidder's company whose name appears above my signature.

Bidders Company Name

.....

Authorised representative's  
Signature

.....

Name

.....

Bidder's Intent

The bidder hereby agrees to fully comply with the requirements and intent of this specifications for the price indicated.

PARTICULARS OF BIDDER / AUTHORISED REPRESENTATIVE

|      |             |           |      |              |
|------|-------------|-----------|------|--------------|
|      |             |           |      |              |
|      |             |           |      |              |
| NAME | DESIGNATION | SIGNATURE | DATE | COMPANY SEAL |

\* Bidder shall include this schedule both in technical and Price offers.

## INSTRUCTIONS FOR FILLING QUALITY PLAN

(Form No. PEM-6042-0)

The Quality Plan shall include all the Quality Control Measures and Checks adopted by the Vendor to ensure that the material/component/assembly/services supplied by him meet/will meet the requirements as per specifications and good practices. They shall include all stages of operation such as materials, processes, manufacture, assembly, packing and despatch. The following guide lines may be noted:

|            |  |
|------------|--|
| Column 1-  | Serial Number  |
| Column 2-  | Component/Operation- The component and/or operation being checked shall be given here.   |
| Column 3-  | Characteristics check- The characteristics being checked shall be given here, e.g., chemical composition, mechanical properties, leak tightness, surface defects etc..   |
| Column 4-  | Category - 'CR' stands for critical characteristic - affecting safety of equipment and personnel<br>'MA' stands for major Characteristic - affecting safety of equipment and personnel<br>'MI' stands for minor characteristic - affecting appearance etc.   |
| Column 5-  | Type/Method of check e.g. chemical analysis tensile testing, hydraulic test, visual examination radiography etc.   |
| Column 6-  | Extent of check, such as, 100, 10, 1 per heat etc.   |
| Column 7-  | Reference Documents - Documents, such as technical specification, drawings, standard specifications (IS, BS ETC.) procedure, etc. according to which check is done.  |
| Column 8-  | Acceptance Norms - Standards etc. according to which acceptability or otherwise of the characteristics being checked is decided.   |
| Column 9-  | Format of Record - Formats, log shets, reports, etc. in which the observations are recorded. Standard log sheets, reports, formats etc. of the Vendors shall be numbered and such reference numbers shall be included here.  |
| Column 10- | Agency - The agency which performs the test/instruction shall be written in sub-column 'W'<br>The agency which verifies test certificates/inspection records and carries out audit check of the components/operation shall be written in sub-column 'V'<br>The agencies are codified '1' stands for (BHEL)<br>as 1,2 & 3 '1' * means the operation shall be cleared by BHEL before the start of the next operation.<br>'2' Stands for Vendor<br>'3' stands for sub-Vendor of the Vendor and so on. |

Example :

|            |  |
|------------|--|
| Entry      | '3' in column 'P' means test./inspection to be performed by sub-Vendor's QC  |
| Entry      | '2' in column 'W' means test./inspection to be witnessed by Vendor's QC  |
| Entry      | '1' in column 'V' means verification shall be done by BHEL and next stage to be started only after the hold point is cleared by BHEL |
| Column II- | Remarks - Any special remarks shall be given here.   |

NOTES :

- In absence of correlation with the test certificate(s) (e.g. material identification) samples shall be drawn bgy BHEL and all tests as per relevent specifications shall be carried out in their presence or in recognized Government Laboratory.
- When materials and components are initially identified and stamped by BHEL QS engineer, the identification marks shall be presserved till despatch. Wherever this is not possible, the identification mark shall be transferred to the components in the presence of BHEL QS Engineer unless other wise agreed.
- For castings and forgings integral test specimens shall be provided, When this is not possible for casting, they shall be poured in the presence of BHEL QS Engineer unless otherwise, if witnessing of test by BHEL is called for.
- When welders qualified by reputed inspection agencies or statutory bodies are not available, qualification tests shall be conducted in the presence of BHEL QS Engineer.
- This Quality Plan is liable to be modified as per the requirements of approved drawings and changes in technical specifications/drawings. If there are contradictions in respect of column 7 & 8 between this Quality Plan and the approved drawings specifications, the latter shall prevail.
- Wherever inspection by BHELs Purchaser/Third Party/Statutory authorities are mandatory, this shall be compiled with.
- Inspection reports, log sheets, test reports/certificate. etc. shall be furnished to BHEL at the approproate stages or at the time of final inspection, as required.
- This Quality Plan is also applicable to spares, if any, under scope of supply of Vendor.
- The quality plan shall be submitted in septuplicate (7 Copies).

## INSPECTION REQUEST

( From Vendor to BHEL Inspection Agency )

**1 PROJECT TITLE:****2 NAME OF VENDOR:****3 BHEL'S LOI / PO NO:****DATE :****4 SYSTEM / ITEM DESCRIPTION****5 ITEMS BEING OFFERED FOR INSPECTION WITH SL. NO. AS PER LOI / PO / BILLING SCHEDULE****6 DESCRIPTION AND SL. NO. OF INSPECTION AS PER QUALITY PLAN****7 QUANTITY OFFERED FOR INSPECTION****8 PLACE OF INSPECTION (FULL ADDRESS AND NAME OF SUB-VENDOR, IF ANY)**

PLACE .....

ADDRESS .....

**9 CONTACT PERSON (FOR SL. NO. 8 ABOVE).**

NAME ..... DESIGNATION .....

TELEPHONE .....

FAX ..... TELEGRAM .....

TELEX .....

**10 THE FOLLOWING DOCUMENTS ARE APPROVED BY BHEL AND AVAILABLE AT PLACE OF INSPECTION**

(A) QUALITY PLAN (B) DRAWINGS (C) DATA SHEETS, CHARACTERISTIC CURVES ETC. (D) PLANT STANDARDS

**11 REQUIRED DATE OF INSPECTION ..... LIKELY DURATION (No of Working days).....**

WEEKLY OFF DAY ..... WORKING HOURS .....

(At least 15 days prior notice shall be given by the Vendor to Inspection Agency)

We hereby certify that the above items are complete in all respects and have been fully inspected/tested by us and are found to be as per technical specification/approved drawings /data sheets/characteristic curves and are acceptable to our QC department. The detailed inspection and test reports of our QC department are enclosed.

## VENDOR'S PARTICULARS

|      |             |           |       |      |              |
|------|-------------|-----------|-------|------|--------------|
| NAME | DESIGNATION | SIGNATURE | PLACE | DATE | COMPANY SEAL |
|------|-------------|-----------|-------|------|--------------|



TITLE

**AUXILIARY STEAM PRESSURE REDUCING  
& DESUPERHEATING STATION**

SPEC. NO.: PE-TS-391-142-N101

VOLUME **III**


SECTION **PART-B**

REV NO. **0** DATE 17.07.2014

SHEET **1** OF **1**

**VOLUME-III  
PART-B**

**PRICE SCHEDULES**


|   |   |                               |                 |
|---|---|-------------------------------|-----------------|
|  | TITLE<br><br><b>SCHEDULE OF PRICES<br/>AUXILIARY STEAM PRESSURE REDUCING<br/>&amp; DESUPERHEATING STATION</b> | SPEC. NO.: PE-TS-391-142-N101 |                 |
|   |   | VOLUME <b>III</b>             |                 |
|   |   | SECTION <b>PART-B</b>         |                 |
|   |   | REV NO. <b>0</b>              | DATE 17.07.2014 |
|   |   | SHEET 1 OF 1                  |                 |


| S.No. | Description of Works or Equipment/System  | Price<br>(in Lakhs of Rs.) |
|-------|---|----------------------------|
| 1.0   | Total price for design, manufacture, assembly, inspection, testing, packing and dispatch to site of auxiliary steam pressure reducing and desuperheating stations complete with desuperheaters, controls valves and all accessories including commissioning spares and special tools & tackles as specified and necessary as per technical specification PE-TS-391-142-N101 |                            |
| 2.0   | Recommended spares, item-wise break up with item-wise price to be given as per “Schedule of Recommended Spares” enclosed under Vol. III of technical specification- price not to be included in clause 1.0 above, Bidder to indicate the break up.  |                            |
| 3.0   | Optional price of supervision of erection and commissioning of equipments – prices not to be included in clause 1.0 above.  |                            |
|       | Indicate all duties, taxes etc. Stating whether included/excluded in above price.   |                            |

-Bidder shall furnish this price schedule in his price offer only.


.-


| PARTICULARS OF VENDOR’S/AUTHORISED REPRESENTATIVE |           |      |              |
|---|-----------|------|--------------|
|   |           |      |              |
| NAME  | SIGNATURE | DATE | COMPANY SEAL |


|   |   |  |                               |                                 |
|---|---|--|-------------------------------|---------------------------------|
|  | <b>TITLE</b><br><b>SCHEDULE OF UNIT PRICES</b><br><b>AUXILIARY STEAM PRESSURE REDUCING &amp; DESUPERHEATING STATION</b>   |  | SPEC. NO.: PE-TS-391-142-N101 |                                 |
|   |   |  | VOLUME <b>III</b>             |                                 |
|   |   |  | SECTION <b>PART-B</b>         |                                 |
|   |   |  | REV NO. <b>0</b>              | DATE 17.07.2014                 |
|   |   |  | SHEET OF                      |                                 |
| S.No.   | Item Description  |  |                               | Unit Price<br>(in Lakhs of Rs.) |
| 1.0   | Design, manufacture, inspection & testing, packing and delivery for site for following as specified in Technical specification PE-TS-391-142-N101:  |  |                               |                                 |
| 1.1   | Unit Price of Control valves (2X660 MW, OPGCL, JHARSUGUDA, ODISHA)<br>a) Combined Type Aux. Steam High Capacity Pr. Reducing Valve (ASV-22)<br>b) Low Capacity Pressure Reducing Valve (from CRH line) (ASV-26)<br>c) HC PRDS Control Spray Valve (CDV-151)<br>d) DESH-2 Control Spray Valve, (CDV-157)<br>e) Low Temperature desuperheater (DESH-2)<br>f) TGS Desuperheater (DESH-3)<br>g) Spray control valve to DESH-3, (CDV-93) |  |                               |                                 |
| 1.2   |   |  |                               |                                 |
| <b>Note</b>   |   |  |                               |                                 |
|   |   |  |                               |                                 |

|    |  | TITLE<br><br><b>* SCHEDULE OF PRICES FOR<br/>COMMISSIONING AND MANDATORY<br/>SPARES</b> |          |                                     |                      | SPECIFICATION NUMBER <b>PE-TS-391-142-N101</b> |                               |                        |                         |
|---|--|---|----------|-------------------------------------|----------------------|--|-------------------------------|------------------------|-------------------------|
|   |  |   |          |                                     |                      | VOLUME III                                     |                               |                        |                         |
|   |  |   |          |                                     |                      | SHEET ..... OF .....                           |                               |                        |                         |
| The bidder shall indicate here the quantity required for erection / commissioning and mandatory spares for equipment as listed in Section-C / Section - D. If the listed spares are not adequate, then the bidder shall indicate those and additional spares considered necessary by him. |  |   |          |                                     |                      |  |                               |                        |                         |
| Type  | Manufacturer's<br>Drawing No. / Part<br>of spare | Description   | Material | Quantity<br>per Unit /<br>Equipment | Quantity<br>Required | If set,<br>Nos.<br>Per set                     | Delivery<br>period<br>(Weeks) | Unit<br>Price<br>(Rs.) | Total<br>Price<br>(Rs.) |
| Erection and<br>Commissioning   |  |   |          |                                     |                      |  |                               |                        |                         |
| Mandatory Spares  |  |   |          |                                     |                      |  |                               |                        |                         |
| Additional Spares<br>Mandatory Erection / Commissioning   |  |   |          |                                     |                      |  |                               |                        |                         |
| PARTICULARS OF BIDDER / AUTHORISED REPRESENTATIVE   |  |   |          |                                     |                      |  |                               |                        |                         |
|   |  |   |          |                                     |                      |  |                               |                        |                         |
| NAME  | DESIGNATION                                      | SIGNATURE   | DATE     | COMPANY SEAL                        |                      |  |                               |                        |                         |



|    |  | TITLE<br><br><b>* SCHEDULE OF PRICES FOR<br/>RECOMMENDED SPARES</b> |          |                               |                      | SPECIFICATION NUMBER PE-TS-391-142-N101 |                         |                  |                   |
|---|--|---|----------|-------------------------------|----------------------|---|-------------------------|------------------|-------------------|
|   |  |   |          |                               |                      | VOLUME III                              |                         |                  |                   |
|   |  |   |          |                               |                      | SHEET ..... OF .....                    |                         |                  |                   |
| The bidder shall give below a list of spares recommended for three years (or as otherwise specified in section - C) for trouble free performance of the equipment / system offered. |  |   |          |                               |                      |   |                         |                  |                   |
| S. No.  | Manufacturer's Drawing No. / Part of spare | Description   | Material | Quantity per Unit / Equipment | Quantity recommended | If set, Nos. Per set                    | Delivery period (Weeks) | Unit Price (Rs.) | Total Price (Rs.) |
|   |  |   |          |                               |                      |   |                         |                  |                   |
| PARTICULARS OF BIDDER / AUTHORISED REPRESENTATIVE   |  |   |          |                               |                      |   |                         |                  |                   |
|   |  |   |          |                               |                      |   |                         |                  |                   |
| NAME  | DESIGNATION                                | SIGNATURE   | DATE     |                               |                      |   |                         |                  |                   |
|   |  |   |          |                               |                      |   | COMPANY SEAL            |                  |                   |

|  |  |                  |  |                   |
|--|--|------------------|--|-------------------|
|   | TITLE<br><br><b>SCHEDULE OF PRICE FOR ERECTION<br/>AND MAINTENANCE TOOLS &amp; TACKLES</b> |                  | SPECIFICATION NUMBER <b>PE-TS-391-142-N101</b> |                   |
|  |  |                  | VOLUME III                                     |                   |
|  |  |                  | SHEET ..... OF .....                           |                   |
| The bidder shall be give below the list of erection and maintenance tools and tackles as offered by him. This shall also include the customer's list of maintenance tools, if specified in Section - C / Section - D.  |  |                  |  |                   |
| S. No.   | Description of Tools & Tackles   | Quantity offered | Unit Price (Rs.)                               | Total Price (Rs.) |
|  |  |                  |  |                   |
| <b>NOTE :</b> The hire charges for vendor's equipment called for in this schedule shall include the cost of consumables, operation services, depreciation, wear and tear as well as vendor's over head and profit. (These rates will be payable by customer to the vendor, only if the customer's requires the use of this equipment for carrying out his own work out side the scope of this contract.) |  |                  |  |                   |
| PARTICULARS OF BIDDER / AUTHORISED REPRESENTATIVE  |  |                  |  | COMPANY SEAL      |
|  |  |                  |  |                   |
| NAME   | DESIGNATION  | SIGNATURE        | DATE   |                   |

|  |  |                                   |      |   |  |
|--|--|-----------------------------------|------|---|--|
|   | TITLE  |                                   |      | SPECIFICATION NUMBER PE-TS-391-142-N101 |  |
|  | <b>SCHEDULE OF BIDDER'S MAN POWER<br/>FOR SUPERVISION OF E &amp; C<br/>AND THEIR CHARGES</b> |                                   |      | VOLUME III                              |  |
|  |  |                                   |      | SHEET ..... OF .....                    |  |
| The bidder shall indicate below, designation-wise, the personnel required for supervision of erection and commissioning and their charges. |  |                                   |      |   |  |
| <b>SUPERVISION OF ERECTION</b>   |  |                                   |      |   |  |
| S. No.   | Designation  | Normal rate per day<br>of 8 hours |      | Overtime rate per hour                  |  |
|  |  |                                   |      |   |  |
| <b>SUPERVISION OF COMMISSIONING</b>  |  |                                   |      |   |  |
| Sl. No.  | Designation  | Normal rate per day<br>of 8 hours |      | Overtime rate per hour                  |  |
|  |  |                                   |      |   |  |
| PARTICULARS OF BIDDER / AUTHORISED REPRESENTATIVE  |  |                                   |      |   |  |
|  |  |                                   |      |   |  |
| NAME   | DESIGNATION  | SIGNATURE                         | DATE | COMPANY SEAL                            |  |