

NUCLEAR POWER CORPORATION OF INDIA LTD.
(A Government of India Enterprise)

SPECIFICATION NO. : PC – M – 963

REVISION NO. :

DATE OF ISSUE
(MONTH/YEAR)

TOTAL NO. OF PAGES
(Including Cover Sheet)

0	1						
Sept 2013	Feb 2014						
10	10						

TECHNICAL SPECIFICATION

FOR

**STAINLESS STEEL FLATS FOR GRIDS FOR
700 MWe PROJECT STEAM GENERATORS**

REF. USI NO. : 33111

	NAME	Designation	SIGNATURE	DATE
PREPARED BY	R.K.Gupta	ACE	Sd/-	11/09/2013
	Braham Prakash	ACE	Sd/-	11/09/2013
CHECKED BY	P.B.Rshikesan	ACE	Sd/-	12/09/2013
	D.Ganesh	ACE	Sd/-	12/09/2013
	M.R.S.Saxena	ACE	Sd/-	12/09/2013
REVIEWED BY	S.N.Kamath	CE	Sd/-	12/09/2013
	M.K.Sharma	CE	Sd/-	12/09/2013
APPROVED BY	U.C.Muktibodh	ED (Engg.)	Sd/-	14/09/2013

(For Revisions see Revision Control Sheet)

File Name : CD No.:

(i)
REVISION CONTROL SHEET

DOCUMENT TYPE : TECHNICAL SPECIFICATION
 NO. : PC – M – 963
 TITLE : TECHNICAL SPECIFICATION FOR
 STAINLESS STEEL FLATS FOR GRIDS FOR
 700 MWe PROJECT STEAM GENERATORS


REV. NO. & DATE	DESCRIPTION OF REVISION	PREPARED BY	CHECKED BY	REVIEWED BY	APPROVED BY
0 Sept 2013	Original (Pages : 10)	Sd/- R.K.Gupta Sd/- Braham Prakash	Sd/- P.B.Rshikesan Sd/- D.Ganesh Sd/- M.R.S.Saxena	Sd/- S.N.Kamath Sd/- M.K.Sharma	Sd/- U.C. Muktibodh
1 Feb 2014	General revision & Residual copper content added at page no 2 clause no 4	<i>R.K.Gupta</i> 13/2/14 R.K.Gupta <i>Braham Prakash</i> 03/02/14 Braham Prakash	<i>P.B.Rshikesan</i> 5/2/14 P.B.Rshikesan <i>D.Ganesh</i> 7/2/14 D.Ganesh <i>M.R.S.Saxena</i> 7/2/14 M.R.S.Saxena	<i>S.N.Kamath</i> 10/2/14 S.N.Kamath <i>M.K.Sharma</i> 14/02/14 M.K.Sharma	<i>U.C. Muktibodh</i> 12-02-2014 U.C. Muktibodh

(ii)

NPCIL PROPRIETARY

This document contains confidential and protected information and that the same are the intellectual property of Nuclear Power Corporation of India Limited.(NPCIL). No part of this document including notably any editorial elements, verbal and figurative marks and images included herein, shall be reproduced or transmitted or utilized or published or stored in any form or by any means now known or hereinafter invented, electronic, digital or mechanical, including photocopying, scanning, recording or by any information storage or retrieval system, without prior written permission from NPCIL, by any person or entity. Unauthorized use, disclosure or copying is strictly prohibited and may constitute unlawful act and can attract legal action.

This page has been kept intentionally blank

 एनपीसीआईएल NPCIL	NUCLEAR POWER CORPORATION OF INDIA LTD	
	ATOMIC POWER PROJECT	Page No. : 1 of 6
	<u>TECHNICAL SPECIFICATION</u>	
	STAINLESS STEEL FLATS FOR GRIDS FOR 700 MWe PROJECT STEAM GENERATORS	Rev. No. : 1

1.0 SCOPE


This specification establishes the technical requirements for the material, manufacture, inspection, examination, testing and supply of stainless steel flats to material designation No. 1.4550 according to DIN EN 10028-7 with supply condition m (o). All requirements given herein are the minimum requirements. Alternate equivalent material may be considered provided it is demonstrated that the above mentioned minimum requirements are met.

This specification is applicable for Steam Generators of 700MWe projects beyond RAPP-7, 8.

2.0 CONTENTS

The requirements of this Specification are presented under the following headings:

<u>Description</u>	<u>Section</u>
Scope	1.0
Contents	2.0
Process of Manufacture	3.0
Chemical Composition	4.0
Heat Treatment	5.0
Mechanical Properties	6.0
Corrosion Test	7.0
Roughness	8.0
Cleanliness	9.0
Straightness	10.0
General	11.0
Test Material	12.0
Dimensional Check	13.0
Procedures and Plans	14.0

 एनपीसीआईएल NPCIL	NUCLEAR POWER CORPORATION OF INDIA LTD	
	ATOMIC POWER PROJECT	Page No. : 2 of 6
	<u>TECHNICAL SPECIFICATION</u>	Rev. No. : 1

Quality Surveillance 15.0

Marking 16.0

Test Reports / Certificates 17.0

Packing and Shipment 18.0

Figure – 1 : Grid Flats

3.0 **PROCESS OF MANUFACTURE**

The flats are made by cold/hot drawing. Subsequently they are to be solution annealed, ground, pickled and passivated. The flats are to be straight without any warping or twisting. Tolerances indicated in the figure-1 of this specification are to be strictly adhered to.

4.0 **CHEMICAL COMPOSITION**

The chemical composition shall be as per DIN EN 10028-7 material no. 1.4550. Residual copper content shall not be more than 0.3%, as per product analysis.

5.0 **HEAT TREATMENT**

All the flats shall be solution annealed according to DIN EN 10028-7.

6.0 **MECHANICAL PROPERTIES**


The mechanical requirements are as per DIN EN 10028-7 material No. 1.4550. Unless otherwise specified, the tests shall be carried out as per ASTM A-370.

7.0 **CORROSION TEST**

Intergranular corrosion test shall be carried out on samples from each heat treated batch as per ASTM A-262 Case E with preceding sensitizing heat treatment at 650°C for 30 minutes.

8.0 **ROUGHNESS**

The flats shall be ground smoothly and the surface finish shall be $Ra \leq 0.8 \mu m$. The surface finish measurement shall be supported with a roughness measurement diagram.

 एनपीसीआईएल NPCIL	NUCLEAR POWER CORPORATION OF INDIA LTD	
	ATOMIC POWER PROJECT	Page No. : 3 of 6
	<u>TECHNICAL SPECIFICATION</u>	
	STAINLESS STEEL FLATS FOR GRIDS FOR 700 MWe PROJECT STEAM GENERATORS	Rev. No. : 1

9.0 **CLEANLINESS**

The external surface of the flats shall be clean and free from every type of contamination or impurity such as grease, oil, remnants of drying materials, decomposition products, cleaning medium etc. The flats shall also be free from ferritic and other external surface impurities.

10.0 **STRAIGHTNESS**

The individual flats shall be straight without any bow or weaviness. The maximum permissible bow and distortion are indicated in Figure-1.

11.0 **GENERAL**

Tears and other material breakages as well as macroscopic visible inclusions are not permissible.

12.0 **TEST MATERIAL**

Each heat treated batch shall be tested at the supplier's works. The supplier shall send one test flat of full length for each heat treated batch with clear identification to the particular lot along with the flats.

13.0 **DIMENSIONAL CHECK**


Each flat shall be visually examined & checked for dimensional conformity with Figure-1.

14.0 **PROCEDURES AND PLANS**

The following procedures and plans shall be submitted to the purchaser for review and approval in six copies each prior to start of manufacture.

- Manufacturing plan indicating the sequence of operations, testing, witness and hold points. Witness point signifies that the manufacturer will intimate date of actual performance of that activity to the purchaser sufficiently in advance so that purchaser can witness the performance of the activity.

However, in case purchaser is not present, the manufacturer can proceed with the job.

 एनपीसीआईएल NPCIL	NUCLEAR POWER CORPORATION OF INDIA LTD	
	ATOMIC POWER PROJECT	Page No. : 4 of 6
	<u>TECHNICAL SPECIFICATION</u>	
	STAINLESS STEEL FLATS FOR GRIDS FOR 700 MWe PROJECT STEAM GENERATORS	Rev. No. : 1

Hold point is similar to witness point except that in case of Hold Point the manufacturer can not proceed with the activity unless purchaser is present or has given written waiver to proceed without his presence.

- b) Heat treatment plan.
- c) Mechanical test procedures.
- d) Quality assurance plan.
- e) Surface treatment procedure.
- f) Intergranular corrosion test procedure.

15.0 **QUALITY SURVEILLANCE**

All material shall be subjected to quality surveillance by the Purchaser or his authorized agency during manufacture. The material shall not be supplied until the shipping release is given by the Purchaser or his authorized agency.


16.0 **MARKING**

16.1 The following shall be legibly marked on each flat by a vibro etcher.

- a) Heat No. / Melt No.
- b) Material specification and grade.
- c) Size and weight.
- d) Supply conditions.
- e) Inspection agency / Purchaser's seal.
- f) Manufacturer's name.

16.2 The following shall be legibly marked on each box before shipment.

- a) Purchase order number.
- b) Material specification
- c) Melt No.
- d) Heat treated lot number.
- e) Number of pieces.
- f) Dimensions.

 एनपीसीआईएल NPCIL	NUCLEAR POWER CORPORATION OF INDIA LTD	
	ATOMIC POWER PROJECT	Page No. : 5 of 6
	<u>TECHNICAL SPECIFICATION</u>	
	STAINLESS STEEL FLATS FOR GRIDS FOR 700 MWe PROJECT STEAM GENERATORS	Rev. No. : 1

g) Destination.

17.0 **TEST REPORTS / CERTIFICATES**

Four (4) copies of all test reports / certificates shall be sent to the Purchaser immediately after completion of tests / inspection, prior to shipment of material. One set of test reports / certificates shall be dispatched along with the material for each unit. The reports shall be submitted in bound volume.

The following reports shall be submitted.


- Chemical analysis.
- Mechanical test reports.
- Heat treatment charts.
- Intergranular corrosion test report.
- Visual and dimensional inspection report.
- Roughness measurement report with diagram.

Final documentation containing all the above shall also be submitted in soft form (pdf format) with proper indexing


18.0 **PACKING AND SHIPMENT**

The flats shall be packed in boxes according to uniform length and same heat treated lots. The individual flat shall be completely covered by plastic sheets and shall be separated from each other by suitable intermediate inserts made of paper or wood. The boxes shall contain moisture absorbents to prevent any ingress of moisture. The packing shall be worthy for sea transport. Adequate supports and bracings shall be provided to ensure that the flats do not bend or distort during handling & transportation. Materials for each unit shall be packed separately.


The supplier shall submit a packing specification/procedure to the Purchaser for review and approval prior to packing and shipment.

 एनपीसीआईएल NPCIL	NUCLEAR POWER CORPORATION OF INDIA LTD	
	ATOMIC POWER PROJECT	Page No. : 6 of 6
	TECHNICAL SPECIFICATION	
	STAINLESS STEEL FLATS FOR GRIDS FOR 700 MWe PROJECT STEAM GENERATORS	Rev. No. : 1

1.PROFILE AND SURFACE




3.STRAIGHTNESS



STRAIGHTNESS RELATED TO
ANY MEASURED LENGTH
= $0.1 \text{ IN } 1000$ OF MEASURED LENG

2.WAVINESS AND TWISTING




WAVINESS RELATED TO ANY MEASURED
LENGTH (L) ($>250 \text{ mm}$) = $0.1 \text{ IN } 1000$ (MAX)
OF MEASURED LENGTH.

TWISTING RELATED TO ANY MEASURED
LENGTH (L) ($>250 \text{ mm}$) = $0.3 \text{ IN } 1000$ (MAX)
OF MEASURED LENGTH

W = WIDTH OF STRIP

T = NOMINAL THICKNESS OF STRIP.

4.CONVEXITY



GRID FLATS

FIGURE-1